


Please type a plus sign (+) inside this box → 

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number

UTILITY PATENT APPLICATION TRANSMITTAL (Only for new nonprovisional applications under 37 CFR 1.53(b))	Attorney Docket No.	20308.702	Total Pages	204
	First Named Inventor or Application Identifier			
	Craig David Weissman, Gregory Vincent Walsh, Eliot Leonard Wegbreit			
	Express Mail Label No.	EMO33396108US		

APPLICATION ELEMENTS See MPEP chapter 600 concerning utility patent application contents.	ADDRESS TO: Assistant Commissioner for Patents Box Patent Application Washington, DC 20231
1. <input checked="" type="checkbox"/> Fee Transmittal Form (Submit an original, and a duplicate for fee processing) 2. <input checked="" type="checkbox"/> Specification [Total Pages <u>154</u>] (preferred arrangement set forth below) - Descriptive title of the Invention - Cross References to Related Applications - Statement Regarding Fed sponsored R&D - Reference to Microfiche Appendix - Background of the Invention - Brief Summary of the Invention - Brief Description of the Drawings - Detailed Description - Claim(s) (47) - Abstract of the Disclosure 3. <input checked="" type="checkbox"/> Drawing(s) (37 CFR 1.152) [Total Sheets <u>36</u>] 4. <input checked="" type="checkbox"/> Oath or Declaration [Total Pages <u>3</u>] a. <input checked="" type="checkbox"/> Newly executed (original or copy) b. <input type="checkbox"/> Copy from a prior application (37 CFR 1.63(d)) (for continuation/divisional with Box 17 completed) [Note Box 5 below] i. <input type="checkbox"/> DELETION OF INVENTOR(S) Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b). 5. <input type="checkbox"/> Incorporation By Reference (useable if Box 4b is checked) The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.	6. <input type="checkbox"/> Microfiche Computer Program (Appendix) 7. Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary) a. <input type="checkbox"/> Computer Readable Copy b. <input type="checkbox"/> Paper Copy (identical to computer copy) c. <input type="checkbox"/> Statement verifying identity of above copies 8. <input checked="" type="checkbox"/> Assignment Papers (cover sheet & documents(s)) 9. <input type="checkbox"/> 37 CFR 3.73(b) Statement [X] Power of Attorney (when there is an assignee) 10. <input type="checkbox"/> English Translation Document (if applicable) 11. <input type="checkbox"/> Information Disclosure [X] Copies of IDS Statement (IDS)PTO-1449 [X] Citations 12. <input type="checkbox"/> Preliminary Amendment 13. <input checked="" type="checkbox"/> Return Receipt Postcard (MPEP 503) (Should be specifically itemized) 14. <input checked="" type="checkbox"/> Small Entity [X] Statement filed in prior application, Statement(s) [X] Status still proper and desired 15. <input type="checkbox"/> Certified Copy of Priority Document(s) (if foreign priority is claimed) 16. <input checked="" type="checkbox"/> Other: Utility Patent Transmittal Letter

17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No. ____/____

16. CORRESPONDING ADDRESS

<input type="checkbox"/> Customer Number of Bar Code Label (Insert Customer No. or Attach bar code label here)		<input checked="" type="checkbox"/> Correspondence address below	
NAME	Kent R. Richardson		
ADDRESS	WILSON SONSINI GOODRICH & ROSATI 650 Page Mill Road		
CITY	Palo Alto	STATE	California
ZIP CODE	94304-1050		
COUNTRY	USA	TELEPHONE	(650) 493-9300
FAX	(650) 845-5000		

SUBMITTED BY

Typed or
Printed Name

Kent R. Richardson

Reg. Number 39,443

Signature

Date May 6, 1998

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

FEE TRANSMITTAL Note: Effective October 1, 1997. Patent fees are subject to annual revision.		Complete if Known		
		Application Number	Not Assigned	
		Filing Date	May 6, 1998	
		First Named Inventor	Craig David Weissman, Gregory Vincent Walsh, Eliot Leonard Wegbreit	
		Group Art Unit	Not Assigned	
TOTAL AMOUNT OF PAYMENT (\$)		814.00	Examiner Name	Not Assigned
			Attorney Docket Number	20308.702

METHOD OF PAYMENT (check one)		FEE CALCULATION (continued)																																																																																																																																																																																					
1. <input checked="" type="checkbox"/> The Commissioner is hereby authorized to charge indicated fees and credit any over payments to: Deposit Account Number: 23-2415 (20308.702) Deposit Account Name: Wilson Sonsini Goodrich & Rosati <input checked="" type="checkbox"/> Charge Any Additional Fee Required Under 37 CFR 1.16 and 1.17 <input type="checkbox"/> Charge the Issue Fee Set in 37 CFR 1.18 at the Mailing of the Notice of Allowance		3. ADDITIONAL FEES <table border="1"> <thead> <tr> <th>Large Entity Fee Code</th> <th>Large Entity Fee (\$)</th> <th>Small Entity Fee Code</th> <th>Small Entity Fee (\$)</th> <th>Fee Description</th> <th>Fee Paid</th> </tr> </thead> <tbody> <tr><td>105</td><td>130</td><td>205</td><td>65</td><td>Surcharge - late filing fee or oath</td><td></td></tr> <tr><td>127</td><td>50</td><td>227</td><td>25</td><td>Surcharge - late provisional filing fee or cover sheet</td><td></td></tr> <tr><td>139</td><td>130</td><td>139</td><td>130</td><td>Non-English specification</td><td></td></tr> <tr><td>147</td><td>2,520</td><td>147</td><td>2,520</td><td>For filing a request for reexamination</td><td></td></tr> <tr><td>112</td><td>920*</td><td>112</td><td>920*</td><td>Requesting publication of SIR prior to Examiner action</td><td></td></tr> <tr><td>113</td><td>1,840*</td><td>113</td><td>1,840*</td><td>Requesting publication of SIR after Examiner action</td><td></td></tr> <tr><td>115</td><td>110</td><td>215</td><td>55</td><td>Extension for reply within first month</td><td></td></tr> <tr><td>116</td><td>400</td><td>216</td><td>200</td><td>Extension for reply within second month</td><td></td></tr> <tr><td>117</td><td>950</td><td>217</td><td>475</td><td>Extension for reply within third month</td><td></td></tr> <tr><td>118</td><td>1,510</td><td>218</td><td>755</td><td>Extension for reply within fourth month</td><td></td></tr> <tr><td>128</td><td>2,060</td><td>228</td><td>1,030</td><td>Extension for reply within fifth month</td><td></td></tr> <tr><td>119</td><td>310</td><td>219</td><td>155</td><td>Notice of Appeal</td><td></td></tr> <tr><td>120</td><td>310</td><td>220</td><td>155</td><td>Filing a brief in support of an appeal</td><td></td></tr> <tr><td>121</td><td>270</td><td>221</td><td>135</td><td>Request for oral hearing</td><td></td></tr> <tr><td>138</td><td>1,510</td><td>138</td><td>1,510</td><td>Petition to institute a public use proceeding</td><td></td></tr> <tr><td>140</td><td>110</td><td>240</td><td>55</td><td>Petition to revive - unavoidable</td><td></td></tr> <tr><td>141</td><td>1,320</td><td>241</td><td>660</td><td>Petition to revive - unintentional</td><td></td></tr> <tr><td>142</td><td>1,320</td><td>242</td><td>660</td><td>Utility issue fee (or reissue)</td><td></td></tr> <tr><td>143</td><td>450</td><td>243</td><td>225</td><td>Design issue fee</td><td></td></tr> <tr><td>144</td><td>670</td><td>244</td><td>335</td><td>Plant issue fee</td><td></td></tr> <tr><td>122</td><td>130</td><td>122</td><td>130</td><td>Petitions to the Commissioner</td><td></td></tr> <tr><td>123</td><td>50</td><td>123</td><td>50</td><td>Petitions related to provisional applications</td><td></td></tr> <tr><td>126</td><td>240</td><td>126</td><td>240</td><td>Submission of Information Disclosure Stmt</td><td></td></tr> <tr><td>581</td><td>40</td><td>581</td><td>40</td><td>Recording each patent assignment per property (times number of properties)</td><td>40.00</td></tr> <tr><td>146</td><td>790</td><td>246</td><td>395</td><td>Filing a submission after final rejection (37 CFR 1.129(a))</td><td></td></tr> <tr><td>149</td><td>790</td><td>249</td><td>395</td><td>For each additional invention to be examined (37 CFR 1.129(b))</td><td></td></tr> <tr><td colspan="5">Other fee (specify)</td><td></td></tr> <tr><td colspan="5">Other fee (specify)</td><td></td></tr> <tr> <td colspan="4">* Reduced by Basic Filing Fee Paid</td> <td>SUBTOTAL (3) (\$)</td> <td>40.00</td> </tr> </tbody> </table>		Large Entity Fee Code	Large Entity Fee (\$)	Small Entity Fee Code	Small Entity Fee (\$)	Fee Description	Fee Paid	105	130	205	65	Surcharge - late filing fee or oath		127	50	227	25	Surcharge - late provisional filing fee or cover sheet		139	130	139	130	Non-English specification		147	2,520	147	2,520	For filing a request for reexamination		112	920*	112	920*	Requesting publication of SIR prior to Examiner action		113	1,840*	113	1,840*	Requesting publication of SIR after Examiner action		115	110	215	55	Extension for reply within first month		116	400	216	200	Extension for reply within second month		117	950	217	475	Extension for reply within third month		118	1,510	218	755	Extension for reply within fourth month		128	2,060	228	1,030	Extension for reply within fifth month		119	310	219	155	Notice of Appeal		120	310	220	155	Filing a brief in support of an appeal		121	270	221	135	Request for oral hearing		138	1,510	138	1,510	Petition to institute a public use proceeding		140	110	240	55	Petition to revive - unavoidable		141	1,320	241	660	Petition to revive - unintentional		142	1,320	242	660	Utility issue fee (or reissue)		143	450	243	225	Design issue fee		144	670	244	335	Plant issue fee		122	130	122	130	Petitions to the Commissioner		123	50	123	50	Petitions related to provisional applications		126	240	126	240	Submission of Information Disclosure Stmt		581	40	581	40	Recording each patent assignment per property (times number of properties)	40.00	146	790	246	395	Filing a submission after final rejection (37 CFR 1.129(a))		149	790	249	395	For each additional invention to be examined (37 CFR 1.129(b))		Other fee (specify)						Other fee (specify)						* Reduced by Basic Filing Fee Paid				SUBTOTAL (3) (\$)	40.00
Large Entity Fee Code	Large Entity Fee (\$)	Small Entity Fee Code	Small Entity Fee (\$)	Fee Description	Fee Paid																																																																																																																																																																																		
105	130	205	65	Surcharge - late filing fee or oath																																																																																																																																																																																			
127	50	227	25	Surcharge - late provisional filing fee or cover sheet																																																																																																																																																																																			
139	130	139	130	Non-English specification																																																																																																																																																																																			
147	2,520	147	2,520	For filing a request for reexamination																																																																																																																																																																																			
112	920*	112	920*	Requesting publication of SIR prior to Examiner action																																																																																																																																																																																			
113	1,840*	113	1,840*	Requesting publication of SIR after Examiner action																																																																																																																																																																																			
115	110	215	55	Extension for reply within first month																																																																																																																																																																																			
116	400	216	200	Extension for reply within second month																																																																																																																																																																																			
117	950	217	475	Extension for reply within third month																																																																																																																																																																																			
118	1,510	218	755	Extension for reply within fourth month																																																																																																																																																																																			
128	2,060	228	1,030	Extension for reply within fifth month																																																																																																																																																																																			
119	310	219	155	Notice of Appeal																																																																																																																																																																																			
120	310	220	155	Filing a brief in support of an appeal																																																																																																																																																																																			
121	270	221	135	Request for oral hearing																																																																																																																																																																																			
138	1,510	138	1,510	Petition to institute a public use proceeding																																																																																																																																																																																			
140	110	240	55	Petition to revive - unavoidable																																																																																																																																																																																			
141	1,320	241	660	Petition to revive - unintentional																																																																																																																																																																																			
142	1,320	242	660	Utility issue fee (or reissue)																																																																																																																																																																																			
143	450	243	225	Design issue fee																																																																																																																																																																																			
144	670	244	335	Plant issue fee																																																																																																																																																																																			
122	130	122	130	Petitions to the Commissioner																																																																																																																																																																																			
123	50	123	50	Petitions related to provisional applications																																																																																																																																																																																			
126	240	126	240	Submission of Information Disclosure Stmt																																																																																																																																																																																			
581	40	581	40	Recording each patent assignment per property (times number of properties)	40.00																																																																																																																																																																																		
146	790	246	395	Filing a submission after final rejection (37 CFR 1.129(a))																																																																																																																																																																																			
149	790	249	395	For each additional invention to be examined (37 CFR 1.129(b))																																																																																																																																																																																			
Other fee (specify)																																																																																																																																																																																							
Other fee (specify)																																																																																																																																																																																							
* Reduced by Basic Filing Fee Paid				SUBTOTAL (3) (\$)	40.00																																																																																																																																																																																		
2. CLAIMS Total Claims: 47 - 20 = 27 X 11 = 297.00 Independent Claims: 5 - 3 = 2 X 41 = 82.00 Multiple Dependent Claims: 0 X 270 = 0		1. FILING FEE <table border="1"> <thead> <tr> <th>Large Entity Fee Code</th> <th>Large Entity Fee (\$)</th> <th>Small Entity Fee Code</th> <th>Small Entity Fee (\$)</th> <th>Fee Description</th> <th>Fee Paid</th> </tr> </thead> <tbody> <tr><td>101</td><td>790</td><td>201</td><td>395</td><td>Utility filing fee</td><td>395.00</td></tr> <tr><td>106</td><td>330</td><td>206</td><td>165</td><td>Design filing fee</td><td></td></tr> <tr><td>107</td><td>540</td><td>207</td><td>270</td><td>Plant filing fee</td><td></td></tr> <tr><td>108</td><td>790</td><td>208</td><td>395</td><td>Reissue filing fee</td><td></td></tr> <tr><td>114</td><td>150</td><td>214</td><td>75</td><td>Provisional filing fee</td><td></td></tr> <tr> <td colspan="4">SUBTOTAL (1) (\$)</td> <td></td> <td>395.00</td> </tr> </tbody> </table>		Large Entity Fee Code	Large Entity Fee (\$)	Small Entity Fee Code	Small Entity Fee (\$)	Fee Description	Fee Paid	101	790	201	395	Utility filing fee	395.00	106	330	206	165	Design filing fee		107	540	207	270	Plant filing fee		108	790	208	395	Reissue filing fee		114	150	214	75	Provisional filing fee		SUBTOTAL (1) (\$)					395.00																																																																																																																																										
Large Entity Fee Code	Large Entity Fee (\$)	Small Entity Fee Code	Small Entity Fee (\$)	Fee Description	Fee Paid																																																																																																																																																																																		
101	790	201	395	Utility filing fee	395.00																																																																																																																																																																																		
106	330	206	165	Design filing fee																																																																																																																																																																																			
107	540	207	270	Plant filing fee																																																																																																																																																																																			
108	790	208	395	Reissue filing fee																																																																																																																																																																																			
114	150	214	75	Provisional filing fee																																																																																																																																																																																			
SUBTOTAL (1) (\$)					395.00																																																																																																																																																																																		
2. <input type="checkbox"/> Payment Enclosed: <input type="checkbox"/> Check <input type="checkbox"/> Money Order <input type="checkbox"/> Other		FEE CALCULATION <table border="1"> <thead> <tr> <th>Large Entity Fee Code</th> <th>Large Entity Fee (\$)</th> <th>Small Entity Fee Code</th> <th>Small Entity Fee (\$)</th> <th>Fee Description</th> <th>Fee Paid</th> </tr> </thead> <tbody> <tr><td>103</td><td>22</td><td>203</td><td>11</td><td>Claims in excess of 20</td><td></td></tr> <tr><td>102</td><td>82</td><td>202</td><td>41</td><td>Independent claims in excess of 3</td><td></td></tr> <tr><td>104</td><td>270</td><td>204</td><td>135</td><td>Multiple dependent claim</td><td></td></tr> <tr><td>109</td><td>82</td><td>209</td><td>41</td><td>Reissue independent claims over original patent</td><td></td></tr> <tr><td>110</td><td>22</td><td>210</td><td>11</td><td>Reissue claims in excess of 20 and over original patent</td><td></td></tr> <tr> <td colspan="4">SUBTOTAL (2) (\$)</td> <td></td> <td>379.00</td> </tr> </tbody> </table>		Large Entity Fee Code	Large Entity Fee (\$)	Small Entity Fee Code	Small Entity Fee (\$)	Fee Description	Fee Paid	103	22	203	11	Claims in excess of 20		102	82	202	41	Independent claims in excess of 3		104	270	204	135	Multiple dependent claim		109	82	209	41	Reissue independent claims over original patent		110	22	210	11	Reissue claims in excess of 20 and over original patent		SUBTOTAL (2) (\$)					379.00																																																																																																																																										
Large Entity Fee Code	Large Entity Fee (\$)	Small Entity Fee Code	Small Entity Fee (\$)	Fee Description	Fee Paid																																																																																																																																																																																		
103	22	203	11	Claims in excess of 20																																																																																																																																																																																			
102	82	202	41	Independent claims in excess of 3																																																																																																																																																																																			
104	270	204	135	Multiple dependent claim																																																																																																																																																																																			
109	82	209	41	Reissue independent claims over original patent																																																																																																																																																																																			
110	22	210	11	Reissue claims in excess of 20 and over original patent																																																																																																																																																																																			
SUBTOTAL (2) (\$)					379.00																																																																																																																																																																																		

SUBMITTED BY		Complete (if applicable)	
Typed or Printed Name	KENT R. RICHARDSON	Reg. Number	39,443
Signature		Date	May 6, 1998
		Deposit Account User ID	23-2415 (20308.702)

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

PATENT APPLICATION

IN RE PATENT APPLICATION OF)	
)	Examiner: Not yet assigned
Craig David Weissman, Gregory Vincent)	
Walsh, Eliot Leonard Wegbreit)	
)	
)	Group Art Unit: Not yet assigned
Application No.: Not Assigned)	
)	
Filing Date: Filed Herewith)	
)	
Title: <i>Method and Apparatus for</i>)	
<i>Creating a Well-Formed Database</i>)	
<i>System Using a Computer</i>)	
)	

POWER OF ATTORNEY BY ASSIGNEE
TO EXCLUSION OF INVENTOR UNDER 37 C.F.R. § 3.71
WITH REVOCATION OF PRIOR POWERS

Commissioner of Patents
and Trademarks
Washington, D.C. 20231

Sir:

The undersigned ASSIGNEE of the entire interest in the above-identified application for letters patent hereby appoints Paul Davis, Reg. No. 29,294; Mark A. Haynes, Reg. No. 30,846; David J. Weitz, Reg. No. 38,362; Kent R. Richardson, Reg. No. 39,443; Charles C. Cary, Reg. No. 36,764; George A. Willman, 41,378; Steven J. Benerofe, Reg. No. P-41,613; David Abraham, Reg. No. 39,554; John Bruckner, Reg. No. 35,816; Travis Dodd, Reg. No. P-42,491; U.P. Peter Eng, Reg. No. 39,666; Henry Groth, Reg. No. 39,696; Jinntung Su, Reg. No. P-42,174, and to prosecute this application and transact all business in the United States Patent and Trademark Office in connection therewith and hereby revokes all prior powers of attorney; said appointment to be to the exclusion of the inventors and the inventors' attorneys in accordance with the provisions of 37 C.F.R. § 3.71.

The following evidentiary documents establish a chain of title from the original owner to the Assignee:

X a copy of an Assignment attached hereto, which Assignment has been (or is herewith) forwarded to the Patent and Trademark Office for recording; or

__ the Assignment recorded on __, frames __/__.


Pursuant to 37 C.F.R. § 3.73(b) the undersigned Assignee hereby states that evidentiary documents have been reviewed and hereby certifies that, to the best of ASSIGNEE's knowledge and belief, title is in the identified ASSIGNEE.

Direct all telephone calls to Kent R. Richardson at (650) 354-4235.

Address all correspondence to:

Kent R. Richardson
WILSON SONSINI GOODRICH & ROSATI
A Professional Corporation
650 Page Mill Road
Palo Alto, CA 94304

ASSIGNEE: **EPIPHANY, INC.**

Name: 
(Signature)

Name: ELIOT L. WEGBREIT
(Print or Type)

Title: Chief Executive Officer

Date: 5/5/98

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application) PATENT APPLICATION
)
Inventor(s): Craig David Weissman, Gregory Vincent)
Walsh, Eliot Leonard Wegbreit)
)
)
Serial No: Not Assigned)
)
)
Filed: Filed Herewith)
)
)
Title: *Method and Apparatus for Creating a*)
Well-Formed Database System Using)
a Computer)
)

VERIFIED STATEMENT CLAIMING SMALL ENTITY STATUS
37 C.F.R. § 1.9(f) AND 1.27(c) - SMALL BUSINESS CONCERN

I hereby declare that I am:

____ The owner of the small business concern identified below.

X An official of the small business concern empowered to act on behalf of the concern identified below.

Name: Epiphany, Inc.

Address: 2300 Geng Road, Suite 200, Palo Alto, California 94303

I hereby declare that the above identified small business concern qualifies as a small business concern as defined in 13 C.F.R. § 121.12, and reproduced in 37 C.F.R. § 1.9(d), for purposes of paying reduced fees under Section 41(a) and (b) of Title 35 U.S.C. in that the number of employees of the concern, including those of its affiliates, does not exceed 500 persons. For purposes of this statement, (1) the number of employees of the business concern is the average over the previous fiscal year of the concern of the persons employed on a full-time, part-time or temporary basis during each of the pay periods of the fiscal year, and (2) concerns are affiliates of each other when either, directly or indirectly, one concern controls or has the power to control the other, or a third-party or parties controls or has the power to control both.

I hereby declare that rights under contract or law have been conveyed to and remain with the small business concern identified below with regard to the invention.

entitled: *Method and Apparatus for Creating a Well-Formed Database System Using a Computer*

by inventor(s): Craig David Weissman, Gregory Vincent Walsh, Eliot Leonard Wegbreit

described in:

X the Specification filed herewith
____ Application SC/Serial No. _____ filed _____
____ Patent No. N/A issued N/A

If the rights held by the above-identified small business concern are not exclusive, each individual, concern or organization having rights to the invention is listed below and no rights to the invention are held by any person, other than the inventor, who could not qualify as a small business concern under 37 C.F.R. § 1.9(d) or by any concern which would not qualify as a small business concern under 37 C.F.R. § 1.9(d) or a nonprofit organization under 37 C.F.R. § 1.9(e).

NAME: _____

ADDRESS: _____

☐ Individual ☐ Small Business Concern ☐ Nonprofit Organization

NAME: _____

ADDRESS: _____

☐ Individual ☐ Small Business Concern ☐ Nonprofit Organization


I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small business entity is no longer appropriate. (37 C.F.R. § 1.28(b)).

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.

Name of Person Signing: ELIOT L. WEGBREIT

Title of Person Signing: Chief Executive Officer

Address of Person Signing: 2300 Geng Road, Suite 200, Palo Alto, California 94303

Signature: 

Date: 5/5/98

* Note: Separate verified statements are required from each named person, concern or organization having rights to the invention averring to their status as small entities. (37 C.F.R. § 1.27).

Title 37, Code of Federal Regulations, § 1.9(c-f)

(c) An independent inventor as used in this chapter means any inventor who (1) has not assigned, granted, conveyed, or licensed, and (2) is under no obligation under contract or law to assign, grant, convey, or license, any rights in the invention to any person who could not likewise be classified as an independent inventor if that person had made the invention, or to any concern which would not qualify as a small business concern or a nonprofit organization under this section.

(d) A small business concern as used in this chapter means any business concern as defined by the Small Business Administration in 13 CFR 121.12. For the convenience of the users of these regulations, that definition states:

121.12 Small business for paying reduced patent fees. (a) Pursuant to Pub. L. 97-247, a small business concern for purposes of paying reduced fees under 35 U.S. Code 41 (a) and (b) to the Patent and Trademark Office means any business concern (1) whose number of employees, including those of its affiliates, does not exceed 500 persons and (2) which has not assigned, granted, conveyed, or licensed, and is under no obligation under contract or law to assign, grant, convey or license, any rights in the invention to any person who could not be classified as an independent inventor if that person had made the invention, or to any concern

which would not qualify as a small business concern or a nonprofit organization under this section. For the purpose of this section concerns are affiliates of each other when either, directly or indirectly, one concern controls or has the power to control the other, or a third party or parties controls or has the power to control both. The number of employees of the business concern is the average over the fiscal year of the persons of the fiscal year. Employees are those persons employed on a full-time, part-time or temporary basis during the previous fiscal year of the concern.

(e) A nonprofit organization as used in this chapter means (1) a university or other institution of higher education located in any country; (2) an organization of the type described in section 501(c)(3) of the Internal Revenue Code of 1954 (26 U.S.C. 501(c)(3)) and exempt from taxation under section 501(a) of the Internal Revenue Code (26 U.S.C. 501(a)); (3) any nonprofit scientific or educational organization qualified under a nonprofit organization statute of a state of this country (35 U.S.C. 201(i)); or (4) any nonprofit organization located in a foreign country which would qualify as a nonprofit organization under paragraphs (e)(2) or (3) of this section if it were located in this country.

(f) A small entity as used in this chapter means an independent inventor, a small business concern or a nonprofit organization.

Method and Apparatus for Creating a Well-Formed Database System Using a Computer

Inventors: Craig David Weissman, Greg Vincent Walsh and Eliot Leonard Wegbreit

Cross References to Related Applications

5 This application relates to the following group of applications. Each application in the group relates to, and incorporates by reference, each other application in the group. The invention of each application is assigned to the assignee of this invention. The group of applications includes the following.

10 United States patent application serial number XX/XXX,XXX, entitled "Method and Apparatus for Creating a Well-Formed Database System Using a Computer," filed XX/XX/XX, and having inventors Craig David Weissman, Greg Vincent Walsh and Eliot Leonard Wegbreit.

United States patent application serial number XX/XXX,XXX, entitled "Method and Apparatus for Creating and Populating a Datamart," filed XX/XX/XX, and having inventors Craig David Weissman, Greg Vincent Walsh and Lynn Randolph Slater, Jr.

15 United States patent application serial number XX/XXX,XXX, entitled "Method and Apparatus for Creating Aggregates for Use in a Datamart," filed XX/XX/XX, and having inventors Allon Rauer, Gregory Vincent Walsh, John P. McCaskey, Craig David Weissman and Jeremy A. Rassen.

20 United States patent application serial number XX/XXX,XXX, entitled "Method and Apparatus for Creating a Datamart and for Creating a Query Structure for the Datamart," filed XX/XX/XX, and having inventors Jeremy A. Rassen, Emile Litvak, abhi a. shelat, John P. McCaskey and Allon Rauer.

Copyright Notice

A portion of the disclosure of this patent document contains material which is subject to copyright protection. The copyright owner has no objection to the facsimile reproduction by any one of the patent disclosure, as it appears in the Patent and Trademark Office patent files or records, but otherwise reserves all copyright rights whatsoever.

The Field of the Invention

This invention relates to the field of databases. In particular, the invention relates to creating databases, and loading and accessing data in the databases.

Background of the Invention

Many different types of databases have been developed. On line transaction processing (OLTP) databases are examples of typical databases used today. OLTP databases are concerned with the transaction oriented processing of data. On line transaction processing is the process by which data is entered and retrieved from these databases. In these transaction-oriented databases, every transaction is guaranteed. Thus, at a very low level, the OLTP databases are very good at determining whether any specific transaction has occurred.

Another type of database is a data warehouse or datamart. A datamart transforms the raw data from the OLTP databases. The transformation supports queries at a much higher level than the OLTP atomic transaction queries. A data warehouse or a datamart typically provides not only the structure for storing the data extracted from the OLTP databases, but also query analysis and publication tools.

13000000
The advantage of datamarts is that users can quickly access data that is important to their business decision making. To meet this goal, datamarts should have the following characteristics. First, datamarts should be consistent in that they give the same results for the same search. The datamart should also be consistent in the use of terms to describe fields in the datamart. For example, "sales" has a specific definition, that when fetched from a database, provides a consistent answer. Datamarts should also be able to separate and combine every possible measure in the business. Many of these issues are discussed in the following book, Ralph Kimball, *The Data Warehouse Toolkit*, John Wiley and Sons, Inc., New York, NY (1996).

10 Multi-dimensional datamarts are one kind of datamart. Multi-dimensional datamarts rely on a dimension modeling technique to define the schema for the datamart. Dimension modeling involves visualizing the data in the datamart as a multi-dimension data space (e.g., image the data as a cube). Each dimension of that space corresponds to a different way of looking at the data. Each point in the space, defined by the dimensions, contains measurements for a particular combination of dimensions. For example, a three dimensional cube might have product, customer, and territory dimensions. Any point in that cube, defined by those three dimensions, will represent data that relates those three dimensions.

15 The data in the datamart is organized according to a schema. In a dimensional datamart, the data is typically organized as a star schema. At the center of a standard star schema is a fact table that contains measure data. Radiating outward from the fact table, like the points of a star, are multiple dimension tables. Dimension tables contain attribute data, such as the names of

customers and territories. The fact table is connected, or joined, to each of the dimension tables, but the dimension tables are connected only to the fact table. This schema differs from that of many conventional relational databases where many tables are joined. The advantage of such a schema is that it supports a top down business approach to the definition of the schema.

5 Present datamarts have a number of drawbacks that are now discussed. First, datamarts are typically difficult to build and maintain. This is because of the requirements that they be consistent and flexible. A related drawback of present day datamarts is that they do not allow the consultants of the datamart to make changes to the schema simply and easily. Because datamarts support very high level queries about the business processes in the business, they require a great
10 deal of consistency in the use of data from the OLTP systems. Additionally, the datamarts need to be very flexible to address changes in the types of high level queries supported. Changing typical datamarts require the changing of hundreds, or potentially thousands, of lines of SQL code. For example, if a fact column is added to a fact table, the change propagates throughout the datamart. These changes are typically implemented by hand, a very time consuming and
15 error prone process. As a result of the hand coding involved, it is quite possible to construct the database in an arbitrary fashion that does not conform to good rules for constructing datamarts. Thus, well-formed datamarts may not result.

Thus an improved data warehousing technology is desired.

A Summary of the Invention

One embodiment of the invention includes a method of defining a well-formed database system by defining the organization of the data in the database, and by defining the operations for that data. The definition can then be used to automatically create and populate the well-
5 formed database system. The well-formed database system conforms to rules of correctness and produces results that conform to the rules. The organization is defined by a data organization definition that specifies tables, their columns, and the relationships between tables. The operations define procedures that operate on the tables and the table columns. Importantly, the operations are defined along with the tables, columns, and relationships, so that the resulting
10 system is well-formed. Without this invention, database systems can be constructed in an arbitrary and inconsistent fashion which can result in an incorrectly constructed database system.

In some embodiments, when the database system is created, it automatically includes the following capabilities: foreign key tracking, automatic indexing, time and date information inclusion. By including some or all of such capabilities in the database system, the system will
15 operate to comply with the rules of correctness.

The following are aspects of various embodiments of the invention. The constructed well-formed database system can automatically guarantee the following. (1) Two columns related by a relational join will be from the same domain. (2) If table A has a many-to-one relationship to table B, then table A has a foreign key that corresponds to table B. (3) A many-to-many
20 relationship, between two tables A and B, is always expressed by an associative table that is created in a uniform way. For each unique many-to-many relationship, a unique value is created

in the associative table and reused whenever that many-to-many relationship occurs.

Denormalization is always done correctly. (4) Pulling information from one table to be put into another table, for access efficiency, is done correctly.

In some embodiments of the invention, the data organization definition includes a schema
5 description for a datamart. The datamart automatically includes the inclusion of transaction type
information and the mapping of source system keys. In these embodiments, the operation
definitions define one or more of the following sets of operations: datamart population
operations, aggregate creation and maintenance operations, query and result interface operations.

Although many details have been included in the description and the figures, the invention is
10 defined by the scope of the claims. Only limitations found in those claims apply to the invention.

A Brief Description of the Drawings

The figures illustrate the invention by way of example, and not limitation. Like references indicate similar elements.

Figure 1 illustrates a datamart system representing one embodiment of the invention.

5 Figure 2 illustrates an embodiment of a method of defining the datamart, loading the datamart, and then querying the data.

Figure 3 illustrates a schema used in the system of Figure 1 to define schemas for the datamart.

Figure 4 illustrates a schema used in the data extraction and loading process.

10 Figure 5 illustrates a runtime schema including aggregates.

Figure 6 illustrates a query mechanism and user interface schema.

Figure 7 through Figure 29 describe a user interface that can be used to define a schema, build a datamart, load the datamart, and query the datamart.

15 Figure 30 through Figure 36 describe a user interface that can be used by a consultant to set up the query interface for a user and to provide the reporting interface.

The Description

Table of Contents

	CROSS REFERENCES TO RELATED APPLICATIONS.....	1
	COPYRIGHT NOTICE	2
5	THE FIELD OF THE INVENTION	2
	BACKGROUND OF THE INVENTION	2
	A SUMMARY OF THE INVENTION.....	5
	A BRIEF DESCRIPTION OF THE DRAWINGS.....	7
	THE DESCRIPTION	8
10	TABLE OF CONTENTS.....	8
	INTRODUCTION TO THE DESCRIPTION	9
	DEFINITIONS	11
	DATAMART SYSTEM.....	12
15	<i>System Element List</i>	13
	<i>System Element Descriptions</i>	14
	Metadata Overview	14
	System Overview	16
	External Elements.....	18
20	EXAMPLE METHOD OF DEFINING AND USING THE DATAMART	20
	TOP LEVEL METADATA SCHEMA	24
	<i>Top Level Metadata List</i>	25
	<i>Top Level Metadata Descriptions</i>	26
	Fact Related Tables	26
	Dimension Related Tables.....	28
25	Semantic Instance Table.....	31
	Aggregate Related Tables.....	31
	Data Store Related Tables	33
	Cleansing Related Tables.	34
	Additional Tables	34
30	<i>Top Level Metadata Use</i>	35
	EXTRACTION METADATA.....	37
	<i>Extraction Metadata List</i>	37
	<i>Extraction Metadata Descriptions</i>	38
	Job Related Tables.....	38
35	Connector Related Tables.....	40
	Extraction Group Related Tables	42
	SQL Statement Related Tables.....	43
	Error Handling.....	44
	Data Semantic Related Tables	44
40	Data Store Related Tables	46

	<i>Extraction Metadata Use</i>	48
	<i>Further Discussion of Templates</i>	50
	<i>Examples</i>	51
	Additional Templates	52
5	RUNTIME METADATA	54
	<i>Runtime Metadata List</i>	56
	<i>Runtime Metadata Descriptions</i>	56
	<i>Time Navigation</i>	61
	QUERY MECHANISM METADATA	63
10	<i>Query Mechanism Schema List</i>	64
	<i>Query Mechanism Schema Metadata Descriptions</i>	64
	Ticksheets Metadata	64
	Measurement Metadata	67
	Filtering Metadata	68
15	Display Options Metadata	70
	USER INTERFACE EXAMPLE OF DEFINING METADATA	71
	<i>General Schema Definitions User Interface</i>	71
	<i>Extraction Interface Elements</i>	74
	<i>Additional Interface</i>	76
20	<i>End User Interface Definition and Example</i>	77
	ALTERNATIVE EMBODIMENTS	84
	THE CLAIMS	86
	THE ABSTRACT	98
	APPENDIX A	99

Introduction to the Description

The following describes a system according to various embodiments of the invention.

Generally, the system allows a consultant to define a well-formed datamart. The system includes tables and columns that conform to the definition of the datamart. The system also includes additional columns for foreign key tracking, source system key mapping, time and date tracking. The system has automatic indexing. The system enforces typing information about the data stored in the datamart. These additional features cause the datamart to operate in a consistent manner. One benefit of such consistent operation is that results are consistent in meaning from query to query.

Focusing on the datamart creation, the system allows a consultant to build a datamart from a schema definition and a definition of the sources of the data. From the schema definition, the system automatically builds the tables needed in the datamart. Also, from the schema definition, and the sources definition, the system can automatically extract the data from those sources.

5 Depending on the semantic meaning of the data, as defined by the schema definition, the system automatically converts the data from the sources into forms that are readily usable in the datamart. Once the datamart has been created, and the data has been loaded, users can then perform queries on the data.

10 As part of the datamart creation, the system allows the consultant to define aggregates for the datamart. The aggregates correspond to pre-computed query results for different types of queries. For example, an aggregate can be created for a query that asks for all sales, by region, by quarter. The corresponding aggregate table would include a set of rows that have the results for this query (e.g., each row includes the quarterly sales for each region). The aggregates are specified using the schema definition. This makes defining and changing aggregates relatively
15 simple.

To allow a user to query the datamart, the system includes an interface for defining what fields can be used by the user to query the datamart. Additionally, by allowing the consultant to define measure and related information, the system allows the consultant to specify how the results are to appear to the users.

20 The following description first presents a system level view of primarily one embodiment. Then, an example use of the system is presented. Next, the metadata used in the system is

described. This metadata description is broken into four parts: a top level description of the metadata used in defining schemas, a description of the metadata used during the extraction, a description of the metadata used while the datamart is running, and a description of the query interface metadata. Next, an example set of user interface screen shots illustrates how consultants can quickly and efficiently define schemas, aggregates, and query interfaces, and how users can query the datamart. Next, additional alternative embodiments are described.

Definitions

Datamart or Data Warehouse – is a database.

Schema – is a description of the organization of data in a database. Often, the schema is defined using a data definition language provided by a database management system. More abstractly, the schema can be the logical definition of a data model for use in a database.

Metadata – is data that defines other data. This is not the actual data in the datamart, but is the data that defines the data in the datamart.

Constellation – a grouping of dimension definitions, fact definitions, like-structured facts (all facts in a constellation have the same dimensional foreign keys), or stars, and other metadata definitions. Often the grouping relates to a business process (e.g., sales).

Fact Table – the central table of a star schema. It stores the numeric measurements of the business that is supplying the information to the datamart.

Measurement – is a piece of data in a fact table, or an arithmetic combination of data.

Dimension – the tables that link to the fact table in a star schema. The tables store the descriptions of the dimensions of the business. Examples of dimensions are product and territory.

Attributes – are the fields of a dimension table (e.g., product name, country name).

5 User – any end user who would normally wish to query a datamart, but would not usually be concerned with the implementation or maintenance of the datamart.

Consultant – is a person responsible for the creation and maintenance of a datamart.

Source System – is any computer system that holds the raw data used by the system.

Examples of such source systems are OLTP database systems.

10 Data Store – any data storage (physical or logical) from which data is received or to which data is stored. Examples of a data store are files, a database, etc.

Computer – is any computing device (e.g., PC compatible computer, Unix workstation, etc.). Generally, a computer includes a processor and a memory. A computer can include a network of computers.

15 Program – a sequence of instructions that can be executed by a computer. A program can include other programs. A program can include only one instruction.

Datamart System

Figure 1 illustrates a datamart system representing one embodiment of the invention. The system supports the creation of a well-formed datamart. This system allows consultants to use
20 metadata to define schemas for a datamart. From the definition of the schema, the system can automatically generate the tables in the datamart. Further, the system can automatically extract

the data from the source systems, perform conversions on that data and populate the datamart.

The system supports the automatic creation and processing of aggregates from aggregate definitions. The system also supports the creation of the query mechanisms from query definitions.

- 5 The following description first lists all the elements of Figure 1, then describes each of those elements, and then discusses how those elements operate together.

System Element List

Figure 1 includes the following elements: source systems 110, a system 100, a web server 186, a consultant computer 190, and a user computer 180. The system 100 includes the metadata 160, an enterprise manager 102, an extraction program 120, staging tables 130, a semantic
10 template conversion program 140, a datamart 150, an aggregate builder 170, and a query and reporting program 104. The metadata 160 includes the following data: schema definitions 161, connectors 162 (connectors are also referred to as extractors), semantic definitions 163, source system information 164, aggregate information 167, measurement information 168, and
15 query/reporting information 169. The user computer 180 is shown running a browser 182. The browser 182 includes a query/results interface 184. The consultant computer 190 shows the enterprise manager interface 192 which shows the metadata organization of the system 100.

System Element Descriptions

The following describes the metadata 160, then the other elements of the system 100, and finally, the elements that are external to the system 100. These elements are all described in greater detail below.

5 Metadata Overview

The metadata 160 includes many different types of data and information. This information can be broken down into information related to (1) the definition of the schema for the datamart 150, (2) the data needed during the extraction from the source systems 110 and loading of the datamart 150, and (3) the information used in the querying of the datamart 150 and supplying the
10 result sets. The relationships between the elements of the metadata 160 are described in greater detail below. However, the following provides brief descriptions of these elements.

The schema definitions 161 hold the definition of the schema for the datamart 150. Typically, a consultant, using the consultant computer 190, can interface with the enterprise manager 102 to define the schema definition 161 for the datamart 150. In particular, the
15 consultant can use the enterprise manager interface 192 to define a star schema for the datamart 150. This star schema is organized around the business processes of the business for which the datamart is being created. What is important is that the consultant can easily define a schema for the datamart 150 and that definition is kept in the schema definitions 161. From the schema
20 definitions 161, not only can the tables in the datamart 150 be generated, but also the automatic extraction and conversion of the data from the source systems 110 can be performed, aggregates are set up, and a query mechanism is generated.

The connectors 162, the semantic definitions 163, and the source system information 164, are all related to the extraction of the data from the source systems 110. The connectors 162 define the access routines for extracting the source systems data 110. The semantic definitions 163 define how that extracted data should be converted when it is loaded into the datamart 150. The semantic definitions 163 provide important advantages to the system 100. In particular, the semantic definitions 163 allow for a simplified definition of the datamart 150, consistent meaning of the data in the datamart 150, and allow for complex changes to the schema to be easily propagated to the datamart 150. The source system information 164 defines how to extract the data from the systems 110.

The aggregate information 167 defines how data in the datamart 150 is treated once it is extracted. The aggregate information 167 allows for the creation of aggregates. Aggregates are aggregations of various fields of data in the datamart 150. Aggregates support more complex and powerful queries to be executed on the datamart 150. The aggregates also improve the performance of the system during the querying process and allow for time navigation of the data in the datamart 150. Time navigation is the process of creating backlog result sets by hopping through date aggregates from the beginning of time in the datamart 150 to the present.

The measurement information 168 and the query/ reporting information 169 support the querying of the datamart 150. A measure is a piece of numeric data in the datamart 150 that is useful to a user. That is, individual fact columns from source systems can be very implementation specific. These columns may not correspond to what users would prefer to see. For example, a user may want to see a net price added with a total cost. However, the fact table

may only include the net price or the total cost. The measure information 168 allows the consultant to define the abstract notion of the calculation associated with the net price added to the total cost.

In some embodiments of the invention, the metadata 160 also includes security information.

- 5 The security information defines the level of access for various users to the various tables and fields in the datamart 150. This security information automatically restricts access to that data.

System Overview

The system 100 can be implemented on a network of computers running Windows NT and UNIX. The datamart 150 can be implemented on top of an Oracle (SQL Server, or ODBC)
10 database. However, this physical structure of the system 100 can be implemented in any number of ways, and the invention does not require this specific hardware configuration.

The enterprise manager 102 is a program that is responsible for supporting the definition of the schema, and the creation of the tables in the datamart 150 from the schema definitions 161. The enterprise manager 102 also controls the extraction program 120. (In some embodiments,
15 the extraction program 120 and the semantic template conversion program 140 are included in the enterprise manager 102). During the execution of the extraction program 120, the extraction program 120, the staging tables 130, the semantic template conversion 140, and the datamart 150 are all used. The extraction program 120 uses the connectors 162 and the source system information 164 to extract the information from the source systems 110. The extracted data is
20 loaded into the staging tables 130.

The staging tables 130 are temporary tables used to hold the source system data before performing any semantic conversions on that data. The staging tables 130 also allow for the conversion of the source system data prior to moving the data into the datamart 150.

Once the staging tables 130 have been loaded, the semantic definitions 163 can be accessed from the enterprise manager 102 to convert the information in the staging tables 130 to predefined data semantics. These predefined data semantics allow for powerful queries, consistency in the definition of the meaning of the data in the datamart 150, and allow for changes to be made to the schema. Generally, the semantic template conversion 140 takes data stored in the staging tables 130, performs a conversion of that data according to a corresponding semantic definition (defined in the schema definitions 161), and populates the datamart 150 with the converted data.

Importantly, the predefined data semantics substantially simplify the creation and population of the datamart 150. In previous systems, the consultant would have to implement all of the data manipulation and population programs by hand. By selecting a particular semantic definition for a particular fact, or dimension, in the schema, the consultant has automatically defined the access and manipulation for populating programs for that table. Allowing the consultant to select a predefined data semantic not only reduces the tedious coding previously required of the consultant, but also allows for the automatic insertion of foreign keys, transaction types, date, and other information into the schema, and therefore the datamart 150. This additional information causes the datamart 150 to be well-formed.

The aggregate builder 170, as mentioned above, aggregates data in the datamart 150 according to the aggregate information 167 and the schema definitions 161. The results of the aggregate builder 170 allow for more powerful and faster queries to be performed on the datamart 150.

5 The query/reporting program 104 supports the querying of the datamart 150 and presents results of those queries. The query and reporting process 104 uses the measurement information 168 and the query and reporting information 169, in addition to the schema definitions 161, to query the datamart 150 and provide that information to the web server 186. The query/reporting information 169 includes filters and form definitions. The filters allow the user to filter different fields out of the datamart 150. The forms allow the users to indicate which fields a user is particularly interested in.

The metadata 160, although including many different types of definitional data, importantly includes the schema definition 161 and the semantic definitions 163. The enterprise manager 102 can use the schema definitions 161 to build the tables in the datamart 150. Through the combination of these two pieces of metadata 160, the enterprise manager 102 can take data from a source system 110, perform semantic conversions on that data and populate the datamart 150. Thus, in some embodiments of the invention, the system includes only the schema definitions 161 and the semantic definitions 163.

External Elements

20 The source systems 110, as defined above, represent large databases from which data for the datamart 150 is pulled. Examples of such systems include large on line transaction processing

(OLTP) systems. Typically these source systems 110 are relational databases having multiple tables and relations between those tables. The source systems 110 do not generally support powerful queries that provide high level information about the business in which the source systems 110 are used. Thus, the system 100 is used to extract the data from the source systems 110 and to provide an improved schema for querying that data. In some embodiments, the source systems 110 include non-relational databases such as object databases. In other embodiments, the source systems 110 can include flat file systems or combined relational and object databases. What is important is the source systems 110 can provide data to the system 100 through the connectors 162 and the source system information 164.

The consultant computer 190 represents any computing device that allows a consultant to access the system 100. (Access to the system 100 can be through a network.) What is important is that the consultant computer 190 allows the consultant to interface with the enterprise manager 102. Note, that the enterprise manager 102 can run on the consultant computer 190.

The user can access the web server 186 through the user computer 180. In this example, the user computer 180 can access the web server 186 through an HTTP connection. The user computer 180 sends a file request to the web server 186. This file request represents a request for a query of the datamart 150. The web server 186 runs a Java program upon receiving the request. The query and reporting program 104 converts the information from the Java program into a query that the datamart 150 will understand. In one embodiment, the query/reporting program 104 converts the query into a set of SQL statements. The SQL statements are run

against the datamart 150. The results of the statements are processed and provided back to the user computer 180.

Example Method of Defining and Using the Datamart

Figure 2 illustrates an embodiment of a method of defining the datamart 150, loading the datamart 150, and then accessing the data in the datamart 150. This example can be broken into four subparts: a build datamart process 202, an extraction and loading process 204, a build aggregates process 205, and a query and reporting process 206. This example can be implemented using the system 100.

At block 210, a consultant uses the enterprise manager 102 to define the schema. The schema is defined using the metadata 160. This process is illustrated in greater detail in Figure 7 through Figure 35. Generally, defining the schema involves determining the business processes of the organization for which the system 100 is being implemented. The consultant then defines the star schema for those business processes. The star schema has a fact table and a number of dimensions. The consultant also defines from where the data in the schema is to be derived.

That is, the consultant defines from which fields and tables the information is to be extracted from the source systems 110. The consultant also defines how that data is to be put into the datamart 150. That is, the consultant associates each piece of data with a semantic meaning.

This semantic meaning defines how the data from the source system is to be manipulated and how it is to populate the datamart 150. At this point, the consultant can also define the

aggregates that can be used in the datamart 150.

Once the datamart 150 has been defined, it can then be automatically built. At block 220, the enterprise manager 102 generates table creation SQL statements according to the definition of the metadata. In one embodiment of the invention, block 220 is accomplished by performing queries on the schema definitions 161 to generate the fact table creation statements, the fact staging table creation statements, the dimension table creation statements, the dimension staging table creation statements, and the dimension mapping table creation statements. These tables are described in greater detail below. From the results of these queries, SQL CREATE TABLE statements are created. Importantly, the schema definitions 161 provide the information the enterprise manager 102 needs to build the datamart 150.

Note that this process can also be used to modify the schema of an existing datamart 150. Therefore, at block 220, the SQL tables being created will cause the existing datamart 150 to be modified without losing the data in the datamart 150.

At block 230, the enterprise manager 102 issues the table generation statements to the database upon which the datamart 150 is being created. That database creates the tables, which correspond to the datamart 150. After block 230, the build the datamart process 202 is complete.

Now the extraction process 204 can be performed. The extraction process 204 is run on a periodic basis to load data from the source systems 110 into the datamart 150. This process can be run multiple times for the datamart 150.

At block 260, the connectors 162 are used by the enterprise manager 102, and in particular, they are used by the extraction program 120 to extract the data from the source systems 110. The connectors 162 can include SQL statement templates (not to be confused with semantic

templates, as described below) for extracting data from the source systems 110. The extraction program 120 uses these templates, in addition to the source system information 164, to generate SQL statements. These SQL statements are issued to the source system 110 and the results are loaded into the staging tables 130. (The staging tables 130 had been created as a result of block 230.) Once the staging tables have been loaded, the data can then be moved into the datamart 150.

At block 270, the staging table data is moved into the datamart 150 using the semantic definitions 163. The semantic definitions 163 are templates for converting the staging tables 130 data according to predefined data semantics. These predefined data semantics, as described below, provide semantic meaning to the data being loaded from the staging tables 130. Note that the data from the staging tables 130, as processed by the semantic template conversion 140, is placed in the tables in the datamart 150.

Thus, the schema definition and the semantic definitions 163 are used to generate and populate the datamart 150 such that the datamart 150 is well-formed. Examples of the well-formedness of the datamart 150 are as follows. (1) Two columns related by a relational join will be from the same domain. (2) If table A has a many-to-one relationship to table B, then table A has a foreign key that corresponds to table B. (3) A many-to-many relationship, between two tables A and B, is always expressed by an associative table that is created in a uniform way. For each unique many-to-many relationship, a unique value is created in the associative table and reused whenever that many-to-many relationship occurs. Denormalization is always done correctly. (4) Pulling information from one table to be put into another table, for access

efficiency, is done correctly. Previous systems cannot guarantee such a well-formed database system because hand coding of the creation and population operations is required. This hand coding can easily introduce errors into datamart creation and population processes.

Once the extraction process 204 has completed, the aggregates can be built in the build aggregates process 205. The aggregates are tables of pre-calculated combinations of dimensions and facts. Importantly, they greatly increase the speed of queries. Generally, the aggregate definitions, stored in the aggregate information 167, are accessed and built using the aggregate definitions (which interface with the schema definitions). At block 275, the aggregate builder 170 accesses the metadata 160 to build the aggregates. Often, the aggregate building is done at night.

After aggregates are built, the querying and reporting process 206 can be performed. The querying and reporting process 206 can be performed anytime after the creation of the datamart 150. Importantly, when an aggregate is created, the appropriate operation for that aggregate is used. For example, revenue elements are added to produce an aggregate, while daily account balances are averaged to produce an aggregate.

At block 277, the consultant defines the query mechanism schema for the system 100. In particular, the consultant defines the query/reporting information 169 and the measurement information 168. These two pieces of metadata 160 allow the system 100 to report meaningfully consistent information to users. Also, the consultant is not burdened with having to hand create the possible reports.

At block 280, a query is generated. In one embodiment of the invention the query is generated at the query/reporting program 104. In other embodiments, the query can be generated at the user computer 180 through the HTTP, web server 186, Java coupling to the query/reporting program 104. What is important here is that some query is generated that can be used to access the datamart 150. Importantly because the schema definitions 161 are available to the query and reporting program 104, the user can be presented with forms from which a query can be easily and automatically generated.

At block 290, the answer set (the results) is created by the datamart 150. This answer set is then propagated back through the query/reporting program 104, and ultimately to the user computer 180. The results are formatted according to the query/reporting information 169.

Top Level Metadata Schema

As noted in the background, multi-dimensional datamarts use star schemas. The system 100 uses star schemas in a larger organization that allows for the sharing of dimension tables by sets of similar facts. This larger organization is called a constellation. Figure 3 illustrates a schema for the schema definitions tables that support constellations. (The schema of Figure 3 is labeled the schema for schema definitions 300.) That is, Figure 3 illustrates a schema used in the system 100 to define schemas for the datamart. Figure 3 also illustrates some of the aggregate information 167 schema.

The following describes the meaning of the various graphical elements in Figure 3 through Figure 5. Each box in the figure represents a table having one or more attributes. A first table having a diamond graphic extending to second table (with a dot on the end) indicates that that

second table has a foreign key pointing to the first table. This can be thought of as a parent child relationship.

It is important to remember that Figure 3 through Figure 5 illustrate the schema of the system used to generate and run the datamart 150. Rows in these tables define the schema for use in the datamart 150. From these rows, create table, table query, etc., commands are created. These commands are used to create the tables in the datamart 150 and to access that datamart.

Also, as mentioned previously, the datamart 150 is well-formed because, among other reasons, the system 100 automatically includes additional columns in the table created in the datamart 150. For example, source system key, foreign key, and time and date columns are automatically added (where appropriate). The rest of the elements of the system can then rely on the existence of these columns. This prevents, for example, the creation of an inconsistent schema where only some of the tables include date and time information.

The following first lists all of the elements in Figure 3 and then describes those elements and their relationships.

Top Level Metadata List

Figure 3 includes the following elements: a constellation 302, a fact table 304, a dimension base 306, a semantic instance 308, a fact column 310, a fact aggregate operator 312, a fact column number 314, a fact dimension cleansing 316, a dimension role 320, a degenerative number 322, a dimension role number 324, a dimension node 326, a dimension column 329, a dimension column number 321, a cleanse type 323, a cleanse map definition 327, a cleanse map 325, a physical type 330, a transaction string 332, a metacolumn 334, an actual table type 336, a

dimension base type 328, a special dimension base 391, an aggregate key operator 392, an aggregate dimension type 393, an aggregate dimension 344, an aggregate group 342, an aggregate fact 340, a aggregate dimension set 372, a dimension column set 370, a dimension column set definition 374, a fact index 380, a fact index definition 384, and a fact index number 382.

Top Level Metadata Descriptions

It is important to remember that the tables in Figure 3 are only used to define the schema in the datamart 150. Thus, a fact table 304 in Figure 3 is not the actual fact table in the datamart 150, but the definition of that fact table. Each row in a table corresponds to an instance of that table.

The constellation 302 defines the organization of the schema in the datamart 150. It is the top level table in the schema definition.

Fact Related Tables

The fact table 304 defines the metadata 160 table describing all of the fact tables within a given constellation 302. The attributes of the fact table 304 include a build aggregates flag, a cleanse flag, a constellation key, a description, a fact table key, a fact table name, and a truncate stage flag. Each attribute corresponds to a column in the fact table 304. The build aggregate flag indicates whether or not to build aggregates for a particular fact on the next execution of the aggregate builder 170. The cleanse flag is a flag that is used in many of the tables to obliterate the actual measures within a table in the datamart 150 (particularly useful in demonstrations of the system 100 where sensitive data would otherwise be revealed). The constellation key points

to the parent constellation 302 for a given fact table 304. The fact table name is the name of the fact table used in constructing the corresponding physical table names in the datamart 150. The truncate stage flag is used to indicate whether or not to truncate the fact staging table on the next extraction.

5 The fact column 310 lists all of the fact attributes within a single fact table 304. The fact column 310 includes a cleanse flag, a description, a fact aggregate operator, a fact column key, a fact column name, a fact column number, a fact table key, and a physical type. The fact aggregate operator is an SQL operator used to aggregate this fact column in the datamart 150. The fact column key is the primary key for the fact column. The fact column name is the
10 physical name of the fact column. The fact column number counts and orders the number of columns in the fact table. The fact table key points to the fact table to which the corresponding fact column belongs. The fact table key points to the fact table to which the fact column belongs. The physical type is the database type for the fact column. This type is a logical type and provides for independence of implementation of the datamart 150 from the underlying database
15 used.

The fact column number 314 and the fact aggregate operator 312 are used by the fact column 310. These have already been described in the context of the fact column 310.

The fact dimension cleanse table 316 has rows that indicate the dimension foreign keys in a fact that should be cleansed. The fact dimension cleanse table 316 includes a dimension role
20 key, a fact dimension cleanse key, and a fact table key. The dimension role key indicates that this dimension role 320 is part of the “group by” set for cleansing a fact table without distorting

trends in the data. The fact dimension cleanse key is the primary key for the fact dimension cleanse table 316. The fact table key is the fact table having its cleansing properties.

Dimension Related Tables

The dimension base 306 is the metadata 160 describing all the dimension tables that can be used in a given constellation 302. These dimension bases can then be used in multiple constellations. The dimension base 306 includes the following attributes: an aggregate key operator, a cleanse flag, a description, a dimension base key, dimension base name, a dimension base type, and a truncate stage flag. The aggregate key operator is an SQL operator used by the aggregate builder 170 to build aggregates from a dimension. The cleanse flag and description act similarly to those attributes in other tables. The dimension base key is the primary key for the dimension base 306. The dimension base name is the name of the base dimension used in constructing real tables in the datamart 150. The dimension base type indicates the type of a dimension base (either default or special (special includes “date” and “transaction type,” which are used by the system 100)). The truncate stage flag operates in the manner similar to other truncate stage flags.

The dimension column 329 defines the list of dimension attributes that are valid for a single base dimension 306 and inherited by a dimension usage. The dimension column 329 includes a cleanse label, a cleanse map key, a cleanse type, a description, a dimension base key, a dimension column key, a dimension column name, a dimension column number, a dimension number key, grouped by field, a physical type, a primary key, a time navigation field, and a default value. The cleanse label is a label presented to users after this column has been cleansed.

The cleanse map key is for use when cleansing using value mapping. The cleanse map key indicates the mapping group to use. The cleanse type is the method for cleansing the dimension column 329. The description is for documenting the dimension column 329. The dimension base key is the numbered base in which the column resides. The dimension column key is the primary key for the dimension column 329. The dimension column name is the physical name of the column. The dimension column number is the count of the dimension columns (to prevent too many from being created in the datamart 150). The dimension node key is the aggregate hierarchy group in which the column resides. The "group by" field is used for special dimensions to indicate whether or not this column needs to be "grouped by" during the processing by the aggregate builder 170. The physical type is a logical database type for this dimension column 329. The primary key is used in special dimensions to indicate whether or not this column is the primary key. The time navigation field is for the date special dimension to indicate whether or not time navigation should use this field. The default value is the default value for the dimension column.

The dimension column number 321 is a look up table for the valid number of dimension columns that can be created. The dimension column number counts the number of dimension columns to make sure there are not too many being defined by the consultant.

The dimension role 320 is a metadata 160 table that describes all of the dimension tables used in a constellation 302. The dimension role 320 includes a constellation key, a degenerative number, a description, a dimension base key, a dimension role key, a dimension role name, and a dimension role number. The constellation key points to the constellation 302 in which the

dimension role 320 resides. The degenerative number defines the order of degenerate columns within fact tables in a constellation. The description is a documentation field for describing a dimension role. The dimension base key is the dimension base that this dimension role refers to. The dimension role key is the primary key for the dimension role 320. The dimension role name is the name of the dimension role and is used when constructing the foreign keys in the fact tables in the datamart 150. The dimension role number defines the order of the dimension roles within a constellation. That is, a constellation may have multiple dimension roles and the dimension role number allows for an ordering of those dimension roles.

The dimension node 326 is a table used for defining and grouping hierarchical dimension attributes that are used by the aggregate builder 170. The dimension node includes a dimension base key, a dimension node key, a node name, a node number, and a parent node number. The dimension base key points to the dimension base being defined. The dimension node key is the primary key for the dimension node. The node name is the logical name for the aggregate hierarchy group being defined. The node number is the logical number for the aggregate hierarchy group being defined. The parent node number is a logical number for the parent of the aggregate hierarchy group being defined.

The degenerative number 322 and the dimension role number are defined as described in the dimension role 320.

The dimension base type 328 is defined as described in relation to the dimension base 306.

Semantic Instance Table

The semantic instance 308 is a single record that represents the manner in which a fact or dimension table is extracted from staging tables, manipulated, and then used to populate the corresponding table in the datamart 150. The semantic instance 308 includes an extraction node
5 key, dimension base key, a fact table key, a semantic instance key, and a semantic type key. The extraction node key points to the extraction node that a particular semantic instance belongs to. The dimension base key is the dimension base table owning this semantic instance. The fact table key points to the fact table owning this semantic instance. Only one of the dimension base key and the fact table key is filled in for a semantic instance 308 because the semantic instance
10 can only be applied to one or the other. The semantic instance key is a primary key for the semantic instance 308. The semantic type key is the indicator of the type of transformation necessary to construct this type of semantic instance in the datamart 150.

Aggregate Related Tables

The aggregate builder 170 is a program that uses the aggregate tables and the schema
15 definitions 161 to build aggregates. Often this will be done on a nightly basis.

The aggregate group 342 defines a set of aggregates to be built for a constellation. An aggregate group 342 will cause a combinatorial creation of many aggregate tables in the datamart 150. The consultant defines for which dimensions aggregates are to be built (e.g., the consultant will define that one, none, all, etc. columns of a dimension are to be aggregated on in an
20 aggregate group). The aggregate filtering done by the query and reporting program 104 will select the most appropriate aggregates for a given query.

1 The aggregate group 342 includes an aggregate group key, an aggregate group name, a
constellation key, a default flag, a description, and an enabled field. The aggregate group key is
the primary key for the aggregate group 342. The aggregate group name is the logical name of
this aggregate group. A constellation key points to the constellation in which this aggregate
5 group resides. The default flag indicates whether or not this group is the default group within a
constellation. Default groups have facts and dimensions automatically added to them. They can
also not be deleted. The description contains the documentation for this aggregate group. The
enabled field indicates whether or not the aggregate builder 170 will actually build this group.

10 The aggregate fact table 340 tracks the membership of a fact within an aggregate group. The
aggregate fact table 340 includes an aggregate fact key, an aggregate group key, and a fact table
key. The aggregate fact key is the primary key for the aggregate fact 340. The aggregate group
key is the aggregate group being defined by the aggregate fact. The fact table key points to the
fact table that is being made a member of the group.

15 The aggregate dimension 344 indicates the membership of a dimension within a constellation
in an aggregate group. The aggregate dimension 344 includes an aggregate dimension key, an
aggregate dimension type, an aggregate group key, a dimension role key, and a special
dimension base key. The aggregate dimension key is the primary key for the aggregate
dimension 344. The aggregate dimension type indicates the manner in which this dimension
(special or role) will be included in the aggregate group. The aggregate group key indicates the
20 aggregate group being defined. The dimension role key points to the dimension role being

included. It is possible that this key is null. The special dimension base key indicates the special dimension being included. The special dimension base key can also be null.

The aggregate key operator 392 is defined as described in the dimension base 306.

The fact aggregate operator 312 is a look up table of valid fact aggregation operations. Each
5 operator is an SQL operator used to aggregate a fact column.

A special dimension base 391 provides details about special built-in dimensions in the system 100. The special dimension base includes an "always include an aggregate" field, a default aggregate dimension type, a dimension base key, a list order in fact, a physical type of key, an index flag, and a special dimension base key. The "always include an aggregate" field
10 indicates whether or not this dimension table must always be included in all aggregates. The default aggregate dimension type is the default manner in which this dimension is included in aggregate groups. The dimension base key is the one to one relationship to a dimension base. The list order in fact is the order in fact tables that the foreign key to this table will be listed. The physical type of key is the logical database type that foreign keys in the fact tables that point to
15 this special dimension will be. The index flag is used in indexing. The special dimension base key is the primary key for the special dimension base 391.

Data Store Related Tables

The physical type 330 defines a look up table of logical data types that are relational database management system (RDBMS) independent. The physical type 330 is a logical data type that
20 works across various source systems storage types. The physical type 330 includes a database physical type, a default value, and a special type.

The translation string 332 defines a list of strings that are translated for different RDBMS's. The translation string is a logical string that can be converted to specific strings for different storage types. Each storage type would correspond to a different source system 110.

Cleansing Related Tables.

5 The cleanse type 323 is a look up table to indicate how to cleanse a dimension column.

The cleanse map 325 is a mapping table for mapping real names to cleanse names. The cleanse map 325 includes a cleanse map key, which is the primary key, and a cleanse map name, which is the name of a set of mapping pairs for the purpose of scrambling data.

The cleanse map definition 327 defines the details of what should be mapped to which fields.

10 The cleanse map definition 327 includes cleanse map character ID, a cleanse integer ID, a cleanse map definition key, a cleanse map key, and a cleanse value. The cleanse character ID is a character value for indexing into this mapping group. The cleanse integer ID is a numeric value for indexing into this mapping group. The cleanse map definition key is the primary key for the cleanse map definition. The cleanse map key is the mapping set to which this particular
15 cleanse map definition belongs. And the cleanse map value is the translation value after the mapping.

Additional Tables

The metacolumn 334 is a column that occurs by default in tables in the datamart 150. The metacolumn 334 includes an actual table type, a list order, a metacolumn key, a metacolumn
20 name, and a physical type. The actual table type indicates the type of physical table in which this special column should appear. The list order is the order this column occurs in tables of the

appropriate type. The metacolumn key is the primary key. The metacolumn name is the physical name of the column when it is used. The physical type is the logical data type for this column.

The actual table type 336 is a look up table for actual table types. Actual table types can be fact, dimension stage, fact stage, dimension map, or dimension.

The aggregate group 342, the aggregate fact 340, the aggregate dimension set 372, the dimension column set 370, the dimension column set definition 374, the fact index 380, the fact index definition 384, and the fact index number 382 are for future use and are therefore optional. Each of these tables provides greater flexibility when defining the metadata 160, improves the performance of the system 100, or may otherwise enhances the system 100.

Top Level Metadata Use

Now that all of the elements in Figure 3 have been listed and described, their relationships and workings are now described.

It is important to note that many of the tables in Figure 3 are actually used in providing layers of abstraction to allow for the reuse of information and non-abstract tables. Therefore, a consultant will often only deal with only some of the tables in the Figure 3. For the purposes of describing how the metadata 160 can be used to define a schema for the datamart 150, these grouping and levels of abstraction tables will be described where appropriate.

Generally, a consultant will create a new datamart 150 by defining instances of the dimension bases 306, and constellations 302. Each instance corresponds to a row in the dimensions bases 306 table or the constellation 302 table. The constellation instances are defined by defining

aggregates, dimensions, facts, measures, and ticksheets. The following describes the definition of a schema using the metadata 160. This corresponds to block 210 of Figure 2.

Beginning with the facts in a constellation, the consultant defines a fact table 304 row that will define the hub table in a star schema supported by the constellation. Again, it is important to remember that the fact tables in Figure 3 are for definitional purposes, and are not the real fact tables in the datamart 150. A row in the fact column 310 holds the details of what columns will be created for place holders of actual values in a corresponding fact table. Thus, for each fact, the consultant defines the various fact columns.

Once the facts have been defined, the consultant can then define the dimensions of the constellation.

Remember that the dimension base 306 holds the information to define the actual dimensions of the tables in the datamart 150. The dimension role 320 allows for the reuse of the dimension base tables. Thus, different dimension roles can refer to the same dimension base. This provides an important feature of some embodiments of the invention where the same dimension bases can be used in multiple constellations or within the same constellation. The dimension columns 329 define the columns on which queries can be performed in the datamart 150. The dimension node table 326 helps relate the dimension columns 329. Thus, the consultant will have defined the basic schema for the datamart 150.

The aggregate group 342 defines how particular facts or dimensions are to be aggregated by the aggregate builder 170. These aggregated facts provide much faster queries in the datamart 150.

The cleansing map tables are for scrambling the data in the datamart 150 for presentations to people who want to see the functionality of the system 100, without having to reveal the actual data in the datamart 150.

The special dimensions are the transaction type table and date values that are included in every fact table. Because this is included in every fact table, the system 100 can rely on the existence of the transaction type during the various stages of datamart 150 creation, modification, querying, and the like.

Thus, the elements of Figure 3 can be used to allow the consultant to define the schema definitions 161 for creating the tables in the datamart 150.

Extraction Metadata

The following describes the metadata 160 used in the extraction process 204. This metadata, represented as extraction schema 400, is shown in Figure 4. The extraction process focuses around the job and connector tables. In general, these tables define the various steps in extracting the source system data into the staging tables 130 and performing the desired semantic conversions on that data.

Extraction Metadata List

Figure 4 includes the following elements: a job 402, a job step 404, a system call 405, a connector 406, a connector time stamp 407, a connector step 408, a connector column latch 409, and an extraction group 411, an extraction note 410, an SQL statement 420, and error handling type 413, an external table 422, an external column 424, the physical type 330, the fact table 304,

a debug level 415, the semantic instance 308, a semantic type 430, a dimension semantic type 432, a fact semantic type 434, the actual table type 336, a semantic type definition 436, an adaptive template 438, and adaptive template block 439, the dimension base 306, a job log 401, a connector store role 448, a store role 446, a statement type enabled 428, a store role allow 444, a data store 440, a source system 442, a file store 441, and Oracle store 454, a store version 452, and SQL server store 456, and ODBC store 458, and a store type 450.

Extraction Metadata Descriptions

Job Related Tables

The job 402 is a top level object for controlling the work flow during the extraction and loading process 204. The job 402 includes a check databases field, a check tables field, a description, a label, an initial load flag, a job key, a job name, a log file width, a mail to on error, a mail to on success, and a truncate flag. The check databases field indicates whether or not an attempt should be made to log into all the data stores before executing the job. The check tables flag indicates whether or not to check for the existence of all the tables in the datamart before executing the job. The description is for documenting the job (usually done by the consultant). The enabled flag indicates whether or not a particular job can be run. The initial load flag indicates whether or not to ignore all previous time stamped constraints when running a particular job. The job key is the primary key for the job table 402. The job name is the internal name of the job. The log file width indicates how many characters wide to make rows in the log file output. The mail to on error, and the mail to on success indicate where E-mail messages

should be sent after failure or success of the particular job. The truncate flag indicates whether or not to truncate any tables when running a job.

The job log 401 is the locations where the running job is logged. That is, the location of the output that will be provided to the consultant indicating what occurred during the extraction (e.g., what errors occurred). The job log 401 includes a data store key, a job key, a job log key, and a job store role. The data store key indicates the data store having a role defined within the job. The job key is a reference to the particular job, the job log key is the primary key for the job log 401. The job store role is the role being assigned to that particular job log 401. An example job store role is "<working directory>," indicating the path to the working director where job log files are store.

The job step table 404 includes the detailed steps that make up a job. This includes connectors and system calls. The job step table 404 includes the following attributes: a connector key, a description, an enabled flag, a job key, a job step key, a list order, a phase, a job step type, and a system call key. The connector key indicates the connector being included in any particular job step. The connector key can be null. The description is for documenting the job step. The enabled flag indicates whether or not a particular step is enabled. The job key points to the job being defined by the job step 404. The job step key is the primary key. The list order indicates the order of a particular job step. The phase also indicates the order of a particular step. By supporting both list order and phase, alternative embodiments of the invention can support parallel extraction. Steps in the same phase can then be executed simultaneously. The job step type indicates the type of the job step (which are defined in the job

step type table 481). The system call key points to a system call included in a particular job step.

The system call key can be null.

The system call 405 is a table including external OS system calls. These external system calls can be used to perform any number of external system functions. The system call 405 includes the system call key, a command string, a description, a name, and an on-error type. The system call key is the primary key for the system call. The command string is the actual operating system command to be run as a result of the system call. The description is for documenting the system call. The name is the logical name of the system call being defined. The on error type is an indicator to point to what to do if the system call fails.

Connector Related Tables

The connector 406 defines a name and a description. The connector 406 is a grouping mechanism for extraction statements and a specification for input and output data stores. The description is used for documenting the connector. The name is the logical name of the connector. The connector 406 represents an ordered collection of connector steps 408.

The connector step 408 defines steps within a connector. The connector step table 408 includes the following attributes: a connector key, a connector step key, an enabled flag, an extraction node key, a list order, and a phase. The connector key points to the connector being defined. The connector step key is the primary key. The enabled flag indicates whether a particular connector step is enabled. The extraction node key points to an extraction node that is, the extraction group of statements and semantics that make up this connector step. The list order is the order of steps in the connector. The phase is also the order of the steps in the connector.

100-3749-050609
10
5
The connector time stamp 407 relates to information about incremental extraction. An incremental extraction is where increments of the data in the source system 110 are extracted. The connector time stamp includes a connector key, a connector time stamp key, current max date, a current max time stamp, a last max date, and a last max time stamp. The connector key points to the connector to which the connector time stamp applies. The connector time stamp key is a primary key. The current max date is an indicator of the proposed new system date of the last successful extraction. The current maximum time stamp is the proposed new SQL server time stamp field for the last successful extraction. The last maximum date is the system date of the last successful extraction. The last maximum time stamp is the SQL server time stamp field for the source system databases at the last successful extraction.

The connector time stamp 407 is particularly useful when only updated data should be pulled from the source systems 110.

15
The connector column latch 409 defines information about incremental extraction based on a database column. The incremental extraction information is thus kept in the database and can be retrieved. The connector column latch 409 includes the following attributes: a column name, a connector column latch key, a connector key, a current maximum value, a last maximum value, and a table name. The table name is the name in the input data store for the corresponding connector. The column name is the column name within that table. The connector column latch key is the primary key. The connector key points to the connector to which this latch applies.
20 The current max value represents the proposed new maximum value for the incremental extraction. This number is pushed into the last maximum value if the currently executing

extraction succeeds. The last maximum value is the maximum value that was extracted during the last run of the extraction.

The connector store role 448 defines the usage of a data store for a particular connector. It indicates whether the data store is input or output. The connector store role points to the connector and the data store. The connector store role also indicates the type of storage usage being defined for this connector (input or output).

Extraction Group Related Tables

The extraction group 411 defines a group of extraction steps. The extraction group 411 includes a description, and a name of the set of extraction steps.

The extraction node 410 is a single node, or step, in the extraction tree. The extraction tree defines the order of extraction steps. An extraction node includes an extraction node type, a debug level, a debug level row, an enabled flag, an extraction group key, an extraction node key, a list order, and on error type, a parent extraction node key, and a phase. The extraction node type defines the type of extraction node (as defined in the extraction node type table 491). This relationship is important and allows for the conversion of data in the staging tables for use in the datamart 150. The debug level indicates how to debug a particular step during execution. The debug level row indicates which row to start debugging at for SQL statements. The enabled flag indicates whether or not to execute a particular SQL statement associated with the extraction node. The extraction group key points to, if not null, the name of the group. The extraction node key is a primary key. The list order and the phase define the order of the corresponding step within an extraction node's parent. The on error type indicates what to do if there is an error

during the execution of the step associated with the extraction node. The parent extraction node key points to the parent extraction node of the present extraction node.

SQL Statement Related Tables

The SQL statement 420 defines a single step in an extraction run. A row in the SQL statement 420 table represents an SQL statement. The columns in the SQL statements match those in the corresponding dimension base definition or fact table definition. In one embodiment the consultant supplies the SQL source in SQL statements.

The SQL statement 420 includes an extraction node key, a description, a dimension base key, and execute against input flag, an external table key, a fact table key, SQL source and SQL statement key, and an SQL statement name. The extraction node key points to the extraction node associated with a particular SQL statement 420. The description is for documenting the SQL. The dimension base key points to the dimension base for the corresponding SQL statement. The execution against input flag indicates whether or not to execute this SQL statement against the source or destination data store of the connector that is calling this SQL statement. The external table key points to the external table, if any, being extracted into. The fact table key points to the fact table, if any being extracted into. The SQL source is the actual SQL source to be executed during the SQL statement execution. The SQL statement key is the primary key. The SQL statement name is the logical name for an extraction SQL statement.

The statement type enabled 428 defines which RDBMS types use this extraction statement.

The statement type enabled 428 includes the following attributes. An SQL statement key, a statement type enabled key, a store role name, and a store type. The SQL statement key points to

the SQL statement. The statement type enabled key is the primary key. The store role name is the role name for which this SQL statement should be used. The store type is the store type for which this statement should be executed.

The external table 422 defines the user defined destination table for use during a multiphase
5 extraction. This user defined destination table can be used to temporarily store data during an extraction. The external table 422 defines the physical name of the external table and whether or not to truncate this external table on the next job run.

The external column 424 defines a column in a user defined extraction table. The external
10 column 424 includes the attributes for documenting a particular external column, and the column name in the external table. A pointer to the external table, a list order of appearance in the external table, and a physical type of the logical database for this column are included in the external column 424.

Error Handling

The error handling type 413 is a look up table to define how to respond to a particular error.
15 An error handling type can be a default action to take when an error occurs.

The debug level 415 defines ways in which extraction steps can be debugged. The debug level includes a logical name for users to pick a debugging behavior. The default level also includes a default flag.

Data Semantic Related Tables

20 The semantic type 430 defines a set of predetermined semantic types for use in defining a schema. The semantic type includes a logical name for a particular transformation. Associated

with the semantic type are a dimension semantic type 432 and a fact semantic type 434. The dimension semantic type table 432 defines the ways in which dimension data in the staging tables 130 can be extracted and put into the datamart 150. Similarly, the fact semantic type defines the ways in which the information in the staging tables 130 can be put into the fact tables of the datamart 150. Both the fact semantic type 434 and the dimension semantic type 432 include pointers to an actual table type and are used to subset the full list of semantic types.

Each semantic type 430 is made up of a semantic type definition. The semantic type definition table 436 defines the set of adaptive templates used in any given semantic type. The semantic type definition 436 includes the semantic type key that points to the semantic type 430 for a particular semantic type definition. The semantic type definition also points to the adaptive template 438 used. The semantic type definition also includes a list order for the ordering of the adaptive templates.

The adaptive template 438 is a semantic transformation template (e.g., an SQL program) that is used in the extraction of the data in the staging tables 130 to turn all source data into transactional data. The adaptive template 438 includes attributes indicating a logical name for an adaptive program used within semantic transformations.

The adaptive template block 439 defines the individual pseudo-SQL statements that make up a template. The adaptive template block 439 has the following attributes: the adaptive template block key, an adaptive template key, a block name, a list order, an on error type, and SQL source. The adaptive template block key is the primary key. The adaptive template points to the adaptive template to which this block belongs. The block name is the internal logical name for this block

of pseudo-SQL source code. The list order is the order of this block within the template. The on error type indicates what to do if this block causes an SQL error when executed. The SQL source includes a template of pseudo SQL source code. This template is described in greater detail below.

Data Store Related Tables

The store type 450 defines the types of RDBMS's supported by the system 100.

The data store 440 defines a logical data source, or sink, used during the extraction. The data store 440 includes the following attributes: the data store key, a data store flag, a description, a name, a source system key, and a store type. The data store key is the primary key. The datamart flag indicates whether or not this data store is the special datamart store. Since the datamart 150 and the metadata 160 can reside in the same database or different, the data mark helps resolve the location of the datamart 150. The description is for documentation of the particular data store. The name is the logical name of the data store. The source system key points to the source system identifier to which this data store belongs. This allows live, and backup, source systems to share the same identifier. The store type indicates the store type of this data store.

The source system 442 is a logical identifier for a source system 110 from which data can be pulled. This allows two physical databases to act as one master database and one backup, for example. The source system 442 includes a description attribute, a source system key and a source system name. The description is for documentation to describe the source system. The source system key is a primary key for this table. This number also becomes identified source

system field in the staging tables 130 being filled. The source system names is a logical name for a source system 110 from which the system 100 is pulling data.

The following store tables are subtypes of the data store table 440. They address specific data stores.

5 The file store table 441 defines the files in which data can be stored. The file store 441 defines a directory and file name for each file.

10 The Oracle store 454 defines information about particular Oracle databases. The Oracle store 454 includes the following attributes: a data store key, an instance name, an Oracle store key, a password, an SQL network name, a user name, and a version. The data store key is a one to one relationship key to the data store being defined. The Oracle store key is the primary key. The password and user name are used to access a specific Oracle system. The version number is the Oracle vendor version number. The SQL network name is the SQL net instance name. The store version is a version of the store type (the database vendor's version for example) that the system recognizes. The store version has a pointer to the store type being defined and also includes a version number attribute.

15 The SQL server store table 456 defines details about an SQL server system. The SQL server store includes the following attributes: a data store key, a database name, a password, a server, and SQL server store key, a user name, and a version. The data store key is a one to one relationship to a data store entry. The database name is an SQL server database name
20 (\$\$DEFAULT means the database in which this role resides). The password is the SQL server password. \$\$ DEFAULT again means the password currently logged into to read this data. The

server is the SQL server name. The SQL server store key is the primary key. The user name is the SQL server user name. The version is the vendor's version number of this SQL server. \$\$DEFAULT means use the default value for the current database being used. For example, the database name means the database in which this role resides.

Extraction Metadata Use

The following describes the tables of Figure 4 in the context of the extraction process 204. The job, the job step, and the connector, group extraction steps for extracting information from the source systems 110 and cause that information to be placed in the datamart 150. This organization allows for a very flexible extraction process. For example, where a two phase extraction is required, one connector could be used to extract the information from the source system 110, while a second connector could then be used to take this extracted data from an external table.

The job defines the order of the execution of the connectors. The job also allows for the running of an external program, such as system call, between connector executions. Thus each, job step in a job can be a system call or a connector.

The following is an example illustrating the organization of job. Assume that a consultant wants to extract information from a source system that provided a raw set of home addresses. A system call could be run as part of a job step. The system call would determine the zip codes associated with those addresses. The zip codes could then be included in the datamart 150.

The relationship between the connector 406, the connector step 408, and the extraction node 410 is that the connector 406 allows for the reuse of extraction nodes in multiple connectors

(through the connector step). This relationship is particularly important where similar connectors are created. For example, assume that a consultant wants to create a connector that runs some steps Monday through Friday and different steps on Saturday and Sunday. Most of the steps in the connector will be common, however some will be different. Through the use of the connector step, the consultant can reuse many of these connector steps in each connector.

As noted before an extraction node can be a leaf or a grouping mechanism for extraction. It can correspond to an SQL statement extraction step or a semantic conversion step. During the definition of the schema, the consultant defines the specific SQL statements for extraction and the specific semantic instances for the facts and dimensions.

An SQL statement is a single step in an extraction run that represents a data push or a data pull. The SQL source code dictates the action for a given extraction node. After the SQL statements are run, the staging tables 130 are ready. The semantic conversion of the data in the staging tables 130 can occur.

The semantic instance represents the use of a single generic template on one fact or dimension table. The semantic type associated with the semantic instance is one of a number of pre-defined recognized data meanings within the system 100 (e.g., an "order"). The semantic types correspond to programs for converting the data in the staging tables 130 into data for use in the datamart 150. An example of a semantic type is a "slowly changing dimension" type.

The semantics types, as mention previously, are made up of a series of templates. These templates include tokens that can be replaced with information from the corresponding dimension base or fact table. An example of an adaptive template is one that would be used in

re-indexing of a fact table. This could be used as the last step in the semantic transformation of facts. The re-indexing will help speed the operation of the datamart 150. Importantly, this same indexing is performed for each fact table. No matter which semantic type is chosen for a given fact table, the same indexing is performed. Thus, this adaptive template can be used in each semantic type through its semantic type definition.

The following describes the slowly changing dimension semantic type. (See Appendix A.) In this semantic type are an insert dimension and an index dimension adaptive template. Each adaptive template has a corresponding set of pseudo-SQL statements. During the semantic template conversion 140 this pseudo-SQL will be transformed into real SQL source code. This is done by converting the pseudo-SQL tokens into actual dimension column names, etc. (the column names and table names are derived from the schema definitions 161).

Thus, during the extraction, the extraction node associated with a particular semantic type instance is processed. This causes the adaptive template blocks associated with the semantic instance to be processed. The dimension information associated with that semantic instance, or the fact table information associated with the semantic instances, can then be used to replace the tokens with the specific information associated with that dimension or that fact.

Some embodiments of the invention correspond to only one or more semantic templates and a computer readable media, a computer, an electromagnetic waveform, or the like.

Further Discussion of Templates

The following describes the pre-parsed template and the post-parsed results in greater detail. Each token begins with a \$\$\$. In the example template, for the slowly changing dimension

semantic type, a number of tokens begin with \$\$ DIM KEY. Similarly, tokens appear that begin with \$\$FSTGTBL[]. In the post-parsed template, the dimension key tokens have been changed to cost center keys, account key, subaccount keys, etc. Note any tokens, and their surrounding text, that are not replaced are removed from the post-parsed text. If more tokens need to be replaced then are available in the template, then an error flag will be set. In other embodiments of the invention, the templates are dynamically generated according to the number of columns defined in the schema definition 161. In other embodiments, templates are not used but the "post-parsed SQL" results are dynamically generated from the schema definitions 161 and the semantic instance types.

In this example, the net price corresponds to a fact column in a fact table. This indicates that the table entitled SSA in the post-parsed example includes one fact called net price.

In some embodiments, the pre-parsed templates include additional tokens to deal with specific data stores. For example, the "select into" statement is a token in the pre-parsed version. This compensates for whether the data store is in Oracle database or an SQL server.

Another feature of the pre-parsed language is that "--#begin#" is used to break the pre-parsed version into adaptive template blocks.

Examples

Appendix A illustrates semantic types that may be supported and their corresponding adaptive template names. For example, the Pipelined semantic type is made up of, in this order, the map_keys the pipe_state and the index_fact adaptive templates. The example pre-parsed and post parsed SQL adaptive templates are then provided.

As mentioned previously, the use of the semantic types significantly reduces the amount of work needed to implement the datamart 150. By selecting a semantic type for a particular fact table or dimension table, the consultant automatically selects the corresponding pre-parsed SQL adaptive templates. The selected adaptive templates are then automatically converted into post-parsed SQL statements that include the schema specific information for the datamart 150. Additionally, these post-parsed SQL statements include the SQL for converting the data in the staging tables 130 into data that can be used in the datamart 150 tables.

Additional Templates

Two types of templates not described in Appendix A are “team” templates and “denormalized” templates.

The team template is used to properly populate an “associative” dimension table. Such a table is used whenever there is a one-to-many relationship between an individual fact row and a dimension. For example, if multiple salespeople can split the credit for an order, one needs some way to represent this situation in the datamart. In a star schema, one normally associates a tuple of dimension values with a fact row (e.g. product, customer, salesrep dimensions for the fact row containing price, quantity etc.). Since there is only a single salesrep_key, one could normally have only one salesrep associated with this transaction. There are two solutions. One is to introduce multiple fact rows for a transaction involving one to many relationships. If there were three salesreps on a specific order, there would be three fact rows for this order stored in the database. This has the disadvantage of multiplying the data size by a factor of three and slows queries. Also queries that are concerned with the total number of transactions become more

difficult to process since duplicate rows, due to the multiplication by the number of salesreps, must be eliminated.

Another solution is to introduce an associative table between the actual salesrep dimension table and the fact table. Conceptually, the associative table contains “teams” of salespeople. If salesreps A, B and C often sell products together, they will be associated with a unique team key. The team key will be stored in each fact row for orders sold by the A, B, C team. The associative table will associate the team key with the three rows for A, B and C in the salesrep table. The associative table will have 3 rows representing this team (A-key, team1-key), (B-key, team1-key) and (C-key, team1-key). If the team of A, B, D and Q also sold products together, the associative table would have four additional rows (A-key, team2-key), (B-key, team2-key), (D-key, team2-key), (Q-key, team2-key). The team template scans the staging table used to load the fact table and generates the appropriate rows for entry into the associative table, only for those teams THAT ACTUALLY OCCUR in the fact rows being loaded.

Also, if a team is already present in the associative table it will be reused.

In real world situations, the number of teams that actually occur is much smaller than the total space of all possible teams.

Note that this team template can be used wherever there is a one to many relationship between fact and dimension rows.

Another example is in a Sales Force Automation system where the fact rows correspond to a sales “opportunity”.

An opportunity may be associated with the dimensions of Sales Lead Source, Product and Customer Contact. All of these may be one to many relations, amenable to the "team" concept.

As mentioned above, the other type of template is the denormalized data template. This is a variant of the

5 "Team" template where instead of introducing the extra associative table between the dimension and fact tables, the dimension table is a combination of the associative table and the actual dimension table. This effectively flattens the data. In the above example the dimension table would contain rows like ("Greg Walsh", A-key, team1-key),

10 ("Craig", B-key, team1-key), ("Ben", C-key" team1-key), ("Greg Walsh", A-key", team2-key) etc. Greg Walsh is a member of both teams 1 and 2 and his name (and

other attributes) rather than just his key (A-key) is stored twice. Used judiciously this can result in faster queries than the associative table case but results in duplicate data being stored.

15 The population of both the denormalized team dimension and the associative table are difficult to code properly. This is especially true if this is done incrementally (e.g., on nightly extracts) and if you want to be independent of team order (e.g. A, B, C) is the same as (A, C, B). Thus, allowing the consultant to simply select this data semantic provides a significant improvement over previous systems.

Runtime Metadata

Figure 5 illustrates the schema for the runtime environment within the system 100. The
20 runtime schema 500 represents the schema description for the schema of the running datamart 150. That is, when the datamart 150 is created or modified, the schema definition is propagated

into the runtime schema 500. Thus, the runtime schema 500 allows for the datamart 150 to be changed without having to rebuild all the tables and repopulate all of those tables. Additionally, the runtime metadata 500 provides the support for aggregate navigation. Aggregate navigation involves determining which aggregate to use in response to a query. Schema modification and aggregate navigation will now be explained in greater detail.

The schema modification involves comparing the changed schema definition with the present schema definition. As will be seen below, an actual table 502 keeps track of all of the dimension tables and the fact tables in the datamart 150. When a change is made to the schema definition, a comparison is made between the old definition and the new definition. The difference between these definitions defines the set of tables, columns, and rows that need to be added, deleted or modified, in some way. Importantly, the modifications can often be made without losing any data in the datamart 150.

The aggregate navigation process determines which aggregate most closely suits a particular query. The runtime metadata 160 keeps track of the aggregates available in the datamart 150. The query and reporting program 104 initiates a view of the runtime metadata 500 (in particular, the tables holding the aggregate tables definitions). The view results indicate which aggregates are available to answer the particular query. The view results are further examined to determine the best aggregate to use (the one that most closely corresponds to the query).

Importantly, the query machinery does not need to be aware of aggregates to be able to take advantage of them. Aggregates are simply presented to the query machinery as a solution to a query.

Additionally, aggregates can use other aggregates to build themselves. This is because the schema definition can be used to determine the relationship between aggregates.

Runtime Metadata List

The runtime schema 500 includes the following elements: an actual table 502, an actual column 504, a fact aggregate table 512, a fact aggregate dimension 514, a dimension base aggregate 516, a dimension base aggregate column 518, a datamart letter 510, the dimension base 306, the fact table 304, the external table 422, an actual column 504, a physical type definition 530, an actual table type 336, an actual column type 540, the physical type 330, a database physical type 595, the translation string 332, a translation actual 539, a store type 450, a date 560, a business process 570, an adaptive template profile 580, and a transaction type 590.

Runtime Metadata Descriptions

The actual table 502 corresponds to metadata 160 that describe which dimension base and fact tables “actually” exist in the datamart 150.

The actual table 502 includes the following attributes: an actual table key, an actual table name, an actual table type, a dimension base key, an external table key, a fact table key, an index flag, a mirror flag, and a logical table name. The primary key is the actual table key. The actual table name corresponds to the physical name of this table in the database implementing the datamart 150. The actual table type is the logical type of this physical table. For example, if this is a dimension staging table or a fact staging table. The dimension base key points to the dimension base table definition that defined the corresponding physical table. The external table

key points to the external table definition that defined the physical table. The fact table key points to the fact table definition that defined the corresponding physical table. The index flag and the mirror flag are used in indexing and mirroring, respectively. The logical table name defines the logical name for this table.

5 The actual column 504 is metadata describing a physical column in a physical table in the datamart 150. The actual column table latches this definition information when the physical tables are built in the datamart 150. The actual column 504 includes the following attributes: the actual column key, an actual column name, an actual column type, an actual table key, a dimension role name, a foreign table key, a group by field, a hierarchy, a list order, a parent hierarchy, a physical type, a primary key, and a time navigation field. The actual column name is the name of the physical column in the physical table in the datamart 150. The actual column type is the logical type of the column. The actual table key points to the actual table in which the actual column lives. The dimension role name is the logical role name of the dimension in the fact table for dimension foreign keys inside of a fact table. The foreign table key points to the actual dimension base tables in the actual tables 502 (the foreign table key is applicable to fact actual columns that are foreign keys to dimensions). The group by field, for dimension table, is true when this column should be included in an aggregate builder group. The hierarchy for dimension, for dimension columns, indicates that aggregate builder group to which this column belongs. The list order is the order of the column in the actual table 502. The parent hierarchy, 10 for dimension columns, indicates the parent aggregate builder group to which this column belongs. The physical type is a logical data type of the column. The primary key, for dimension 15

20

tables, is true when this column is the primary key of the actual table 502. The time navigation field, for the database dimension, is true if this field can be used by the time navigator.

The fact aggregate table 512 includes a list of fact aggregates in the datamart 150. The fact aggregates includes attributes that point to the actual fact table in which this aggregate belongs.

5 The fact aggregate table 512 indicates which numbered aggregate represents the fact table in question, the number of rows in this aggregate, a datamart letter, and an enabled flag. The datamart letter indicates the mirrored datamart to which this fact aggregate belongs.

Mirror is used to ensure that partially completed extractions from the source systems 110 do not cause the database to become inconsistent.

10 The fact aggregate dimension 514 lists which aggregates contain which dimensions. The fact aggregate dimension includes the following attributes: an actual dimension role key, a dimension base aggregate key, a fact aggregate dimension key, and the fact aggregate key. The actual dimension role key is the dimension foreign key in this fact aggregate that is being defined. The dimension base aggregate key is the dimension aggregate that this fact aggregate points to for this foreign key. The fact aggregate dimension key is the primary key. The fact aggregate key points to the fact aggregate being defined.

The dimension base aggregate table 516 lists all the dimension aggregates in the datamart. The dimension base aggregate includes the following attributes: an actual table key, an aggregate number, an aggregate size, a datamart letter, a dimension base aggregate key, and an enable flag.

20 The actual table key points to the physical header for this dimension base. The aggregate number, for the dimension table in question, is the number of this particular aggregate. The

aggregate size is the number of rows in the aggregate. The datamart letter indicates which mirrored database this aggregate lives in. The dimension base aggregate key is the primary key. The enable flag indicates whether or not the aggregate navigator should work with this aggregate.

The dimension base aggregate column 518 is a list of columns in a given dimension aggregate. The dimension base aggregate column includes attributes which point to which column is included in this dimension aggregate, and a pointer to a dimension aggregate being defined.

The datamart letter 510 indicates which of two mirrored datamarts a particular aggregate belongs to. This is an optional element which may not be required if mirroring does not occur in the datamart 150. Mirroring duplicates the tables in the datamart 150. Changes can then be made to one copy of the datamart 150, while the other datamart 150 continues running. These changes can then be propagated when possible.

The actual column type 540 is a logical description of role a column plays in the system 100. The actual column type 540 includes attributes that define the default value to be used in a database for a column of this type.

The physical type definition 530 defines which physical types are allowed for which table types. The physical type definition 530 includes attributes which point to an actual table type. The actual table type is a logical type of a physical table (for example, dimension, fact etc.) being defined. The physical type definition also includes an attribute that indicates whether to select this item by default when giving the consultant or user a choice.

The database physical type 595 defines the name of the physical database.

The translation actual table 539 defines the actual values of translations strings for a single relational database management system. These translations strings are the real strings to use for a given translation string within a store type. The translation actual table 539 also includes attributes that point to the store type.

5 Figure 5 also illustrates additional tables used in the system 100.

The date table 560 is used to track date information in the datamart 150. Importantly, times and dates are always treated corrected in the datamart 150. This can be guaranteed because the consultant cannot change the definition of dates in the datamart 150. Thus, for example, the month of September will always have 30 days, and leap years will be handled correctly.

10 The transaction type table 590 is a list of the available transaction types within the system 100.

15 The adaptive template profile 580 is used as a communications mechanism for templates. The adaptive template profile 580 includes a number of rows being communicated back to the calling program. The adaptive template profile 580 also indicates the logical name for information being communicated back from an adaptive template to the calling program.

The business process table 570 is a look up table for supported business process types during the extraction. The business process 570 includes a business process key and a process name. The process name corresponds to a logical name for a business process to which fact staging table belongs. The process key identifies a business process record in a fact staging table.

Time Navigation

An important feature of some embodiments of the invention is the ability to compactly store and rapidly query “historical” backlog/balance/inventory quantities. By historical we mean the amount of backlog or inventory as it existed at a given point in time--not necessarily today. Note that backlog/balance/inventory quantities are different than transactional quantities. For example, your bank balance at the end of Q1 1997 is not the sum of your bank balances at the end of Jan, Feb and March. It is computed by adding all of the deposit transactions and subtracting all the withdrawals from the balance at the end of Q4 1996. One could compute balances by this method when a user queries the system but because this method requires rolling forward all of the appropriate transactions “from the beginning of time,” the queries will likely be slow.

The traditional solution in datamarts is to store periodic “snapshots” of the balance. The snapshots are often stored at daily intervals for the recent historical past, and at greater intervals (e.g. weekly or monthly) for less recent history. This approach has two big disadvantages. The first is an enormous multiplication of data volume. If, for example, you are keeping track of inventory in a store you must store a snapshot for each product you hold in inventory for each day, even if you only sell a small fraction of all of your products on a given day. If you sell 10,000 different products but you only have 500 transactions a day, the “snapshot” datamart is 20 times larger than the transactional datamart. The second disadvantage relates to the most common solution for alleviating the first problem, namely storing snapshots at less frequent intervals for less recent history. This results in the inability to compare levels of inventory in

corresponding time periods since the same level of detail is not present in earlier data. For example, in manufacturing companies it is often the case that much business is done near the end of fiscal quarters. If one wants to compare inventory levels between Q1 1995, Q1 1996 and Q1 1997, and focus on the most important changes which occur near quarter end, one cannot use the approach of storing the snapshots at coarser levels of detail since daily data would be required.

In some embodiments of the system, the aggregate tables are used to answer queries about backlog/balance/inventory quantities. In order to answer such queries, the previously described rolling forward from the beginning of time is done. However, this is performed efficiently through the accessing of the appropriate time aggregates. For example, assume the datamart has five years of historical transaction data beginning in 1993. Assume that one desires the inventory of some specified products on May 10, 1996. This would be computed by querying all of the transactions in the 1993, 1994 and 1995 year aggregates, the 1996 Q1 quarter aggregate, the April 1996 month aggregate, the May 1996 week 1 aggregate and finally 3 days of actual May, 1996 daily transactions. These transactions (additions and subtractions from inventory) would be added to the known starting inventory in order to produce the inventory on May 10. Note that this "time navigation "hops" by successively smaller time intervals (year, quarter, month, week, day) in order to minimize the number of database accesses. What is important is the exploitation of aggregate tables, that already exist in the system in order to answer transactional queries rapidly (e.g. What were the total sales of product X in Apr 1996?). This avoids the need to build what is essentially a second data datamart with the balance/inventory/backlog snapshots.

Query Mechanism Metadata

The following describes the metadata 160 used in the query/reporting program 104. This metadata is shown in Fig. 6. Generally, the query mechanism metadata can be broken into ticksheet metadata, measurement metadata, filtering metadata and display options metadata. The ticksheet metadata defines the user interface objects for user interaction with the datamart 150. The ticksheet defines how users can initiate queries and how results are presented back to the user. The measurement metadata defines a logical business calculation that can be presented to a user. Typically, the measurement metadata defines a format for presenting information to user that is more easily understood by the user or provides a more valuable result to the user. The filtering metadata defines how a user can filter results. Filtering allows the results set to be limited to particular dimension values. The display options metadata defines display options that can be provided to the user.

The following describes some important features of the user interface. The user interface allows the user to drill down through data. Also, portions of the query forms can be dynamic based upon values in fields (e.g., a list box can be dynamically updated because it is tied to a field in the datamart 150, that when changed, cause the values in the list box to change). Also, a query is guaranteed to be consistent with the schema because the query is tied to the schema definition.

Query Mechanism Schema List.

Figure 6 includes the following elements: the constellation 302, a ticksheet 602, a data set 606, a ticksheet column 608, a tip 601, an attribute role 603, an attribute 610, a ticksheet attribute 605, a ticksheet type 604, a measure 620, a measure term 630, a measure unit 624, a term operator 632, a transaction type 590, an RPN operator 636, the fact column 310, the fact table 304, a backlog 638, a measure mapping 622, a ticksheet column element 612, a dictionary 640, a filter block 650, a filter block type 652, a filter group 654, a filter element 656, a ticksheet type option 660, an option location 662, an option value 664, an option name 666, an option display type 668, an application type 691, the dimension role 320, the dimension column 329, and the dimension base 306.

Query Mechanism Schema Metadata Descriptions

Ticksheets Metadata

Under the constellation 302, the ticksheet is a top level object for defining the user interface objects for user interaction. The ticksheet 602 table includes a data set key, a name, a ticksheet type, a constellation key, a label, label detail, a list order, a cleanse flag, and a description. The cleanse flag indicates whether or not to cleanse the filter data on this ticksheet. The constellation flag indicates the constellation in which the dimensions and measures for this ticksheet reside. The data set key indicates the page in which the end user makes report selections. The data set key represents a logical grouping of similar ticksheets. The description is for documentation purposes. The label is the string for the name of the ticksheet. The list order indicates the ticksheet list order. The name is the hidden name of the ticksheet. The ticksheet includes a

primary key. The label detail allows for more verbose documentation. The ticksheet type indicates the type of application that interprets the selections made on this ticksheet.

The data set table 606 is a grouping mechanism for ticksheets into sets that describe their contents. The data set table 606 includes the following columns: a data set key, a data set name, a label, a description, and a list order. The data set name is a logical name for top level user definition of like ticksheets across ticksheet types. The description is the description of the data set.

The ticksheet column 608 defines a single column for displaying measure choices on a ticksheet. The ticksheet column table 608 includes the ticksheet column key, the list order, the ticksheet key, and the description. These columns and the ticksheet column table 608 operate in a manner similar to such columns in other tables in this metadata.

The ticksheet column element 612 is a single value within a measure display column on a ticksheet. The ticksheet column element 612 includes an abbreviation, a description, a dictionary key, a label, a list order, a name, a ticksheet column element key, and a ticksheet column key. The ticksheet column element key is the primary key for this table. The ticksheet column key points to the ticksheet column 608 entry. The name is the hidden name for the column element. The abbreviation is the shortened name for the user display. The dictionary key is the key for help text entry for this element. It is a key into the dictionary 640. The other columns act in a manner similar to columns in other tables of similar names.

The tip table 601 includes a ticksheet key, a name, a description, and a list order. The tip is a definition of user tips for using a particular ticksheet.

10 The attribute table 610 defines the dimension attribute choices within a ticksheet. These
choices are tied to a single dimension column in the schema definition of the datamart 150. The
attribute table 610 includes an abbreviation, an attribute key, a dictionary key, a dimension
column key, a dimension role key, a hyperlink, a label, a list order, a name, and a ticksheet key.
5 The abbreviation is the shortened user string for the attribute. The attribute key is the primary
key for this attribute. The dictionary key is a pointer to the dictionary 640 that includes help
message for a particular attribute. The dimension column key is the dimension column in which
this attribute refers. For degenerate dimensions this reference is null. The dimension usage,
within a constellation, is defined by the dimension role key. The hyperlink is an html text for
10 navigating return values for this attribute to other web sites, such as a company name look-ups
etc. The label is what the user sees for a particular attribute. The list order defines a sort order
on pop-up menus where one is the topmost in the list. The name is the internal name for the
attribute. The ticksheet key indicates the ticksheet to which this attribute belongs.

15 The attribute role 603 table is a lookup table list of valid roles for attributes within a ticksheet
type. The attribute role includes the attribute role key and the ticksheet type.

The ticksheet attribute 605 indicates the roles played by dimension attributes within a
ticketsheet. The ticksheet attribute 605 includes the attribute key, an attribute role, a ticksheet
attribute key, and a ticksheet key. The attribute key indicates the attribute in the attribute table
610 which has a role define on the ticksheet. The attribute role is the role being granted. The
20 ticksheet attribute key is the primary key. The ticksheet key is the ticksheet being defined.

The application type 691 is the top level grouping for ticksheet types.

The ticksheet type table 604 lists the applicable applications that can use ticksheets.

Examples may be simple reporting applications or relevancy applications or trend type of applications. The ticksheet type 604 includes the application type, a ticksheet type, a template, and a ticksheet type name. The application type is the definition of the high level application in which a particular ticksheet type resides. The ticksheet type is the logical name for a program that interprets ticksheets. The template is the template for the ticksheet. The ticksheet type name is the name displayed for a particular ticksheet type.

Measurement Metadata

The following describes the measures used in the query mechanism schema 600. The measure table 620 defines a top level object for a logical business calculation. The measure table 620 includes a constellation key, a description, a measure key, a measure unit, and a name. The constellation key points to the constellation in which the measure resides. The description is for documentation purposes. The measure key is the primary key for the measure table 620. The measure unit is an indicator of the manner in which numbers are to be displayed. The name is the logical name of the measure.

The measure unit table 624 is a lookup table of the valid list of measure unit types. An example of such unit types is currency.

The measure term table 630 indicates a single component of a measure. The measure term can be combined arithmetically to construct a measure. The measure term table 630 includes a backlog type, a fact column key, a fact table key, a list order, a measure key, a measure term key, an RPN operator, a term operator, and a transaction type key. The backlog type indicates the

type of backlog operation to use for a particular term (e.g., "beginning of period" and "end of period"). This can possibly be none. The backlog types are defined in the backlog type table 638. The fact column key points to the particular numeric column to operate on in the fact table. The fact table key indicates the fact table being operated on. The list order is the order of this
5 term in the measure 620. The measure key is the measure being defined. The measure term key is the primary key for this table. The RPN operator is for the measure terms that perform arithmetic operations on other terms. (The RPN operator table lists the valid arithmetic operations to use when constructing a measure.) The term operator is an SQL operator to use on a set of fact rows. (The term operator table 632 indicates the valid set of SQL operators to use on
10 a measure term.) The transaction type is the transaction type values to filter on for the fact in question.

The relation between measures and ticksheets is handled through the measure mapping table 622. The measure mapping table 622 includes the measure key, the ticksheet key, and the combination ID. The measure key points to the particular measure that is related to the particular
15 ticksheet. The combination ID identifies a set of ticksheet column elements being defined.

Filtering Metadata

Filtering allows results to be limited to only particular dimension values. For example, a user may want to limit the results to particular customer names.

The following describes the filtering tables. The filter block 650 is a top level grouping table
20 for filter area within a ticksheet. The filter block 650 is tied to a particular dimension column in the schema definition. The filter block 650 includes, columns, a description, a dictionary key, a

dimension column key, a dimension role key, a filter block key, a filter block type, a label, a list order, a name, a plural, a mapping flag, and a ticksheet key. The columns field indicates the number of columns in this filter block. The description is for documentation. The dictionary key points to the help dictionary. The dimension column key points to the actual column name and the datamart to be filtered on. A null value here means degenerate dimension as determined by the dimension role key. The dimension role key points to the dimension role in the constellation of the ticksheet that is the form key to filter on for all facts in this constellation. A null value here means that a special dimension shared by all constellations is being used. The filter block key is the primary key for this table. The filter block type points to the filter block type table 652 which defines the ways in which this filter block is displayed to the user (e.g., a checkbox or a radio button). The label is the text that appears to the user for the filter block. The list order is the order that the filter block should appear in a list. The name is the name of the filter block. The plural field is the text that appears to the user for the filter block. The mapping flag is used in mapping. The ticksheet key points to the ticksheet that this filter block belongs.

The filter group 654 is a mid-level grouping for a filter on a ticksheet. This groups individual selections into logical units.

The filter element table 656 defines individual values for a dimension attribute within a filter block. The filter element table 656 includes a dictionary key, a filter element key, a filter group key, a label, a list order, a name, an SQL statement, and a value. The dictionary key points to the user help text for a particular filter element. The filter element key is the primary key. The filter group key points to the filter group to which this element belongs. The label is the user

displayed string for the element. A list order is the order of this element within a filter group. The name is the hidden name of this element. The SQL statement is an SQL statement used to build the list of values for a dynamic list box filter group. The value is the database value that this element translates into in a SQL "WHERE" clause.

Display Options Metadata

To control the method in which information is displayed with a ticksheet, a set of options are supplied. The ticksheet type option table 660 helps support this feature. The ticksheet type option table 660 includes a list order, an option display type, an option location, an option name key, a ticksheet type, and a ticksheet type option key. The list order is the order to display options for a ticksheet type. The option display type is an html control type to use when displaying a particular option. The option location is the location of the option on the ticksheet. (The option location table 662 holds the list of possible locations of options on a ticksheet.) The option name key is the option being included in a ticksheet type. (The option name table 666 defines an option that has meaning for one or more applications that can be used by users.) The ticksheet type is the ticksheet type being defined. The ticksheet type option key is the primary key for this table.

The option name table 666 includes option name key, a name, a label, and a dictionary key. The option name key is the primary key. The name is the logical name for the option. The label is the label seen by the user as the name of the option. The dictionary key is the pointer to the help text dictionary.

The option value table 664 defines single valid values for options. The option value table 664 includes the dictionary key, a label, a list order, an option name key, an option value key, and a value. The dictionary key is the help text dictionary key. The label is the label seen by the user for this option choice. The list order is the order of the valid values for the option. The option name key is the option set being defined. The option value key is the primary key for this table. The value is the hidden value for the option.

The option display type table 668 is a lookup table indicating the valid way that options can be displayed.

The dictionary table 640 is a table for help text for users.

User Interface Example of Defining Metadata

General Schema Definitions User Interface

The following describes a constellation used in a business. In this example a new dimension is added very simply and the changes are automatically propagated into the datamart 150. The enterprise manager interface 192 is used by the consultant to define and manipulate the system 100.

Figure 7 illustrates the enterprise manager interface 192. Multiple system 100's can be connected to through that interface. Many of the objects and tables in the system 100 are shown. The base dimensions definitions 710 correspond to the base dimensions available under the "epitest" datamart. The constellations 712 for this datamart include an expense constellation and a sales constellation 720. Thus, the sales constellation 720 would appear as a row in the

constellation table 302. Under the sales constellation 720 appear the definitions for the sales aggregates 721, the sales dimensions 723, the sales degenerate dimensions 725, the sales facts 726, the sales measures 728, and the sales ticksheets 729. Also, the extraction definitions 740 and security definitions for the “epitest” datamart are accessible. The sales dimensions 723
5 define rows in the dimension role table 320. These rows include customer billed to, product, application, program, customer ship to, and territory.

Figure 8 illustrates the dimension table definition window 800 (presented to the consultant as the result of selecting the customer billed to dimension role under dimensions). A dimension table definition window 800 show that the dimension 820 is customer bill to and the base dimension 810, to which the dimension 820 points to, is named customer.
10

Figure 9 illustrates a base dimension window 900 showing the definition of the base dimension 810 named customer. In this case, the customer base dimension has a “slowly changing dimensions” dimension data semantic 910. In this example, the dimension base 810 customer has a number of dimension columns 920. L1 is an example of a dimension node.

Figure 10 illustrates the dimension column window 1000 for the customer region code column 1010. The physical type is the type of data defining that dimension column. The VARCHAR_50 physical type is then mapped to an actual type through the physical type table 330. The translation is dependent on the store type.
15

Figure 11 illustrates the base dimension window for the base dimension date (substantially un-editable). The user interface indicates that the date dimension is not an editable base dimension (shown as black circles under “Base Dimensions”), and grayed out in the base
20

dimension window 900. The transtype (transaction type) is similarly not editable and is similarly shown in the user interface.

Figure 12 shows the dimension column “date day quarter end”. Note that column cannot be edited.

5 Figure 13 illustrates a fact table window 1300 that is open on the order fact table 1310 definition. The fact data semantic 1310 is transactional/state like/force close/unjoined. The transactional/state like/force close/unjoined means that the invoice part of an order is transactional, the booking is state like, orders that are not otherwise dealt with, are closed out, and the data may become dirty and so it needs to be cleansed, thus, it is unjoined. This semantic type is described in detail in Appendix A. Note that the user can select from many different types of fact table semantics. The fact table window 1300 also shows the fact columns 1330 for the order fact table.

10 Figure 14 illustrates a fact column window 1400 opened on the definition of the net_price fact column 1410. Here the fact column 1410 has a physical type 1420 called FACTMONEY and an aggregate operation 1430 called a SUM.

15 Figure 15 illustrates how the consultant would select the semantic type for the order fact table 1310.

Figure 16 illustrates the results of a request by the consultant to generate the datamart 150 from the definitions of the datamart. The results show that a number of tables have been created in the datamart 150. Importantly, Figure 16 illustrates the results of an initial build process. In subsequent modifications, only those elements of the datamart that have changed will be

changed. In other words, the subsequent changes are handled as an update process. An example of the update process is described below.

Extraction Interface Elements

The following describes the creation of the connectors 162. Once the schema definitions 161 are set, the consultant then defines the connectors 162 to the source systems 110. The connectors, as noted above, define how information is to be extracted from the source systems 110 and how that information is to be placed into the datamart 150.

These connectors are defined under the extraction definitions 740. Figure 17 illustrates the job definition window 1700 presented when the consultant has selected a particular job.

Figure 18 illustrates the job steps 1810 within the default job. The checkbox indicates whether the particular job step is enabled for that job. The list of job steps is shown in the order that they are executed. The two foreign keys within the job step are shown in the dialog box of Figure 17 to indicate whether the job step is a connector or a system call.

Figure 19 illustrates the All Semantics connector as defined in the connector definition window 1900. This connector includes the description and a definition of the input and output data stores. In this case, both of the data stores are the “epimart” (which is the datamart 150).

Figure 20 illustrates the data store window 2000 interface for showing a data store. This is the data store that is referenced in the connector All Semantics.

Returning to the discussion of connectors, Figure 21 illustrates the connector entitled MFG.

The MFG connector has two major steps: (1) order dimension staging, and (2) order fact staging.

The results of these extraction steps are put in the staging tables 130. (The all extraction steps window 2100 illustrates all the possible steps in the system that can be used.)

Figure 22 illustrates the SQL statement window 2200. The SQL statement window 2200 has an SQL field 2210 that includes the SQL statements that loads a customer table. As shown in the dialog box, the table references for the SQL statement includes the customer dimension table column definitions. That is, this SQL statement is going to be used to populate the customer dimension table.

In this example, the base name, type code, type name, region code, region name and tier name corresponds to the column names within the customer dimension. The date modify is an additional field that is to be used to indicate when this field was last modified in the database. Additionally, there is a source system key that is automatically included in every dimension. The source system key helps ensure that the datamart 150 is well-formed.

In one embodiment of the invention, these names can be automatically propagated into the SQL field 2110 window via a template that is generated from the corresponding base dimension. This allows the consultant to more easily define the SQL selection statement.

Figure 23 illustrates the SQL statement for the Open Order Stage for populating the order fact table.

At this point the steps for generating the staging table information are complete. Now the semantic conversion steps are defined.

In Figure 24, returning to the connector steps window, we have switched to an All Semantics connector 2410. The All Semantics connector 2410 causes the semantic conversion of the information in the staging table for use in the datamart 150.

Figure 25 illustrates the semantic transformation window 2500 showing the dimension table customer semantic 2510.

Figure 26 illustrates the order fact semantic 2610 definition.

Figure 27 illustrates the results of a consultant adding a new dimension 2700 (called warehouse) to the sales constellation 720. The batch operation window 1600 illustrates the changes that are being made to the datamart that was created in Figure 16. To achieve these results, the consultant need only perform the following steps:

1. Define the new dimension.
2. Define the connector steps, including the SQL Statement to extract the warehouse data from the source systems 110.
3. Add the warehouse information to the Open Order Stage SQL Statement.
4. Define a semantic transformation for the warehouse, e.g., slowing changing dimension.
5. Have the enterprise manager 102 update the datamart 150.

Thus, changing the schema definition of the datamart 150 is significantly simpler than previous systems.

Additional Interface

Figure 28 illustrates the aggregate group window 2800, where aggregates can be defined.

For a given aggregate group, the consultant can define which fact share the aggregate, and which

type of aggregate should be built for a given dimension in the aggregate. Additionally, dimensions can be added to, or removed from, an aggregate group.

Figure 29 illustrates a portion of the configuration window 2900. In this example, a partial list of the transaction types 2910 is shown. Thus, the consultant can determine which transaction types will be available to him/her.

End User Interface Definition and Example

Figure 27 illustrates the interface used to define a user interface for the end user. Figure 30 includes a user interface definition window 3000 which can be used to define measures and ticksheets. In this case, the measure definition window 3010 is shown.

The measure definition window 3010 allows the consultant to define which measures will be available in the system. The consultant defines the name, units, and constellation for a particular measure. The measure is further defined by defining the list of measure terms that make up a measure (the calculations for the measure 3020). In this example, the ASPBacklogOrderGross measure has seven calculation steps, some of them arithmetic (e.g., SUM) and others RPN (Reverse Polish Notation).

Figure 31 illustrates the ticksheet definition window 3100. The ticksheet definition window allows a consultant to define a ticksheet that will be used to generate a query form for a user. The consultant defines the attributes, the columns, and the filters for a ticksheet. Figure 32 illustrates the query form 3200 generated from the ticksheet defined in Figure 31.

Figure 33 illustrates the measure mappings window 3300, that allows the consultant to map measure definitions to user friendly measure names. In the example of Figure 33, the

PriceShipGrossMonth measure is mapped to a combination of the dollar amount, gross, and sell-through being selected in the query form 3200.

Figure 34 illustrates another query form 3200 generated from a different ticksheet definition.

When the user selects the create report button, the query is issued against the datamart 150.

5 Figure 35 illustrates some sample results from such a query.

The following query log illustrates the actual query that was executed against the datamart 150. The query log illustrates that an aggregate and navigation process determined which aggregate would be the most appropriate. The aggregate builder had created these aggregates.

The most appropriate aggregate for the requested query was selected. The results were then returned.

```
*****
Query log
*****

time      : <A Date Here>
addr      : 192.0.0.210
host      : 192.0.0.210
user      :
agent     : Mozilla/4.01 [en] (WinNT; U)

Database information: DRIVER={SQL SERVER};SERVER=bigfoot;DATABASE=macromedia

Keys and values coming in from the browser:
  file =
  fileDesc =
  queryaction = QUERY
  hidden_queryaction = QUERY
  OK_callback =
  NOK_callback =
  ticksheet = Orders
  hidden_ticksheet = Orders
  Rows = Customer
  hidden_Rows = Customer
  Columns = Fiscal Year
  hidden_Columns = Fiscal Year
  units = Price
  hidden_units = Price
  facttype = Shipped
  hidden_facttype = Shipped
  facttype2 = Gross
  hidden_facttype2 = Gross
  stage = Orders
  hidden_stage = Orders
  currencyunits = Thousands
```

```

hidden_currencyunits = Thousands
rowtotal = yes
hidden_rowtotal = yes
columntotal = yes
hidden_columntotal = yes
percent = none
hidden_percent = none
precision = 0
hidden_precision = 0
charts = 3D
hidden_charts = 3D
maxrows = 10
hidden_maxrows = 10
rowsorttype = value
hidden_rowsorttype = value
Fiscal_Years = All
hidden_Fiscal_Years = All
Fiscal_Quarters = All
hidden_Fiscal_Quarters = All
Calendar_Months = All
hidden_Calendar_Months = All
Business_Units = All
hidden_Business_Units = All
Product_Lines = All
hidden_Product_Lines = All
Product_Supergroups = All
hidden_Product_Supergroups = All
Platforms = All
hidden_Platforms = All
Product_Languages = All
hidden_Product_Languages = All
Product_SKUs = All
hidden_Product_SKUs = All
Product_SKU =
Sales_Reps = All
hidden_Sales_Reps = All
Channels = All
hidden_Channels = All
Customer_Types = All
hidden_Customer_Types = All
Customer_Regions = All
hidden_Customer_Regions = All
Customers = All
hidden_Customers = All
Customer =
sqStyle = classic
hidden_sqStyle = classic

```

Contents of %FormData:

```

Columns = Fiscal Year
rowsorttype = value
ticksheet = Orders
Customers = All
charts = 3D
Customer Types = All
Product SKUs = All
Customer Regions = All
Fiscal Quarters = All
Rows = Customer
Channels = All
precision = 0
Product Supergroups = All
percent = none
maxrows = 10
Sales Reps = All
columntotal = yes
Calendar Months = All
queryaction = QUERY
sqStyle = classic
Fiscal Years = All
Product Languages = All

```

Platforms = All
Product Lines = All
rowtotal = yes
currencyunits = Thousands
Business Units = All

The colheaders are:

The Cellitems are:
Price Shipped Gross Orders

The Cellitems abbreviated are:
Dollar Amount Shipped Gross Orders

pid is: 310

spid is: 25

The valid collheaders are:

The invalid colheaders are:

The valid cellitems are:
Price Shipped Gross Orders
The invalid cellitems are:

The unitstack is:
CURRENCY

The cellstack is:
-SUM(Order.net_price)

The selectstack is:
-SUM(Order.net_price)

The typestack is:
SHIP

Transtypes are:

"BEGIN_RETURN" = 1007
"END_GROSS" = 1004
"END_SRBOOTH" = 1018
"END_SRADJ" = 1012
"BOOK" = 1
"BEGIN_ANET" = 1013
"END_IADJ" = 1024
"END_ICOMP" = 1022
"BEGIN_GROSS" = 1003
"BEGIN_SRBOOTH" = 1017
"END_SBOOTH" = 1016
"END" = 1002
"BEGIN_SRADJ" = 1011
"END_SADJ" = 1010
"BEGIN_IADJ" = 1023
"BEGIN_ICOMP" = 1021
"END_NET" = 1006
"SHIP_ADJUST" = 103
"LOST" = 3
"END_SALL" = 1020
"BEGIN_SBOOTH" = 1015
"BEGIN" = 1001
"BEGIN_SADJ" = 1009
"BOOK_RETURN" = 2
"END_FADJ" = 1026
"BEGIN_NET" = 1005
"BEGIN_SALL" = 1019
"GL" = 105
"SHIP_RETURN" = 102
"SHIP_RADJ" = 104
"SHIP" = 101
"END_RETURN" = 1008
"INV_ADJUST" = 201
"LEAD_LOST" = 4
"BEGIN_FADJ" = 1025
"FINV_ADJUST" = 202

```

"END_ANET" = 1014
The facttable is:
  Order
The limitvalues are:
The access limitations are:
The limitvalues are:
The header took 261 milliseconds.
Parsing took 160 milliseconds.
Generating the header took 0 milliseconds.
Building user limits took 0 milliseconds.

  Phase 0: Aggregate navigator initialization.
  Phase 1: Getting dimensions from SQL. ( 10 )
  Phase 2: Getting fields available from SQL. ( 90 )
  Phase 3: Getting degenerate fields from SQL. ( 0 )

Phase 0: Preparing for query building and execution.R2[0 -> 0] = (SUM(Z0))
R1[0] = SUM(Z0)

The column router:
  Cell location 0 will be returned in column 0 when Type is SHIP.
The result router:
  Result location 0 is (SUM(Z0)) 0

The unique facttables are:Order
The number of unique facttables are: 1

The unique types are:SHIP
Table to unique number lookup
  Order => _0_

Begin work on the query based on the facttable Order
Phase 1: Table Order. Creating table aliases ( 10 )
JOIN_FIELD IS CUSTOMER_BILLTO_KEY FOR Customer
JOIN_FIELD IS FOR Fiscal Year

SQL table aliases:
  Order[] : T3
  Date[] : T2
  Customer[]CUSTOMER_BILLTO_KEY : T1
Table aliases:
  tablealiaslookup(T1) = Customer
  tablealiaslookup(T2) = Date
  tablealiaslookup(T3) = Order
selectalias:
  Customer: T1.base_name
  Fiscal Year: T2.fy_name
selectstackalias:
  -SUM(Order.net_price): -SUM(T3.net_price)
joinalias:
  Customer: T1.customer_key = T3.customer_billto_key
Phase 2: Building SELECT clause ( 0 )
Phase 3: Building FROM clause ( 0 )
Phase 4: Building WHERE clause ( 0 )
Phase 5: Building GROUP BY clause ( 0 )

SQL before going through the aggregate navigator:
SELECT
  Columns = T2.fy_name,
  Type = T3.Transtype_key,
  C0 = -SUM(T3.net_price),
  Rows = T1.base_name
INTO #tmp_0_
FROM
  Customer T1,
  Date T2,
  Order T3

```

```

WHERE
  T1.customer_key = T3.customer_billto_key and
  T2.date_key = T3.date_key and
  T3.Transtype_key in (101)
GROUP BY
  T1.base_name,
  T2.fy_name,
  T3.Transtype_key

*****
Selecting appropriate aggregate for the query.
*****
Phase 0: Aggregate navigator. Preparing for query building and execution.
Phase 1: Splitting query into clauses. ( 0 )
Phase 2: Construction of aliases. ( 0 )
Phase 3: Extracting neededfields from where clause. ( 0 )
Phase 4: Extracting neededfields from group by clause. ( 0 )
Phase 5: Extracting neededfields from select clause. ( 0 )
Phase 6: Unaliasing. ( 0 )
Phase 7: Constructing the SQL to fetch smallest aggregate. ( 20 )
Phase 8: Running the big SQL. ( 20 )
Phase 9: Extracting results from the big SQL. ( 0 )
Phase 10: Adjusting input with aggregate information. ( 0 )
Phase 6: Aggregate Navigating ( 40 )

*****
Appropriate aggregate determined (CUSTOMER_0, DATE_4, ORDER_86), now select
*****
SQL after going through the aggregate navigator:
SELECT
  Columns = T2.fy_name,
  Type = T3.Transtype_key,
  C0 = -SUM(T3.net_price),
  Rows = T1.base_name
INTO #tmp_0_
FROM
  CUSTOMER_0 T1,
  DATE_4 T2,
  Order_86 T3
WHERE
  T1.customer_key = T3.customer_billto_key and
  T2.date_key = T3.date_key and
  T3.Transtype_key in (101)
GROUP BY
  T1.base_name,
  T2.fy_name,
  T3.Transtype_key

Phase 7: Building results table in sql ( 10435 )
Phase 15: Splitting tables by type (needed = 0) ( 0 )
Phase 16: Merging results into one table (needed = 0) ( 0 ) GR_COLS = C0 = SUM(C0)

SQL: SELECT Rows INTO #tmpAllRows FROM #tmp_0_ GROUP BY Rows ORDER BY SUM(C0) DESC
SQL: SELECT count(Rows) FROM #tmpAllRows
Phase 17: Extracting rows and doing number of total records (10508/10498) ( 1022 )
SQL: set rowcount 10
SELECT Rows INTO #tmpTopRows FROM #tmpAllRows
set rowcount 0

Phase 19: Sorting, Top (needed = 10498) ( 10 )

-- creating row totals
SELECT
  #tmp_0_.Rows,
  C0 = SUM(C0)
INTO #tmpRows
FROM #tmp_0_, #tmpTopRows
WHERE #tmp_0_.Rows = #tmpTopRows.Rows
GROUP BY #tmp_0_.Rows

```

```

-- creating col, grand totals
SELECT
    Columns,
    C0 = SUM(C0)
INTO #tmpColumns
FROM #tmp_0
GROUP BY Columns

Checking ADJ of GRAND

SQL: SELECT C0 = SUM(C0) INTO #tmpGrand FROM #tmpColumns

-- final results table
SELECT #tmp_0.Rows, Columns, C0
INTO #tmpFinalResults
FROM #tmp_0, #tmpTopRows
WHERE #tmp_0.Rows = #tmpTopRows.Rows

Phase 20: Filtering results    ( 841 )
Phase 21: Reading Row Totals  ( 10 )
Phase 22: Reading Column Totals ( 10 )
Phase 23: Reading Grand      ( 10 )
SQL:
-- calculate remaining columns
SELECT
    Columns = #tmpColumns.Columns,
    C0 = #tmpColumns.C0 - ISNULL(SUM(#tmpFinalResults.C0),0)
INTO #tmpRemaining
FROM #tmpFinalResults, #tmpColumns
WHERE #tmpColumns.Columns *= #tmpFinalResults.Columns
GROUP BY #tmpColumns.Columns, #tmpColumns.C0
select C0 = SUM(C0) from #tmpRemaining

Phase 24: Reading Remaining Column Totals (needed = 10498)    ( 20 )
Phase 25: Final Results    ( 30 )
Phase 26: Sorting columns by time (if necessary).    ( 20 )
Phase 27: sorting rows by time or name (if necessary).    ( 0 )ERR FROM BUILD_AND_EXEC:0

Getting results took 12658 milliseconds.

Phase 0: Beginning output generation.
Phase 3: performing cumulative (if necessary).    ( 0 )

Dollar Amount / Shipped / Gross
The columns are: 1994
                 1995
                 1996
                 1997
                 1998

The rows are: ***** A number of customer names here *****

The table headers are:
The contents of the results array are:
*****
A number of customer name, value pairs
*****

The contents of the rowtotal array are:<
key: *****Row totals*****<
...

The contents of the coltotal array are:
1995: *****An amount*****
1996: *****An amount*****
1997: *****An amount*****
1998: *****An amount*****
1994: *****An amount*****

The contents of the grdtotal array are:
Grand: *****A grand total amount*****

Processing and formatting results took 220 milliseconds.

```

Total time was 13299 milliseconds.
Processing sylk took 81 milliseconds.

Figure 36 illustrates the options form 3600 that the user can use to select the display options for a result.

Alternative Embodiments

5 The following describes alternative embodiments of the invention.

Importantly, various embodiments of the invention do not necessarily include all of the features described above. For example, some embodiments of the invention do not include the first phase of the extraction process (loading the staging tables) because the source system data is provided to the system 100 directly by other extraction programs. Another example is where the datamart 150 is created, but a separate query interface is used to query the datamart 150. The query interface could use only a different communications protocol (e.g., instead of HTTP), or could be a completely different front end.

Other embodiments of the invention are configured differently than the embodiments described above. For example, the extraction node key in the semantic instance table 308 is not included, but the extraction node 410 includes a semantic instance key.

Some embodiments of the invention build a database system, not necessarily a datamart. Additionally, these embodiments do not have to conform to a star schema definition in the metadata 160.

An object database system could be generated instead of a relational database system.

Some embodiments of the invention comprise only a computer readable media (e.g., a CD, a tape, a hard drive or other storage media) that has the programs that implement all, or a portion of, the system 100. Some embodiments of the invention include an electromagnetic waveform having the programs. Some embodiments of the invention include only the computer system running the datamart, other embodiments of the invention include only the computer system that creates, accesses, and queries the datamart, but does not include in the datamart itself.

Additional, or different, data semantics can be included in other embodiments of the invention.

Some embodiments of the invention include different user interfaces for the enterprise manager interface 192 and the query/results interface 184. For example, in the enterprise manager interface 192, the semantic types need not be selected in the fact and dimension base windows, but can be selected in the semantic instance window.

The Claims

What is claimed is:

1. A method of creating a system for creating a well-formed database system using a computer, the method comprising:

5 the computer accessing a definition of the system, the definition defining a schema for use by the system, the schema defining a set of tables, a set of columns that correspond to the set of tables, and a set of relationships between the tables of the set of tables, the definition further defining a set of operations for manipulating the data, the set of operations defining programs that operate on the set of tables and the set of table columns; and
10 the computer using the definition to generate the set of tables.

2. The method of claim 1 wherein the set of tables includes a first table and a second table, wherein the first table includes a first column, wherein the second table includes a second column, and wherein the first column and the second column are related by a join and are therefore guaranteed to be from the same domain.

15 3. The method of claim 1 wherein the set of tables includes a first table and a second table, and wherein the definition defines that the first table relates to the second table by a many to one relationship, and wherein the generating the set of tables includes automatically generating a

foreign key column in the first table, wherein the foreign key column is for holding a foreign key to the second table.

4. The method of claim 1 wherein the set of tables includes a first table and a second table, and wherein the definition defines that the first table relates to the second table by a many to many relationship, and wherein the generating the set of tables includes automatically generating an associative table corresponding to the first table and the second table, and wherein the associative table has a unique value created for each unique many-to-many relationship between the first table and the second table.

5. The method of claim 1 wherein the set of tables includes a first table and a second table, and wherein the first table includes one or more columns from the second table, and wherein said one or more columns are automatically populated from the one or more columns.

6. The method of claim 1 wherein the computer using the definition to generate the set of tables also includes the computer performing at least some of the set of operations on at least some of the set of tables.

7. The method of claim 1 wherein a transaction type column is automatically included in some tables of the set of tables.

8. The method of claim 1 wherein a date column is automatically included in some tables of the set of tables.

9. The method of claim 1 wherein a source system key column is automatically included in some tables of the set of tables.

5 10. The method of claim 1 wherein the definition defines a set of source system extraction operations, wherein the set of source system extraction operations are for extracting data from a source system and for manipulating the data for populating the database, and wherein the set of source system extraction operations correspond to the schema definition.

10 11. The method of claim 10 wherein the source system extraction operations correspond to the schema definition by populating source system data into the database system according the schema definition.

12. The method of claim 1 wherein the definition defines a set of aggregates for the database system, the set of aggregates corresponding to the schema definition, the method further comprising:

15 the computer using the definition to create a set of aggregate tables corresponding to the set of aggregates; and
populating the set of aggregate tables.

13. The method of claim 12 wherein the set of aggregates corresponds to the schema definition by defining which aggregates should be made from which tables in the database system.

14. The method of claim 12 wherein the definition defines an aggregate operation for an aggregate of the set of aggregates.

15. The method of claim 14 wherein the aggregate operation includes a SUM operation.

16. The method of claim 14 wherein the aggregate operation includes an AVERAGE operation.

17. The method of claim 1 wherein the definition includes a user interface definition for querying the database and for presenting results, the user interface definition corresponding to the schema definition.

18. The method of claim 17 wherein the user interface definition specifies which columns from which tables can be used in a query.

19. The method of claim 1 wherein the definition defines a set of source system extraction operations, a set of aggregates, and a user interface definition, that correspond to the schema definition.

20. The method of claim 1 wherein the database system includes a datamart, wherein the schema definition includes a star schema definition, wherein the set of tables includes a set of fact tables and a set of dimension tables.

21. A system comprising:

5 a database system;

a first program for accessing a definition of the schema for the database system, the schema defining a set of tables, a set of columns corresponding to the set of tables, and a set of relationships between the tables of the set of tables, the definition further defining a set of operations for manipulating the data, the set of operations defining programs that operate on the set of tables and the set of table columns, the first program further for using the definition to generate the set of tables.

22. The system of claim 21 wherein the set of tables includes a first table and a second table, wherein the first table includes a first column, wherein the second table includes a second column, and wherein the first column and the second column are related by a join and are
15 therefore guaranteed to be from the same domain.

23. The system of claim 21 wherein the set of tables includes a first table and a second table, and wherein the definition defines that the first table relates to the second table by a many to one relationship, and wherein the generating the set of tables includes automatically generating a

foreign key column in the first table, wherein the foreign key column is for holding a foreign key to the second table.

24. The system of claim 21 wherein the set of tables includes a first table and a second table, and wherein the definition defines that the first table relates to the second table by a many to many relationship, and wherein the generating the set of tables includes automatically generating an associative table corresponding to the first table and the second table, and wherein the associative table has a unique value created for each unique many-to-many relationship between the first table and the second table.

25. The system of claim 21 wherein the set of tables includes a first table and a second table, and wherein the first table includes one or more columns from the second table, and wherein said one or more columns are automatically populated from the one or more columns.

26. The system of claim 21 wherein the first program includes an enterprise manager for accessing the definition, causing the generation of the set of tables, and causing the population of the tables.

27. The system of claim 21 further comprising a database, the database for storing the set of tables.

28. The system of claim 21 further comprising an aggregate building program for accessing a definition of a set of aggregates and the definition of the schema and for generating the set of aggregates from the definition of the set of aggregates and the definition of the schema.

29. The system of claim 21 further comprising a query and reporting program for generating
5 a user interface from a definition of the user interface and the definition of the schema.

30. A system comprising:

means for accessing a definition of the system, the definition defining a schema for use by
the system, the schema defining a set of tables, a set of columns corresponding to the set
of tables, and a set of relationships between the tables of the set of tables, the definition
further defining a set of operations for manipulating the data, the set of operations
defining programs that operate on the set of tables and the set of table columns; and
means for using the definition to generate the set of tables.

31. The system of claim 30 wherein the set of tables includes a first table and a second table,
wherein the first table includes a first column, wherein the second table includes a second
15 column, and wherein the first column and the second column are related by a join and are
therefore guaranteed to be from the same domain.

32. The system of claim 30 wherein the set of tables includes a first table and a second table,
and wherein the definition defines that the first table relates to the second table by a many to one

relationship, and wherein the generating the set of tables includes automatically generating a foreign key column in the first table, wherein the foreign key column is for holding a foreign key to the second table.

33. The system of claim 30 wherein the set of tables includes a first table and a second table,
5 and wherein the definition defines that the first table relates to the second table by a many to many relationship, and wherein the generating the set of tables includes automatically generating an associative table corresponding to the first table and the second table, and wherein the associative table has a unique value created for each unique many-to-many relationship between the first table and the second table.

34. The system of claim 30 wherein the set of tables includes a first table and a second table,
10 and wherein the first table includes one or more columns from the second table, and wherein said one or more columns are automatically populated from the one or more columns.

35. The system of claim 34 wherein the definition of the system further includes a definition of the aggregates for the system, the system further comprising:

15 means for generating a set of aggregates from the definition of the aggregates and the definition of the schema.

36. The system of claim 33 wherein the definition of the system further includes a definition of the a user interface for the system, the system further comprising:

means for generating the user interface from the definition of the user interface and the definition of the schema.

37. The system of claim 33 wherein the definition of the system includes a definition of aggregates for use in the system and a definition of a query and reporting mechanism interface for the system, the set of tables includes a set of fact tables and a set of dimension tables, and wherein the system further comprises:

means for generating the set of fact tables;

means for generating the set of dimension tables;

means for generating a set of aggregate tables; and

means for generating a query and reporting mechanism interface.

38. A computer program product comprising:

a memory medium; and

a computer program stored on the memory medium, the computer program comprising

instructions for accessing a definition of a system, the definition defining a schema for

use by the system, the schema defining a set of tables, a set of columns corresponding to

the set of tables, and a set of relationships between the tables of the set of tables, the

definition further defining a set of operations for manipulating the data, the set of

operations defining programs that operate on the set of tables and the set of table

columns, and instructions for using the definition to generate the set of tables.

39 The computer program product of claim 38 wherein the set of tables includes a first table and a second table, wherein the first table includes a first column, wherein the second table includes a second column, and wherein the first column and the second column are related by a join and are therefore guaranteed to be from the same domain.

5 40. The computer program product of claim 38 wherein the set of tables includes a first table and a second table, and wherein the definition defines that the first table relates to the second table by a many to one relationship, and wherein the generating the set of tables includes automatically generating a foreign key column in the first table, wherein the foreign key column is for holding a foreign key to the second table.

10 41. The computer program product of claim 38 wherein the set of tables includes a first table and a second table, and wherein the definition defines that the first table relates to the second table by a many to many relationship, and wherein the generating the set of tables includes automatically generating an associative table corresponding to the first table and the second table, and wherein the associative table has a unique value created for each unique many-to-many
15 relationship between the first table and the second table.

42. The computer program product of claim 38 wherein the set of tables includes a first table and a second table, and wherein the first table includes one or more columns from the second table, and wherein said one or more columns are automatically populated from the one or more columns.

43. A computer data signal embodied in a carrier wave comprising:

a computer program, the computer program comprising instructions for accessing a definition of a system, the definition defining a schema for use by the system, the schema defining a set of tables, a set of columns corresponding to the set of tables, and a set of relationships between the tables of the set of tables, the definition further defining a set of operations for manipulating the data, the set of operations defining programs that operate on the set of tables and the set of table columns, and instructions for using the definition to generate the set of tables.

44. The computer data signal embodied in the carrier wave of claim 43 wherein the set of tables includes a first table and a second table, wherein the first table includes a first column, wherein the second table includes a second column, and wherein the first column and the second column are related by a join and are therefore guaranteed to be from the same domain.

45. The computer data signal embodied in the carrier wave of claim 43 wherein the set of tables includes a first table and a second table, and wherein the definition defines that the first table relates to the second table by a many to one relationship, and wherein the generating the set of tables includes automatically generating a foreign key column in the first table, wherein the foreign key column is for holding a foreign key to the second table.

46. The computer data signal embodied in the carrier wave of claim 43 wherein the set of tables includes a first table and a second table, and wherein the definition defines that the first

table relates to the second table by a many to many relationship, and wherein the generating the set of tables includes automatically generating an associative table corresponding to the first table and the second table, and wherein the associative table has a unique value created for each unique many-to-many relationship between the first table and the second table.

- 5 47. The computer data signal embodied in the carrier wave of claim 43 wherein the set of tables includes a first table and a second table, and wherein the first table includes one or more columns from the second table, and wherein said one or more columns are automatically populated from the one or more columns.

The Abstract

A method of defining a well-formed database system by defining the organization of the data in the database, and by defining the operations for that data, is described. The definition can be used to automatically create and populate the well-formed database system. The well-formed database system conforms to rules of correctness and produces results that conform to the rules. The organization is defined by a data organization definition that specifies tables, their columns, and the relationships between tables. The operations define procedures that operate on the tables and the table columns. Importantly, the operations are defined along with the tables, columns, and relationships, so that the resulting system is well-formed.

Appendix A

Appendix A illustrates semantic types that may be supported and their corresponding adaptive template names. For example, the Pipelined semantic type is made up of, in this order, the map_keys the pipe_state and the index_fact adaptive templates. The example pre-parsed and post parsed SQL adaptive templates are then provided.

As mentioned previously, the use of the semantic types significantly reduces the amount of work needed to implement the datamart 150. By selecting a semantic type for a particular fact table or dimension table, the consultant automatically selects the corresponding pre-parsed SQL adaptive templates. The selected adaptive templates are then automatically converted into post parsed SQL statements that include the schema specific information for the datamart 150. Additionally, these post parsed SQL statements include the SQL for accessing and manipulating the datamart 150 tables.

semantic_type_name	adaptive_template_name
Pipelined	map_keys
Pipelined	pipe_state
Pipelined	index_fact
Pipelined/Unjoined	upd_unj
Pipelined/Unjoined	map_keys
Pipelined/Unjoined	pipe_state
Pipelined/Unjoined	index_fact
Slowly Changing Dimensions	insert_dim
Slowly Changing Dimensions	index_dim
Transactional	map_keys
Transactional	load_trans
Transactional	ren_trans
Transactional	index_fact
Transactional/Inventory	map_keys

Transactional/Inventory	load_trans
Transactional/Inventory	inv_adjust
Transactional/Inventory	index_fact
Transactional/Inventory/ForceZero	map_keys
Transactional/Inventory/ForceZero	load_trans
Transactional/Inventory/ForceZero	force_zero
Transactional/Inventory/ForceZero	inv_adjust
Transactional/Inventory/ForceZero	index_fact
Transactional/Inventory/ForceZero/Unjoined	upd_unj
Transactional/Inventory/ForceZero/Unjoined	map_keys
Transactional/Inventory/ForceZero/Unjoined	load_trans
Transactional/Inventory/ForceZero/Unjoined	force_zero
Transactional/Inventory/ForceZero/Unjoined	inv_adjust
Transactional/Inventory/ForceZero/Unjoined	index_fact
Transactional/Inventory/Unjoined	upd_unj
Transactional/Inventory/Unjoined	map_keys
Transactional/Inventory/Unjoined	load_trans
Transactional/Inventory/Unjoined	inv_adjust
Transactional/Inventory/Unjoined	index_fact
Transactional/Statelike	map_keys
Transactional/Statelike	load_trans
Transactional/Statelike	load_state
Transactional/Statelike	index_fact
Transactional/Statelike/ForceClose	map_keys
Transactional/Statelike/ForceClose	load_trans
Transactional/Statelike/ForceClose	force_close
Transactional/Statelike/ForceClose	load_state
Transactional/Statelike/ForceClose	index_fact
Transactional/Statelike/ForceClose/Unjoined	upd_unj
Transactional/Statelike/ForceClose/Unjoined	map_keys
Transactional/Statelike/ForceClose/Unjoined	load_trans
Transactional/Statelike/ForceClose/Unjoined	force_close
Transactional/Statelike/ForceClose/Unjoined	load_state

Transactional/Statelike/ForceClose/Unjoined	index_fact
Transactional/Statelike/Unjoined	upd_unj
Transactional/Statelike/Unjoined	map_keys
Transactional/Statelike/Unjoined	load_trans
Transactional/Statelike/Unjoined	load_state
Transactional/Statelike/Unjoined	index_fact
Transactional/Unjoined	upd_unj
Transactional/Unjoined	map_keys
Transactional/Unjoined	load_trans
Transactional/Unjoined	ren_trans
Transactional/Unjoined	index_fact

The following are the pre-parsed pseudo-SQL source for the adaptive templates.

```
--#TEMPLATE_BEGIN# force_close

/*****
--
-- Copyright * 1997, Epiphany Marketing Software, Inc. All Rights Reserved.
-- force_close
-- Close out deleted orders - those that no longer appear in the
-- staging table
-- SEE SAFETY VALVE BELOW
--
*****/

/*****
-- Delete temporary tables
*****/

--#BLOCK_BEGIN# DropTemps

$$DDL_BEGIN
$$DROP_TABLE_IF_EXISTS[$$FCTTBL[]_FC]
$$DDL_END

--#BLOCK_END# DropTemps

/*****
-- Insert negative BOOKs for deleted orders
--
-- FC: ForceClose
*****/

--#BLOCK_BEGIN# MakeFC

$$SELECT_INTO_BEGIN[$$FCTTBL[]_FC]
SELECT
    f.iss,
    f.ss_key,
    MAX(f.date_key) date_key,
    MIN(f.transtype key) transtype key,
```



```

OR      (SUM(f.$$FCTCOL_007) <> 0)
OR      (SUM(f.$$FCTCOL_008) <> 0)
OR      (SUM(f.$$FCTCOL_009) <> 0)
OR      (SUM(f.$$FCTCOL_010) <> 0)
OR      (SUM(f.$$FCTCOL_011) <> 0)
OR      (SUM(f.$$FCTCOL_012) <> 0)
OR      (SUM(f.$$FCTCOL_013) <> 0)
OR      (SUM(f.$$FCTCOL_014) <> 0)
OR      (SUM(f.$$FCTCOL_015) <> 0)
OR      (SUM(f.$$FCTCOL_016) <> 0)
OR      (SUM(f.$$FCTCOL_017) <> 0)
OR      (SUM(f.$$FCTCOL_018) <> 0)
OR      (SUM(f.$$FCTCOL_019) <> 0)
OR      (SUM(f.$$FCTCOL_020) <> 0)
OR      (SUM(f.$$FCTCOL_021) <> 0)
OR      (SUM(f.$$FCTCOL_022) <> 0)
OR      (SUM(f.$$FCTCOL_023) <> 0)
OR      (SUM(f.$$FCTCOL_024) <> 0)
)
AND
    MIN(f.transtype_key) <= 99
AND
    MIN(f.transtype_key) >= 1

--#BLOCK_END# MakeFC

/*****/
-- SAFETY VALVE - THIS PROC ONLY DOES ANYTHING
-- IF THE STAGING TABLE HAS AT LEAST ONE ROW
/*****/

--#BLOCK_BEGIN# SafetyValue

DECLARE $$VAR[count_MAP] $$EPIINT$$EOS

BEGIN

$$VAR_ASSIGN_BEGIN[count_MAP]
SELECT COUNT(1)
$$VAR_ASSIGN_INTO[count_MAP]
FROM $$FSTGTBL[]_MAP
$$VAR_ASSIGN_END

$$IF[($$VAR[count_MAP] = 0)]
DELETE FROM $$FCTTBL[]_FC$$EOS
$$END_IF

END$$EOS

--#BLOCK_END# SafetyValue

/*****/
-- Count processed, inserted rows
/*****/

--#BLOCK_BEGIN# SPResults

BEGIN

INSERT INTO adaptive_template_profile (token_name, number_rows)
SELECT 'PROCESSED', COUNT(1) FROM $$FCTTBL[]_FC$$EOS

INSERT INTO adaptive_template_profile (token_name, number_rows)
SELECT 'INSERTED', COUNT(1) FROM $$FCTTBL[]_FC$$EOS

END$$EOS

--#BLOCK_END# SPResults

--#TEMPLATE_END# force_close

```

```
--#TEMPLATE_BEGIN# load_state

/*****/
--
-- Copyright * 1997, Epiphany Marketing Software, Inc. All Rights Reserved.
--
-- load_state
--
-- Load order bookings into fact table by creating transactional
-- data from state data
--
-- load_trans must be run before this procedure to create TIN table
--
/*****/

/*****/
-- Delete temporary tables
/*****/

--#BLOCK_BEGIN# DropTemps

$$DDL_BEGIN
$$DROP_TABLE_IF_EXISTS[$$FCTTBL[]_MFL]
$$DROP_TABLE_IF_EXISTS[$$FCTTBL[]_1ST]
$$DROP_TABLE_IF_EXISTS[$$FCTTBL[]_IL]
$$DROP_TABLE_IF_EXISTS[$$FCTTBL[]_IR]
$$DROP_TABLE_IF_EXISTS[$$FCTTBL[]_IRD]
$$DROP_TABLE_IF_EXISTS[$$FCTTBL[]_IND]
$$DROP_TABLE_IF_EXISTS[$$FCTTBL[]_NFD]
$$DROP_TABLE_IF_EXISTS[$$FCTTBL[]_IRM]
$$DROP_TABLE_IF_EXISTS[$$FCTTBL[]_IDM]
$$DROP_TABLE_IF_EXISTS[$$FCTTBL[]_ILM]
$$DROP_TABLE_IF_EXISTS[$$FCTTBL[]_IMI]
$$DDL_END

--#BLOCK_END# DropTemps

/*****/
-- Set join order for SQL Server
/*****/

--#BLOCK_BEGIN# ForcePlanOn

$$SQLSERVER[SET FORCEPLAN ON]

--#BLOCK_END# ForcePlanOn

/*****/
-- Remove rows older than fact table - history can not be rewritten - only
-- the last date for an order can be changed. Note that we compare transtype's
-- because SHIP type transactions might occur at a later date and we don't want
-- those to interfere
--
-- Also, since the staging table may have multiple entries for a given order on
-- a single day - we assume that the list one inserted in the Staging table will
-- be used (since ikey is an IDENTITY column)
--
-- Note that a given ss_key must use the same Booking transtype for all of time,
-- otherwise the transtype_key
--
-- MFL: Mapped Filtered
/*****/

--#BLOCK_BEGIN# MakeMFL

$$SELECT_INTO_BEGIN[$$FCTTBL[]_MFL]
SELECT
    s.*
$$SELECT_INTO_BODY[$$FCTTBL[]_MFL]
FROM
```

```

WHERE    $$FSTGTBL[]_MAP s, bus_process b
        ((s.date_key >= (SELECT MAX(date_key) FROM $$FCTTBL[]$$CURR f WHERE
            s.iss = f.iss AND s.ss_key = f.ss_key AND
            s.transtype_key = f.transtype_key))
OR NOT EXISTS (SELECT * FROM $$FCTTBL[]$$CURR f WHERE
            s.iss = f.iss AND s.ss_key = f.ss_key AND
            s.transtype_key = f.transtype_key))
AND      s.ikey = (SELECT MAX(t.ikey) FROM $$FSTGTBL[]_MAP t WHERE
            s.iss = t.iss AND
            s.ss_key = t.ss_key AND
            s.date_key = t.date_key AND
            t.process_key = b.process_key)
AND
        s.process_key = b.process_key AND b.process_name = 'LoadState'

--#BLOCK_END# MakeMFL

/*****/
-- Index MFL table for later queries
/*****/

--#BLOCK_BEGIN# IndexMFL

$$DDL_BEGIN
$$DDL_EXEC[
CREATE INDEX X$$FCTTBL[]_MFL ON $$FCTTBL[]_MFL
(
    iss, ss_key, date_key
)
]
$$DDL_END

--#BLOCK_END# IndexMFL

/*****/
-- Get oldest state rows for each unique sskey
--
-- We need to treat the first entry for each order
-- in the staging table separately from all others, since
-- only the first entry needs to be compared with
-- already existing fact entry rows to create transactions.
-- All subsequent dates for that order in the Fact table
-- can be delta'd with other staging table entries - see the
-- section below on Pairwise deltas.
--
-- MFL should be indexed
--
-- 1ST: The first record for each iss, ss_key
/*****/

--#BLOCK_BEGIN# Make1ST

$$SELECT_INTO_BEGIN[$$FCTTBL[]_1ST]
SELECT
    s.*
$$SELECT_INTO_BODY[$$FCTTBL[]_1ST]
FROM
    $$FCTTBL[]_MFL s
WHERE
    s.date_key = (SELECT MIN(date_key) FROM $$FCTTBL[]_MFL t WHERE
        s.iss = t.iss AND s.ss_key = t.ss_key)

--#BLOCK_END# Make1ST

/*****/
-- Index 1ST for later queries
/*****/

--#BLOCK_BEGIN# Index1ST

```

```

$$DDL_BEGIN
$$DDL_EXEC[
CREATE UNIQUE INDEX XPK$$FCTTBL[]_1ST ON $$FCTTBL[]_1ST
(
    iss, ss_key
)
]
$$DDL_END

--#BLOCK_END# Index1ST

/*****/
-- Insert negative BOOKs for changed dim keys
--
-- This query will add up all existing Books and Loss's
-- for this order and the net facts will be cancelled out
-- with the old Dimension keys. Note that an invariant of this
-- procedure is that only one set of dimensions at a time
-- can have non-zero facts.
--
-- Fact table Should be indexed
--
-- HAVING Clause is needed to prevent changing of dimensions
-- on fully shipped order from causing a transaction - no sense
-- creating fact rows with all zero's in them
--
-- Note that we increment the sequence number just in case
-- this new transaction occurs on the same date as the last
-- existing one in the fact table - to avoid index errors
--
-- IL: InsertLost
/*****/

--#BLOCK_BEGIN# MakeIL

$$SELECT_INTO_BEGIN[$$FCTTBL[]_IL]
SELECT
    s.iss,
    s.ss_key,
    s.date_key,
    s.transtype_key,
    MAX(f.seq) + 1 seq
,
    f.$$DIMKEYR_01
,
    f.$$DIMKEYR_02
,
    f.$$DIMKEYR_03
,
    f.$$DIMKEYR_04
,
    f.$$DIMKEYR_05
,
    f.$$DIMKEYR_06
,
    f.$$DIMKEYR_07
,
    f.$$DIMKEYR_08
,
    f.$$DIMKEYR_09
,
    f.$$DIMKEYR_10
,
    f.$$DEGKEY_01
,
    f.$$DEGKEY_02
,
    f.$$DEGKEY_03
,
    -SUM(f.$$FCTCOL_001) $$FCTCOL_001
,
    -SUM(f.$$FCTCOL_002) $$FCTCOL_002
,
    -SUM(f.$$FCTCOL_003) $$FCTCOL_003
,
    -SUM(f.$$FCTCOL_004) $$FCTCOL_004
,
    -SUM(f.$$FCTCOL_005) $$FCTCOL_005
,
    -SUM(f.$$FCTCOL_006) $$FCTCOL_006
,
    -SUM(f.$$FCTCOL_007) $$FCTCOL_007
,
    -SUM(f.$$FCTCOL_008) $$FCTCOL_008
,
    -SUM(f.$$FCTCOL_009) $$FCTCOL_009
,
    -SUM(f.$$FCTCOL_010) $$FCTCOL_010
,
    -SUM(f.$$FCTCOL_011) $$FCTCOL_011
,
    -SUM(f.$$FCTCOL_012) $$FCTCOL_012
,
    -SUM(f.$$FCTCOL_013) $$FCTCOL_013
,
    -SUM(f.$$FCTCOL_014) $$FCTCOL_014
,
    -SUM(f.$$FCTCOL_015) $$FCTCOL_015

```

```

,      -SUM(f.$$FCTCOL_016) $$FCTCOL_016
,      -SUM(f.$$FCTCOL_017) $$FCTCOL_017
,      -SUM(f.$$FCTCOL_018) $$FCTCOL_018
,      -SUM(f.$$FCTCOL_019) $$FCTCOL_019
,      -SUM(f.$$FCTCOL_020) $$FCTCOL_020
,      -SUM(f.$$FCTCOL_021) $$FCTCOL_021
,      -SUM(f.$$FCTCOL_022) $$FCTCOL_022
,      -SUM(f.$$FCTCOL_023) $$FCTCOL_023
,      -SUM(f.$$FCTCOL_024) $$FCTCOL_024

$$SELECT INTO BODY[$$FCTTBL[]_IL]
FROM      $$FCTTBL[]_1ST s, $$FCTTBL[]$$CURR f
WHERE     s.iss = f.iss AND s.ss_key = f.ss_key
AND
      ((s.$$DIMKEYR_06 <> f.$$DIMKEYR_06) OR
      (s.$$DIMKEYR_05 <> f.$$DIMKEYR_05) OR
      (s.$$DIMKEYR_07 <> f.$$DIMKEYR_07) OR
      (s.$$DIMKEYR_04 <> f.$$DIMKEYR_04) OR
      (s.$$DIMKEYR_08 <> f.$$DIMKEYR_08) OR
      (s.$$DIMKEYR_03 <> f.$$DIMKEYR_03) OR
      (s.$$DIMKEYR_09 <> f.$$DIMKEYR_09) OR
      (s.$$DIMKEYR_02 <> f.$$DIMKEYR_02) OR
      (s.$$DIMKEYR_10 <> f.$$DIMKEYR_10) OR
      (s.$$DIMKEYR_01 <> f.$$DIMKEYR_01) )
GROUP BY
      s.iss,
      s.ss_key,
      s.date_key,
      s.transtype_key
,      f.$$DIMKEYR_01
,      f.$$DIMKEYR_02
,      f.$$DIMKEYR_03
,      f.$$DIMKEYR_04
,      f.$$DIMKEYR_05
,      f.$$DIMKEYR_06
,      f.$$DIMKEYR_07
,      f.$$DIMKEYR_08
,      f.$$DIMKEYR_09
,      f.$$DIMKEYR_10
,      f.$$DEGKEY_01
,      f.$$DEGKEY_02
,      f.$$DEGKEY_03

HAVING
      MIN(f.transtype_key) = s.transtype_key
AND
      (
OR      (SUM(f.$$FCTCOL_001) <> 0)
OR      (SUM(f.$$FCTCOL_002) <> 0)
OR      (SUM(f.$$FCTCOL_003) <> 0)
OR      (SUM(f.$$FCTCOL_004) <> 0)
OR      (SUM(f.$$FCTCOL_005) <> 0)
OR      (SUM(f.$$FCTCOL_006) <> 0)
OR      (SUM(f.$$FCTCOL_007) <> 0)
OR      (SUM(f.$$FCTCOL_008) <> 0)
OR      (SUM(f.$$FCTCOL_009) <> 0)
OR      (SUM(f.$$FCTCOL_010) <> 0)
OR      (SUM(f.$$FCTCOL_011) <> 0)
OR      (SUM(f.$$FCTCOL_012) <> 0)
OR      (SUM(f.$$FCTCOL_013) <> 0)
OR      (SUM(f.$$FCTCOL_014) <> 0)
OR      (SUM(f.$$FCTCOL_015) <> 0)
OR      (SUM(f.$$FCTCOL_016) <> 0)
OR      (SUM(f.$$FCTCOL_017) <> 0)
OR      (SUM(f.$$FCTCOL_018) <> 0)
OR      (SUM(f.$$FCTCOL_019) <> 0)
OR      (SUM(f.$$FCTCOL_020) <> 0)
OR      (SUM(f.$$FCTCOL_021) <> 0)
OR      (SUM(f.$$FCTCOL_022) <> 0)

```

```

OR      (SUM(f.$$FCTCOL_023) <> 0)
OR      (SUM(f.$$FCTCOL_024) <> 0)
)

--#BLOCK_END# MakeIL

/*****
-- Index IL for later queries
*****/

--#BLOCK_BEGIN# IndexIL

$$DDL_BEGIN
$$DDL EXEC[
CREATE INDEX XPK$$FCTTBL[]_IL ON $$FCTTBL[]_IL
(
    iss, ss_key
)
]
$$DDL_END

--#BLOCK_END# IndexIL

/*****
-- Insert BOOKs for changed dim keys
--
-- When a dimension changes then just create a booking
-- transaction for whatever we negated above with the new
-- dimension and fact values
--
-- 1ST should be indexed
--
-- Note that we add one to whatever we used as the last
-- seq because this transaction occurs on the same
-- date as the negative one above
--
-- IR: Insert Rebook
*****/

--#BLOCK_BEGIN# MakeIR

$$SELECT_INTO_BEGIN[$$FCTTBL[]_IR]
SELECT
    s.iss,
    s.ss_key,
    s.date_key,
    l.transtype_key,
    l.seq + 1 seq
,
    s.$$DIMKEYR_01
,
    s.$$DIMKEYR_02
,
    s.$$DIMKEYR_03
,
    s.$$DIMKEYR_04
,
    s.$$DIMKEYR_05
,
    s.$$DIMKEYR_06
,
    s.$$DIMKEYR_07
,
    s.$$DIMKEYR_08
,
    s.$$DIMKEYR_09
,
    s.$$DIMKEYR_10
,
    s.$$DEGKEY_01
,
    s.$$DEGKEY_02
,
    s.$$DEGKEY_03
,
    -1.$$FCTCOL_001 $$FCTCOL_001
,
    -1.$$FCTCOL_002 $$FCTCOL_002
,
    -1.$$FCTCOL_003 $$FCTCOL_003
,
    -1.$$FCTCOL_004 $$FCTCOL_004
,
    -1.$$FCTCOL_005 $$FCTCOL_005
,
    -1.$$FCTCOL_006 $$FCTCOL_006
,
    -1.$$FCTCOL_007 $$FCTCOL_007
,
    -1.$$FCTCOL_008 $$FCTCOL_008
,
    -1.$$FCTCOL_009 $$FCTCOL_009

```

```

,      -1.$$FCTCOL_010 $$FCTCOL_010
,      -1.$$FCTCOL_011 $$FCTCOL_011
,      -1.$$FCTCOL_012 $$FCTCOL_012
,      -1.$$FCTCOL_013 $$FCTCOL_013
,      -1.$$FCTCOL_014 $$FCTCOL_014
,      -1.$$FCTCOL_015 $$FCTCOL_015
,      -1.$$FCTCOL_016 $$FCTCOL_016
,      -1.$$FCTCOL_017 $$FCTCOL_017
,      -1.$$FCTCOL_018 $$FCTCOL_018
,      -1.$$FCTCOL_019 $$FCTCOL_019
,      -1.$$FCTCOL_020 $$FCTCOL_020
,      -1.$$FCTCOL_021 $$FCTCOL_021
,      -1.$$FCTCOL_022 $$FCTCOL_022
,      -1.$$FCTCOL_023 $$FCTCOL_023
,      -1.$$FCTCOL_024 $$FCTCOL_024

$$SELECT INTO BODY[$$FCTTBL[]_IR]
FROM
    $$FCTTBL[]_IL 1, $$FCTTBL[]_1ST s
WHERE l.iss = s.iss AND l.ss_key = s.ss_key

--#BLOCK_END# MakeIR

/*****
-- Insert BOOKs for changed dim keys where fact
-- also changed
--
-- When a dimension changes at the same time as
-- a fact then we need to make up the fact difference
--
-- 1ST should be indexed
--
-- Note that we add two to whatever we used as the last
-- seq because this transaction occurs on the same
-- date as the negative and positive ones above
--
-- Note also that the Left Outer join uses transtype_key
-- so that only the Bookings at the old value will be counted.
-- Whereas above for the negative transaction value
-- we want to include Shipments in our calculation, here
-- we only want to see how Booking Facts have changed.
--
-- Here again, only one Booking transaction type is supported
-- per ss_key
--
-- IRD: Insert Rebook delta
*****/

--#BLOCK_BEGIN# MakeIRD

$$SELECT INTO BEGIN[$$FCTTBL[]_IRD]
SELECT
    s.iss,
    s.ss_key,
    s.date_key,
    s.transtype_key,
    l.seq + 2 seq
,      s.$$DIMKEYR_01
,      s.$$DIMKEYR_02
,      s.$$DIMKEYR_03
,      s.$$DIMKEYR_04
,      s.$$DIMKEYR_05
,      s.$$DIMKEYR_06
,      s.$$DIMKEYR_07
,      s.$$DIMKEYR_08
,      s.$$DIMKEYR_09
,      s.$$DIMKEYR_10
,      s.$$DEGKEY_01
,      s.$$DEGKEY_02
,      s.$$DEGKEY_03

```



```

, MAX(s.$FCTCOL_001)-$$NVL(SUM(f.$FCTCOL_001) ~,~ 0) $$FCTCOL_001
, MAX(s.$FCTCOL_002)-$$NVL(SUM(f.$FCTCOL_002) ~,~ 0) $$FCTCOL_002
, MAX(s.$FCTCOL_003)-$$NVL(SUM(f.$FCTCOL_003) ~,~ 0) $$FCTCOL_003
, MAX(s.$FCTCOL_004)-$$NVL(SUM(f.$FCTCOL_004) ~,~ 0) $$FCTCOL_004
, MAX(s.$FCTCOL_005)-$$NVL(SUM(f.$FCTCOL_005) ~,~ 0) $$FCTCOL_005
, MAX(s.$FCTCOL_006)-$$NVL(SUM(f.$FCTCOL_006) ~,~ 0) $$FCTCOL_006
, MAX(s.$FCTCOL_007)-$$NVL(SUM(f.$FCTCOL_007) ~,~ 0) $$FCTCOL_007
, MAX(s.$FCTCOL_008)-$$NVL(SUM(f.$FCTCOL_008) ~,~ 0) $$FCTCOL_008
, MAX(s.$FCTCOL_009)-$$NVL(SUM(f.$FCTCOL_009) ~,~ 0) $$FCTCOL_009
, MAX(s.$FCTCOL_010)-$$NVL(SUM(f.$FCTCOL_010) ~,~ 0) $$FCTCOL_010
, MAX(s.$FCTCOL_011)-$$NVL(SUM(f.$FCTCOL_011) ~,~ 0) $$FCTCOL_011
, MAX(s.$FCTCOL_012)-$$NVL(SUM(f.$FCTCOL_012) ~,~ 0) $$FCTCOL_012
, MAX(s.$FCTCOL_013)-$$NVL(SUM(f.$FCTCOL_013) ~,~ 0) $$FCTCOL_013
, MAX(s.$FCTCOL_014)-$$NVL(SUM(f.$FCTCOL_014) ~,~ 0) $$FCTCOL_014
, MAX(s.$FCTCOL_015)-$$NVL(SUM(f.$FCTCOL_015) ~,~ 0) $$FCTCOL_015
, MAX(s.$FCTCOL_016)-$$NVL(SUM(f.$FCTCOL_016) ~,~ 0) $$FCTCOL_016
, MAX(s.$FCTCOL_017)-$$NVL(SUM(f.$FCTCOL_017) ~,~ 0) $$FCTCOL_017
, MAX(s.$FCTCOL_018)-$$NVL(SUM(f.$FCTCOL_018) ~,~ 0) $$FCTCOL_018
, MAX(s.$FCTCOL_019)-$$NVL(SUM(f.$FCTCOL_019) ~,~ 0) $$FCTCOL_019
, MAX(s.$FCTCOL_020)-$$NVL(SUM(f.$FCTCOL_020) ~,~ 0) $$FCTCOL_020
, MAX(s.$FCTCOL_021)-$$NVL(SUM(f.$FCTCOL_021) ~,~ 0) $$FCTCOL_021
, MAX(s.$FCTCOL_022)-$$NVL(SUM(f.$FCTCOL_022) ~,~ 0) $$FCTCOL_022
, MAX(s.$FCTCOL_023)-$$NVL(SUM(f.$FCTCOL_023) ~,~ 0) $$FCTCOL_023
, MAX(s.$FCTCOL_024)-$$NVL(SUM(f.$FCTCOL_024) ~,~ 0) $$FCTCOL_024
,

$$SELECT INTO BODY[$$FCTTBL[]_IRD]
FROM
    $$FCTTBL[]_IL 1, $$FCTTBL[]_1ST s
    $$LOJ_FROM[$$FCTTBL[]]$CURR f ~,~ s.iss = f.iss AND s.ss_key = f.ss_key AND
s.transtype_key = f.transtype_key]
WHERE
    l.iss = s.iss AND l.ss_key = s.ss_key
$$JOIN WHERE[s.iss = f.iss (+) AND s.ss_key = f.ss_key (+) AND s.transtype_key =
f.transtype_key (+)]
GROUP BY
    s.iss,
    s.ss_key,
    s.date_key,
    s.transtype_key,
    l.seq
, s.$DIMKEYR_01
, s.$DIMKEYR_02
, s.$DIMKEYR_03
, s.$DIMKEYR_04
, s.$DIMKEYR_05
, s.$DIMKEYR_06
, s.$DIMKEYR_07
, s.$DIMKEYR_08
, s.$DIMKEYR_09
, s.$DIMKEYR_10
, s.$DEGKEY_01
, s.$DEGKEY_02
, s.$DEGKEY_03

HAVING
    ($$NVL(SUM(f.$FCTCOL_001) ~,~ 0) <> MAX(s.$FCTCOL_001))
OR
    ($$NVL(SUM(f.$FCTCOL_002) ~,~ 0) <> MAX(s.$FCTCOL_002))
OR
    ($$NVL(SUM(f.$FCTCOL_003) ~,~ 0) <> MAX(s.$FCTCOL_003))
OR
    ($$NVL(SUM(f.$FCTCOL_004) ~,~ 0) <> MAX(s.$FCTCOL_004))
OR
    ($$NVL(SUM(f.$FCTCOL_005) ~,~ 0) <> MAX(s.$FCTCOL_005))
OR
    ($$NVL(SUM(f.$FCTCOL_006) ~,~ 0) <> MAX(s.$FCTCOL_006))
OR
    ($$NVL(SUM(f.$FCTCOL_007) ~,~ 0) <> MAX(s.$FCTCOL_007))
OR
    ($$NVL(SUM(f.$FCTCOL_008) ~,~ 0) <> MAX(s.$FCTCOL_008))
OR
    ($$NVL(SUM(f.$FCTCOL_009) ~,~ 0) <> MAX(s.$FCTCOL_009))
OR
    ($$NVL(SUM(f.$FCTCOL_010) ~,~ 0) <> MAX(s.$FCTCOL_010))
OR
    ($$NVL(SUM(f.$FCTCOL_011) ~,~ 0) <> MAX(s.$FCTCOL_011))
OR
    ($$NVL(SUM(f.$FCTCOL_012) ~,~ 0) <> MAX(s.$FCTCOL_012))
OR
    ($$NVL(SUM(f.$FCTCOL_013) ~,~ 0) <> MAX(s.$FCTCOL_013))
OR
    ($$NVL(SUM(f.$FCTCOL_014) ~,~ 0) <> MAX(s.$FCTCOL_014))
OR
    ($$NVL(SUM(f.$FCTCOL_015) ~,~ 0) <> MAX(s.$FCTCOL_015))
OR
    ($$NVL(SUM(f.$FCTCOL_016) ~,~ 0) <> MAX(s.$FCTCOL_016))

```

```

OR      ($$NVL(SUM(f.$$FCTCOL_017) ~,~ 0] <> MAX(s.$$FCTCOL_017))
OR      ($$NVL(SUM(f.$$FCTCOL_018) ~,~ 0] <> MAX(s.$$FCTCOL_018))
OR      ($$NVL(SUM(f.$$FCTCOL_019) ~,~ 0] <> MAX(s.$$FCTCOL_019))
OR      ($$NVL(SUM(f.$$FCTCOL_020) ~,~ 0] <> MAX(s.$$FCTCOL_020))
OR      ($$NVL(SUM(f.$$FCTCOL_021) ~,~ 0] <> MAX(s.$$FCTCOL_021))
OR      ($$NVL(SUM(f.$$FCTCOL_022) ~,~ 0] <> MAX(s.$$FCTCOL_022))
OR      ($$NVL(SUM(f.$$FCTCOL_023) ~,~ 0] <> MAX(s.$$FCTCOL_023))
OR      ($$NVL(SUM(f.$$FCTCOL_024) ~,~ 0] <> MAX(s.$$FCTCOL_024))

--#BLOCK_END# MakeIRD

/*****/
-- Insert BOOKS for deltas with same dim keys OR for
-- brand new orders.
--
-- Note that we DON'T want to count Shipments
-- (so shipment ss_key's should be different from
-- order ss_keys) since we just want bookings to sum up
-- to whatever this transaction says they should be.
--
-- Fact table should be indexed
--
-- WHERE clause prevents double booking on changed
-- dimension - if we didn't use the NOT EXISTS clause
-- then this query would repeat the work of the last one
-- above - which we have already taken care of
--
-- HAVING clause ensures that multiple 0 records don't
-- get inserted whenever this procedure is run
--
-- Note that we increment the sequence number just in case
-- this new transaction occurs on the same date as the last
-- existing one in the fact table - to avoid index errors
--
-- IND: Insert New Delta
/*****/

--#BLOCK_BEGIN# MakeIND

$$SELECT INTO BEGIN[$$FCTTBL[]_IND]
SELECT
    s.iss,
    s.ss_key,
    s.date_key,
    s.transtype_key,
    $$NVL(MAX(f.seq) ~,~ 0] + 1 seq
    ,
    s.$$DIMKEYR_01
    ,
    s.$$DIMKEYR_02
    ,
    s.$$DIMKEYR_03
    ,
    s.$$DIMKEYR_04
    ,
    s.$$DIMKEYR_05
    ,
    s.$$DIMKEYR_06
    ,
    s.$$DIMKEYR_07
    ,
    s.$$DIMKEYR_08
    ,
    s.$$DIMKEYR_09
    ,
    s.$$DIMKEYR_10
    ,
    s.$$DEGKEY_01
    ,
    s.$$DEGKEY_02
    ,
    s.$$DEGKEY_03
    ,
    MAX(s.$$FCTCOL_001)-$$NVL(SUM(f.$$FCTCOL_001) ~,~ 0] $$FCTCOL_001
    ,
    MAX(s.$$FCTCOL_002)-$$NVL(SUM(f.$$FCTCOL_002) ~,~ 0] $$FCTCOL_002
    ,
    MAX(s.$$FCTCOL_003)-$$NVL(SUM(f.$$FCTCOL_003) ~,~ 0] $$FCTCOL_003
    ,
    MAX(s.$$FCTCOL_004)-$$NVL(SUM(f.$$FCTCOL_004) ~,~ 0] $$FCTCOL_004
    ,
    MAX(s.$$FCTCOL_005)-$$NVL(SUM(f.$$FCTCOL_005) ~,~ 0] $$FCTCOL_005
    ,
    MAX(s.$$FCTCOL_006)-$$NVL(SUM(f.$$FCTCOL_006) ~,~ 0] $$FCTCOL_006
    ,
    MAX(s.$$FCTCOL_007)-$$NVL(SUM(f.$$FCTCOL_007) ~,~ 0] $$FCTCOL_007
    ,
    MAX(s.$$FCTCOL_008)-$$NVL(SUM(f.$$FCTCOL_008) ~,~ 0] $$FCTCOL_008
    ,
    MAX(s.$$FCTCOL_009)-$$NVL(SUM(f.$$FCTCOL_009) ~,~ 0] $$FCTCOL_009
    ,
    MAX(s.$$FCTCOL_010)-$$NVL(SUM(f.$$FCTCOL_010) ~,~ 0] $$FCTCOL_010
    ,
    MAX(s.$$FCTCOL_011)-$$NVL(SUM(f.$$FCTCOL_011) ~,~ 0] $$FCTCOL_011

```

```

, MAX(s.$$FCTCOL_012)-$$NVL(SUM(f.$$FCTCOL_012) ~,~ 0] $$FCTCOL_012
, MAX(s.$$FCTCOL_013)-$$NVL(SUM(f.$$FCTCOL_013) ~,~ 0] $$FCTCOL_013
, MAX(s.$$FCTCOL_014)-$$NVL(SUM(f.$$FCTCOL_014) ~,~ 0] $$FCTCOL_014
, MAX(s.$$FCTCOL_015)-$$NVL(SUM(f.$$FCTCOL_015) ~,~ 0] $$FCTCOL_015
, MAX(s.$$FCTCOL_016)-$$NVL(SUM(f.$$FCTCOL_016) ~,~ 0] $$FCTCOL_016
, MAX(s.$$FCTCOL_017)-$$NVL(SUM(f.$$FCTCOL_017) ~,~ 0] $$FCTCOL_017
, MAX(s.$$FCTCOL_018)-$$NVL(SUM(f.$$FCTCOL_018) ~,~ 0] $$FCTCOL_018
, MAX(s.$$FCTCOL_019)-$$NVL(SUM(f.$$FCTCOL_019) ~,~ 0] $$FCTCOL_019
, MAX(s.$$FCTCOL_020)-$$NVL(SUM(f.$$FCTCOL_020) ~,~ 0] $$FCTCOL_020
, MAX(s.$$FCTCOL_021)-$$NVL(SUM(f.$$FCTCOL_021) ~,~ 0] $$FCTCOL_021
, MAX(s.$$FCTCOL_022)-$$NVL(SUM(f.$$FCTCOL_022) ~,~ 0] $$FCTCOL_022
, MAX(s.$$FCTCOL_023)-$$NVL(SUM(f.$$FCTCOL_023) ~,~ 0] $$FCTCOL_023
, MAX(s.$$FCTCOL_024)-$$NVL(SUM(f.$$FCTCOL_024) ~,~ 0] $$FCTCOL_024

$$SELECT INTO BODY[$$FCTTBL[]_IND]
FROM
    $$FCTTBL[]_1ST s $$LOJ FROM[$$FCTTBL[]$$CURR f ~,~
        s.iss = f.iss AND s.ss_key = f.ss_key AND f.transtype_key = s.transtype_key]
WHERE
    NOT EXISTS (SELECT * FROM $$FCTTBL[]_IL WHERE iss = s.iss AND ss_key = s.ss_key)
$$JOIN WHERE[s.iss = f.iss (+) AND s.ss_key = f.ss_key (+) AND s.transtype_key =
f.transtype_key (+)]
GROUP BY
    s.iss,
    s.ss_key,
    s.date_key,
    s.transtype_key
    s.$$DIMKEYR_01
    s.$$DIMKEYR_02
    s.$$DIMKEYR_03
    s.$$DIMKEYR_04
    s.$$DIMKEYR_05
    s.$$DIMKEYR_06
    s.$$DIMKEYR_07
    s.$$DIMKEYR_08
    s.$$DIMKEYR_09
    s.$$DIMKEYR_10
    s.$$DEGKEY_01
    s.$$DEGKEY_02
    s.$$DEGKEY_03

HAVING
    ($$NVL(SUM(f.$$FCTCOL_001) ~,~ 0] <> MAX(s.$$FCTCOL_001))
OR
    ($$NVL(SUM(f.$$FCTCOL_002) ~,~ 0] <> MAX(s.$$FCTCOL_002))
OR
    ($$NVL(SUM(f.$$FCTCOL_003) ~,~ 0] <> MAX(s.$$FCTCOL_003))
OR
    ($$NVL(SUM(f.$$FCTCOL_004) ~,~ 0] <> MAX(s.$$FCTCOL_004))
OR
    ($$NVL(SUM(f.$$FCTCOL_005) ~,~ 0] <> MAX(s.$$FCTCOL_005))
OR
    ($$NVL(SUM(f.$$FCTCOL_006) ~,~ 0] <> MAX(s.$$FCTCOL_006))
OR
    ($$NVL(SUM(f.$$FCTCOL_007) ~,~ 0] <> MAX(s.$$FCTCOL_007))
OR
    ($$NVL(SUM(f.$$FCTCOL_008) ~,~ 0] <> MAX(s.$$FCTCOL_008))
OR
    ($$NVL(SUM(f.$$FCTCOL_009) ~,~ 0] <> MAX(s.$$FCTCOL_009))
OR
    ($$NVL(SUM(f.$$FCTCOL_010) ~,~ 0] <> MAX(s.$$FCTCOL_010))
OR
    ($$NVL(SUM(f.$$FCTCOL_011) ~,~ 0] <> MAX(s.$$FCTCOL_011))
OR
    ($$NVL(SUM(f.$$FCTCOL_012) ~,~ 0] <> MAX(s.$$FCTCOL_012))
OR
    ($$NVL(SUM(f.$$FCTCOL_013) ~,~ 0] <> MAX(s.$$FCTCOL_013))
OR
    ($$NVL(SUM(f.$$FCTCOL_014) ~,~ 0] <> MAX(s.$$FCTCOL_014))
OR
    ($$NVL(SUM(f.$$FCTCOL_015) ~,~ 0] <> MAX(s.$$FCTCOL_015))
OR
    ($$NVL(SUM(f.$$FCTCOL_016) ~,~ 0] <> MAX(s.$$FCTCOL_016))
OR
    ($$NVL(SUM(f.$$FCTCOL_017) ~,~ 0] <> MAX(s.$$FCTCOL_017))
OR
    ($$NVL(SUM(f.$$FCTCOL_018) ~,~ 0] <> MAX(s.$$FCTCOL_018))
OR
    ($$NVL(SUM(f.$$FCTCOL_019) ~,~ 0] <> MAX(s.$$FCTCOL_019))
OR
    ($$NVL(SUM(f.$$FCTCOL_020) ~,~ 0] <> MAX(s.$$FCTCOL_020))
OR
    ($$NVL(SUM(f.$$FCTCOL_021) ~,~ 0] <> MAX(s.$$FCTCOL_021))
OR
    ($$NVL(SUM(f.$$FCTCOL_022) ~,~ 0] <> MAX(s.$$FCTCOL_022))
OR
    ($$NVL(SUM(f.$$FCTCOL_023) ~,~ 0] <> MAX(s.$$FCTCOL_023))
OR
    ($$NVL(SUM(f.$$FCTCOL_024) ~,~ 0] <> MAX(s.$$FCTCOL_024))

--#BLOCK_END# MakeIND

/*****

```

```

-- Form pairwise deltas for all rows except earliest for each sskey
--
-- Each row created in NFD will consist of two sequential entries from the
-- staing table. So if N enties for an order exist in MFL (after we have filtered
-- out same-date duplicates) then all the queries above will deal with the earliest entry,
whereas
-- all the queries below (including this one) will deal with the N-1 deltaing transactions
--
-- This query assumes that MFL will already have been filtered
-- to have a single record for each order/datekey
--
-- NFD: Not First Delta
/*****
--#BLOCK_BEGIN# MakeNFD

$$SELECT INTO_BEGIN[$$FCTTBL[]_NFD]
SELECT
    s.iss siss, t.iss tiss
    , s.ss_key sss_key, t.ss_key tss_key
    , s.date_key sdate_key, t.date_key tdate_key
    , s.transtype_key stranstype_key, t.transtype_key ttranstype_key
    , s.$$DIMKEYR_01 s$$DIMKEYR_01, t.$$DIMKEYR_01 t$$DIMKEYR_01
    , s.$$DIMKEYR_02 s$$DIMKEYR_02, t.$$DIMKEYR_02 t$$DIMKEYR_02
    , s.$$DIMKEYR_03 s$$DIMKEYR_03, t.$$DIMKEYR_03 t$$DIMKEYR_03
    , s.$$DIMKEYR_04 s$$DIMKEYR_04, t.$$DIMKEYR_04 t$$DIMKEYR_04
    , s.$$DIMKEYR_05 s$$DIMKEYR_05, t.$$DIMKEYR_05 t$$DIMKEYR_05
    , s.$$DIMKEYR_06 s$$DIMKEYR_06, t.$$DIMKEYR_06 t$$DIMKEYR_06
    , s.$$DIMKEYR_07 s$$DIMKEYR_07, t.$$DIMKEYR_07 t$$DIMKEYR_07
    , s.$$DIMKEYR_08 s$$DIMKEYR_08, t.$$DIMKEYR_08 t$$DIMKEYR_08
    , s.$$DIMKEYR_09 s$$DIMKEYR_09, t.$$DIMKEYR_09 t$$DIMKEYR_09
    , s.$$DIMKEYR_10 s$$DIMKEYR_10, t.$$DIMKEYR_10 t$$DIMKEYR_10
    , s.$$DEGKEY_01 s$$DEGKEY_01, t.$$DEGKEY_01 t$$DEGKEY_01
    , s.$$DEGKEY_02 s$$DEGKEY_02, t.$$DEGKEY_02 t$$DEGKEY_02
    , s.$$DEGKEY_03 s$$DEGKEY_03, t.$$DEGKEY_03 t$$DEGKEY_03
    , s.$$FCTCOL_001 s$$FCTCOL_001, t.$$FCTCOL_001 t$$FCTCOL_001
    , s.$$FCTCOL_002 s$$FCTCOL_002, t.$$FCTCOL_002 t$$FCTCOL_002
    , s.$$FCTCOL_003 s$$FCTCOL_003, t.$$FCTCOL_003 t$$FCTCOL_003
    , s.$$FCTCOL_004 s$$FCTCOL_004, t.$$FCTCOL_004 t$$FCTCOL_004
    , s.$$FCTCOL_005 s$$FCTCOL_005, t.$$FCTCOL_005 t$$FCTCOL_005
    , s.$$FCTCOL_006 s$$FCTCOL_006, t.$$FCTCOL_006 t$$FCTCOL_006
    , s.$$FCTCOL_007 s$$FCTCOL_007, t.$$FCTCOL_007 t$$FCTCOL_007
    , s.$$FCTCOL_008 s$$FCTCOL_008, t.$$FCTCOL_008 t$$FCTCOL_008
    , s.$$FCTCOL_009 s$$FCTCOL_009, t.$$FCTCOL_009 t$$FCTCOL_009
    , s.$$FCTCOL_010 s$$FCTCOL_010, t.$$FCTCOL_010 t$$FCTCOL_010
    , s.$$FCTCOL_011 s$$FCTCOL_011, t.$$FCTCOL_011 t$$FCTCOL_011
    , s.$$FCTCOL_012 s$$FCTCOL_012, t.$$FCTCOL_012 t$$FCTCOL_012
    , s.$$FCTCOL_013 s$$FCTCOL_013, t.$$FCTCOL_013 t$$FCTCOL_013
    , s.$$FCTCOL_014 s$$FCTCOL_014, t.$$FCTCOL_014 t$$FCTCOL_014
    , s.$$FCTCOL_015 s$$FCTCOL_015, t.$$FCTCOL_015 t$$FCTCOL_015
    , s.$$FCTCOL_016 s$$FCTCOL_016, t.$$FCTCOL_016 t$$FCTCOL_016
    , s.$$FCTCOL_017 s$$FCTCOL_017, t.$$FCTCOL_017 t$$FCTCOL_017
    , s.$$FCTCOL_018 s$$FCTCOL_018, t.$$FCTCOL_018 t$$FCTCOL_018
    , s.$$FCTCOL_019 s$$FCTCOL_019, t.$$FCTCOL_019 t$$FCTCOL_019
    , s.$$FCTCOL_020 s$$FCTCOL_020, t.$$FCTCOL_020 t$$FCTCOL_020
    , s.$$FCTCOL_021 s$$FCTCOL_021, t.$$FCTCOL_021 t$$FCTCOL_021
    , s.$$FCTCOL_022 s$$FCTCOL_022, t.$$FCTCOL_022 t$$FCTCOL_022
    , s.$$FCTCOL_023 s$$FCTCOL_023, t.$$FCTCOL_023 t$$FCTCOL_023
    , s.$$FCTCOL_024 s$$FCTCOL_024, t.$$FCTCOL_024 t$$FCTCOL_024

$$SELECT INTO_BODY[$$FCTTBL[]_NFD]
FROM
    $$FCTTBL[]_MFL s, $$FCTTBL[]_MFL t
WHERE
    s.iss = t.iss AND s.ss_key = t.ss_key
AND
    s.date_key = (SELECT MAX(date_key) FROM $$FCTTBL[]_MFL u WHERE
    u.iss = s.iss AND u.ss_key = s.ss_key AND u.date_key < t.date_key)

--#BLOCK_END# MakeNFD

```

```

/*****
--
-- Insert BOOKs for deltas with same dim keys
--
-- If the dimensions don't change then we create a
-- new booking order (as long as at least one of the facts
-- have changed)
--
-- IDM: Insert Delta More
--
/*****

--#BLOCK_BEGIN# MakeIDM

$$SELECT INTO_BEGIN[$$FCTTBL[]_IDM]
SELECT
    tiss iss,
    tss_key ss_key,
    tdate_key date_key,
    ttranstype_key transtype_key,
    0 seq
    , t$$DIMKEYR_01 $$DIMKEYR_01
    , t$$DIMKEYR_02 $$DIMKEYR_02
    , t$$DIMKEYR_03 $$DIMKEYR_03
    , t$$DIMKEYR_04 $$DIMKEYR_04
    , t$$DIMKEYR_05 $$DIMKEYR_05
    , t$$DIMKEYR_06 $$DIMKEYR_06
    , t$$DIMKEYR_07 $$DIMKEYR_07
    , t$$DIMKEYR_08 $$DIMKEYR_08
    , t$$DIMKEYR_09 $$DIMKEYR_09
    , t$$DIMKEYR_10 $$DIMKEYR_10
    , t$$DEGKEY_01 $$DEGKEY_01
    , t$$DEGKEY_02 $$DEGKEY_02
    , t$$DEGKEY_03 $$DEGKEY_03
    ,
    , t$$FCTCOL_001-s$$FCTCOL_001 $$FCTCOL_001
    , t$$FCTCOL_002-s$$FCTCOL_002 $$FCTCOL_002
    , t$$FCTCOL_003-s$$FCTCOL_003 $$FCTCOL_003
    , t$$FCTCOL_004-s$$FCTCOL_004 $$FCTCOL_004
    , t$$FCTCOL_005-s$$FCTCOL_005 $$FCTCOL_005
    , t$$FCTCOL_006-s$$FCTCOL_006 $$FCTCOL_006
    , t$$FCTCOL_007-s$$FCTCOL_007 $$FCTCOL_007
    , t$$FCTCOL_008-s$$FCTCOL_008 $$FCTCOL_008
    , t$$FCTCOL_009-s$$FCTCOL_009 $$FCTCOL_009
    , t$$FCTCOL_010-s$$FCTCOL_010 $$FCTCOL_010
    , t$$FCTCOL_011-s$$FCTCOL_011 $$FCTCOL_011
    , t$$FCTCOL_012-s$$FCTCOL_012 $$FCTCOL_012
    , t$$FCTCOL_013-s$$FCTCOL_013 $$FCTCOL_013
    , t$$FCTCOL_014-s$$FCTCOL_014 $$FCTCOL_014
    , t$$FCTCOL_015-s$$FCTCOL_015 $$FCTCOL_015
    , t$$FCTCOL_016-s$$FCTCOL_016 $$FCTCOL_016
    , t$$FCTCOL_017-s$$FCTCOL_017 $$FCTCOL_017
    , t$$FCTCOL_018-s$$FCTCOL_018 $$FCTCOL_018
    , t$$FCTCOL_019-s$$FCTCOL_019 $$FCTCOL_019
    , t$$FCTCOL_020-s$$FCTCOL_020 $$FCTCOL_020
    , t$$FCTCOL_021-s$$FCTCOL_021 $$FCTCOL_021
    , t$$FCTCOL_022-s$$FCTCOL_022 $$FCTCOL_022
    , t$$FCTCOL_023-s$$FCTCOL_023 $$FCTCOL_023
    , t$$FCTCOL_024-s$$FCTCOL_024 $$FCTCOL_024

$$SELECT INTO_BODY[$$FCTTBL[]_IDM]
FROM
    $$FCTTBL[]_NFD d
WHERE
    (
        (s$$DIMKEYR_06 = t$$DIMKEYR_06) AND
        (s$$DIMKEYR_05 = t$$DIMKEYR_05) AND
        (s$$DIMKEYR_07 = t$$DIMKEYR_07) AND
        (s$$DIMKEYR_04 = t$$DIMKEYR_04) AND
        (s$$DIMKEYR_08 = t$$DIMKEYR_08) AND
        (s$$DIMKEYR_03 = t$$DIMKEYR_03) AND
    )

```



```

--
-- Insert BOOKs for deltas with different dim keys
--
-- When a dimension key changes then we can simply insert all the new facts with the
-- new dimension keys
--
-- Note that seq = 1 here because this is the second transaction on this date for
-- this order.
--
-- IRM: Insert Rebook More
--
/*****/

--#BLOCK_BEGIN# MakeIRM

$$SELECT INTO_BEGIN[$$FCTTBL[]_IRM]
SELECT
    t1ss iss,
    tss key ss_key,
    tdate_key date_key,
    ttranstype_key transtype_key,
    l seq
    , t$$DIMKEYR_01 $$DIMKEYR_01
    , t$$DIMKEYR_02 $$DIMKEYR_02
    , t$$DIMKEYR_03 $$DIMKEYR_03
    , t$$DIMKEYR_04 $$DIMKEYR_04
    , t$$DIMKEYR_05 $$DIMKEYR_05
    , t$$DIMKEYR_06 $$DIMKEYR_06
    , t$$DIMKEYR_07 $$DIMKEYR_07
    , t$$DIMKEYR_08 $$DIMKEYR_08
    , t$$DIMKEYR_09 $$DIMKEYR_09
    , t$$DIMKEYR_10 $$DIMKEYR_10
    , t$$DEGKEY_01 $$DEGKEY_01
    , t$$DEGKEY_02 $$DEGKEY_02
    , t$$DEGKEY_03 $$DEGKEY_03
    ,
    , t$$FCTCOL_001 $$FCTCOL_001
    , t$$FCTCOL_002 $$FCTCOL_002
    , t$$FCTCOL_003 $$FCTCOL_003
    , t$$FCTCOL_004 $$FCTCOL_004
    , t$$FCTCOL_005 $$FCTCOL_005
    , t$$FCTCOL_006 $$FCTCOL_006
    , t$$FCTCOL_007 $$FCTCOL_007
    , t$$FCTCOL_008 $$FCTCOL_008
    , t$$FCTCOL_009 $$FCTCOL_009
    , t$$FCTCOL_010 $$FCTCOL_010
    , t$$FCTCOL_011 $$FCTCOL_011
    , t$$FCTCOL_012 $$FCTCOL_012
    , t$$FCTCOL_013 $$FCTCOL_013
    , t$$FCTCOL_014 $$FCTCOL_014
    , t$$FCTCOL_015 $$FCTCOL_015
    , t$$FCTCOL_016 $$FCTCOL_016
    , t$$FCTCOL_017 $$FCTCOL_017
    , t$$FCTCOL_018 $$FCTCOL_018
    , t$$FCTCOL_019 $$FCTCOL_019
    , t$$FCTCOL_020 $$FCTCOL_020
    , t$$FCTCOL_021 $$FCTCOL_021
    , t$$FCTCOL_022 $$FCTCOL_022
    , t$$FCTCOL_023 $$FCTCOL_023
    , t$$FCTCOL_024 $$FCTCOL_024

$$SELECT INTO_BODY[$$FCTTBL[]_IRM]
FROM
    $$FCTTBL[]_NFD d
WHERE
    (
        (s$$DIMKEYR_06 <> t$$DIMKEYR_06) OR
        (s$$DIMKEYR_05 <> t$$DIMKEYR_05) OR
        (s$$DIMKEYR_07 <> t$$DIMKEYR_07) OR
        (s$$DIMKEYR_04 <> t$$DIMKEYR_04) OR
        (s$$DIMKEYR_08 <> t$$DIMKEYR_08) OR
    )

```



```

(s$$DIMKEYR_03 <> t$$DIMKEYR_03) OR
(s$$DIMKEYR_09 <> t$$DIMKEYR_09) OR
(s$$DIMKEYR_02 <> t$$DIMKEYR_02) OR
(s$$DIMKEYR_10 <> t$$DIMKEYR_10) OR
(s$$DIMKEYR_01 <> t$$DIMKEYR_01)
)
AND
(
(t$$FCTCOL_001 <> 0)
OR
(t$$FCTCOL_002 <> 0)
OR
(t$$FCTCOL_003 <> 0)
OR
(t$$FCTCOL_004 <> 0)
OR
(t$$FCTCOL_005 <> 0)
OR
(t$$FCTCOL_006 <> 0)
OR
(t$$FCTCOL_007 <> 0)
OR
(t$$FCTCOL_008 <> 0)
OR
(t$$FCTCOL_009 <> 0)
OR
(t$$FCTCOL_010 <> 0)
OR
(t$$FCTCOL_011 <> 0)
OR
(t$$FCTCOL_012 <> 0)
OR
(t$$FCTCOL_013 <> 0)
OR
(t$$FCTCOL_014 <> 0)
OR
(t$$FCTCOL_015 <> 0)
OR
(t$$FCTCOL_016 <> 0)
OR
(t$$FCTCOL_017 <> 0)
OR
(t$$FCTCOL_018 <> 0)
OR
(t$$FCTCOL_019 <> 0)
OR
(t$$FCTCOL_020 <> 0)
OR
(t$$FCTCOL_021 <> 0)
OR
(t$$FCTCOL_022 <> 0)
OR
(t$$FCTCOL_023 <> 0)
OR
(t$$FCTCOL_024 <> 0)
)

--#BLOCK_END# MakeIRM

/*****
-- Delete the output tables
*****/

--#BLOCK_BEGIN# DropOutput

$$DDL_BEGIN
$$DROP_TABLE_IF_EXISTS[$$FCTTBL[]$$NEXT]
$$DROP_TABLE_IF_EXISTS[$$FCTTBL[]_INC]
$$DDL_END

--#BLOCK_END# DropOutput

/*****
--Create FC table in case force_close was
-- not run
*****/

--#BLOCK_BEGIN# MakeFC

DECLARE $$VAR[fc_exists] $$EPIINT$$EOS

$$DDL_BEGIN_NO_DECLARE

$$VAR_ASSIGN_BEGIN[fc_exists]
SELECT COUNT(1)
$$VAR_ASSIGN INTO[fc_exists]
FROM $$SQLSERVER[sysobjects]$$ORACLE[tabs]
WHERE
$$SQLSERVER[id = object_id('dbo.$$FCTTBL[]_FC') AND sysstat & 0xf = 3]
$$ORACLE[table_name = UPPER('$$FCTTBL[]_FC')]
$$VAR_ASSIGN_END

$$IF[$$VAR[fc_exists] = 0]
$$DDL_EXEC[

```



```

--
-- Note that transaction tables must be built before
-- these statements are run
/*****/

--#BLOCK_BEGIN# MakeNewFact

$$SELECT INTO_BEGIN[$$FCTTBL[]$$NEXT]
SELECT *
$$SELECT INTO_BODY[$$FCTTBL[]$$NEXT]
FROM $$FCTTBL[]$$CURR s
WHERE s.date_key < (SELECT MIN(date_key) FROM $$FCTTBL[]_INC)
UNION ALL
SELECT * FROM $$FCTTBL[]_IMI

--#BLOCK_END# MakeNewFact

/*****/
-- Count processed, inserted rows
/*****/

--#BLOCK_BEGIN# SPResults

DECLARE $$VAR[count_INC] $$EPIINT$$EOS

BEGIN

$$VAR_ASSIGN_BEGIN[count_INC]
SELECT COUNT(1)
$$VAR_ASSIGN_INTO[count_INC]
FROM $$FCTTBL[]_INC
$$VAR_ASSIGN_END

INSERT INTO adaptive_template_profile (token_name, number_rows)
SELECT 'PROCESSED', COUNT(1) FROM $$FCTTBL[]_MFL$$EOS

INSERT INTO adaptive_template_profile (token_name, number_rows)
SELECT 'INSERTED', $$VAR[count_INC] - COUNT(1) FROM $$FCTTBL[]_TIN$$EOS

END$$EOS

--#BLOCK_END# SPResults

/*****/
-- Set join order for SQL Server
/*****/

--#BLOCK_BEGIN# ForcePlanOff

$$SQLSERVER[SET FORCEPLAN OFF]

--#BLOCK_END# ForcePlanOff

/*****/
-- Drop temp tables and TXN and TIN table
/*****/

--#BLOCK_BEGIN# DropTempsAfter

$$DDL BEGIN
$$DROP_TABLE_IF_EXISTS[$$FCTTBL[]_TIN]
$$DROP_TABLE_IF_EXISTS[$$FCTTBL[]_TMI]
$$DROP_TABLE_IF_EXISTS[$$FCTTBL[]_FC]
$$DROP_TABLE_IF_EXISTS[$$FCTTBL[]_TXN]
$$DROP_TABLE_IF_EXISTS[Concat MFL]
$$DROP_TABLE_IF_EXISTS[$$FCTTBL[]_1ST]
$$DROP_TABLE_IF_EXISTS[$$FCTTBL[]_IL]
$$DROP_TABLE_IF_EXISTS[$$FCTTBL[]_IR]
$$DROP_TABLE_IF_EXISTS[$$FCTTBL[]_IRD]
$$DROP_TABLE_IF_EXISTS[$$FCTTBL[]_IND]
$$DROP_TABLE_IF_EXISTS[$$FCTTBL[]_NFD]

```

```

$$DROP_TABLE_IF_EXISTS[$$FCTTBL[]_IRM]
$$DROP_TABLE_IF_EXISTS[$$FCTTBL[]_IDM]
$$DROP_TABLE_IF_EXISTS[$$FCTTBL[]_ILM]
$$DROP_TABLE_IF_EXISTS[$$FCTTBL[]_IMI]
$$DDL_END

--#BLOCK_END# DropTempsAfter

--#TEMPLATE_END# load_state
--#TEMPLATE_BEGIN# load_trans

/*****/
--
-- Copyright * 1997, Epiphany Marketing Software, Inc. All Rights Reserved.
--
-- load_trans
--
-- Move transaction-like staging data into Fact table - create a temp
-- table with TXN extension that has all old rows along with new rows.
-- Also produce a TIN (TXN INC) table that has only the new rows
--
-- Note that the new table will also include all existing rows from
-- the Fact table.
--
/*****/

/*****/
-- Delete output tables
--
-- Output table is called TXN and includes old and new rows
--
-- Also, leave around _TIN as incremental table from this
-- procedure
--
-- We also create a table called _TMI which contains all the
-- _TIN records plus the records of overlapping period from the
-- old existing fact table.
/*****/

--#BLOCK_BEGIN# RemoveOutput

$$DDL_BEGIN
$$DROP_TABLE_IF_EXISTS[$$FCTTBL[]_TXN]
$$DROP_TABLE_IF_EXISTS[$$FCTTBL[]_TMI]
$$DROP_TABLE_IF_EXISTS[$$FCTTBL[]_TIN]
$$DDL_END

--#BLOCK_END# RemoveOutput

/*****/
-- Set join order for SQL Server
/*****/

--#BLOCK_BEGIN# ForcePlanOn

$$$SQLSERVER[SET FORCEPLAN ON]

--#BLOCK_END# ForcePlanOn

/*****/
-- Remove stuff already in fact table
--
-- Note that currently this filter implies that once a transactional
-- fact entry is made it cannot be changed - and no further fact
-- entries on that date or any previous date can be made either
/*****/

--#BLOCK_BEGIN# CreateTIN

$$SELECT_INTO_BEGIN[$$FCTTBL[]_TIN]
SELECT

```

```

s.iss,
s.ss_key,
s.date_key,
s.transtype_key,
s.ikey seq
,
s.$$DIMKEYR_01
,
s.$$DIMKEYR_02
,
s.$$DIMKEYR_03
,
s.$$DIMKEYR_04
,
s.$$DIMKEYR_05
,
s.$$DIMKEYR_06
,
s.$$DIMKEYR_07
,
s.$$DIMKEYR_08
,
s.$$DIMKEYR_09
,
s.$$DIMKEYR_10
,
s.$$DEGKEY_01
,
s.$$DEGKEY_02
,
s.$$DEGKEY_03
,
,
s.$$FCTCOL_001
,
s.$$FCTCOL_002
,
s.$$FCTCOL_003
,
s.$$FCTCOL_004
,
s.$$FCTCOL_005
,
s.$$FCTCOL_006
,
s.$$FCTCOL_007
,
s.$$FCTCOL_008
,
s.$$FCTCOL_009
,
s.$$FCTCOL_010
,
s.$$FCTCOL_011
,
s.$$FCTCOL_012
,
s.$$FCTCOL_013
,
s.$$FCTCOL_014
,
s.$$FCTCOL_015
,
s.$$FCTCOL_016
,
s.$$FCTCOL_017
,
s.$$FCTCOL_018
,
s.$$FCTCOL_019
,
s.$$FCTCOL_020
,
s.$$FCTCOL_021
,
s.$$FCTCOL_022
,
s.$$FCTCOL_023
,
s.$$FCTCOL_024

$$SELECT_INTO_BODY[$$FCTTBL[]_TIN]
FROM
    $$FSTGTBL[]_MAP s, bus_process b
WHERE
    NOT EXISTS (SELECT * FROM $$FCTTBL[]$$CURR f WHERE
        s.iss = f.iss AND
        s.ss_key = f.ss_key AND
        f.date_key >= s.date_key)
AND
    (
    OR (s.$$FCTCOL_001 <> 0)
    OR (s.$$FCTCOL_002 <> 0)
    OR (s.$$FCTCOL_003 <> 0)
    OR (s.$$FCTCOL_004 <> 0)
    OR (s.$$FCTCOL_005 <> 0)
    OR (s.$$FCTCOL_006 <> 0)
    OR (s.$$FCTCOL_007 <> 0)
    OR (s.$$FCTCOL_008 <> 0)
    OR (s.$$FCTCOL_009 <> 0)
    OR (s.$$FCTCOL_010 <> 0)
    OR (s.$$FCTCOL_011 <> 0)
    OR (s.$$FCTCOL_012 <> 0)
    OR (s.$$FCTCOL_013 <> 0)
    OR (s.$$FCTCOL_014 <> 0)
    OR (s.$$FCTCOL_015 <> 0)
    OR (s.$$FCTCOL_016 <> 0)
    OR (s.$$FCTCOL_017 <> 0)
    OR (s.$$FCTCOL_018 <> 0)
    )

```

```

OR      (s.$$FCTCOL_019 <> 0)
OR      (s.$$FCTCOL_020 <> 0)
OR      (s.$$FCTCOL_021 <> 0)
OR      (s.$$FCTCOL_022 <> 0)
OR      (s.$$FCTCOL_023 <> 0)
OR      (s.$$FCTCOL_024 <> 0)
)
AND
    s.process_key = b.process_key AND b.process_name = 'LoadTrans'

--#BLOCK_END# CreateTIN

/*****/
-- Set join order for SQL Server
/*****/

--#BLOCK_BEGIN# ForcePlanOff
$$$SQLSERVER[SET FORCEPLAN OFF]

--#BLOCK_END# ForcePlanOff

/*****/
-- CR158: We want to load _TMI table and still keep the non-descending
-- order so that the clustered index on a fact table can be created
-- without sorting. This way can speed up significantly in creating a
-- clustered index on a very large already sorted fact table.
/*****/

--#BLOCK_BEGIN# CreateTMI
$$SELECT INTO BEGIN[$$FCTTBL[]_TMI]
SELECT
    *
$$SELECT INTO BODY[$$FCTTBL[]_TMI]
FROM
    $$FCTTBL[]$$CURR
WHERE
    date_key >= (SELECT MAX(date_key) FROM $$FCTTBL[]_TIN)
UNION ALL
SELECT
    *
FROM
    $$FCTTBL[]_TIN
$$$SQLSERVER[ORDER BY
    date_key
    ,   $$DIMKEYR_01
    ,   $$DIMKEYR_02
    ,   $$DIMKEYR_03
    ,   $$DIMKEYR_04
    ,   $$DIMKEYR_05
    ,   $$DIMKEYR_06
    ,   $$DIMKEYR_07
    ,   $$DIMKEYR_08
    ,   $$DIMKEYR_09
    ,   $$DIMKEYR_10
]

--#BLOCK_END# CreateTMI

/*****/
-- Insert everything into the new fact table
/*****/

--#BLOCK_BEGIN# CreateTXN
$$SELECT INTO BEGIN[$$FCTTBL[]_TXN]
SELECT
    *
$$SELECT INTO BODY[$$FCTTBL[]_TXN]
FROM

```

```

        $$FCTTBL[$$CURR s
WHERE s.date_key < (SELECT MAX(date_key) FROM $$FCTTBL[]_TIN)
UNION ALL
SELECT
    *
FROM
    $$FCTTBL[]_TMI f

--#BLOCK_END# CreateTXN

/*****/
-- Count inserted data and put results into communication table
/*****/

--#BLOCK_BEGIN# SPResults

BEGIN

INSERT INTO adaptive_template_profile (token_name, number_rows)
SELECT 'PROCESSED', COUNT(1) FROM $$FSTGTBL[]_MAP$$EOS

INSERT INTO adaptive_template_profile (token_name, number_rows)
SELECT 'INSERTED', COUNT(1) FROM $$FCTTBL[]_TIN$$EOS

END$$EOS

--#BLOCK_END# SPResults

--#TEMPLATE_END# load_trans

--#TEMPLATE_BEGIN# index_fact

/*****/
--
-- Copyright * 1997, Epiphany Marketing Software, Inc. All Rights Reserved.
--
-- Post processing after an extraction run
--
-- Reindex fact tables
-- CR158: added WITH SORTED_DATA in creating cluster index on fact table
--
-- Remove any temp tables generated during the extraction
--
/*****/

/*****/
-- Primary key index the fact table
/*****/

--#BLOCK_BEGIN# PKIndexFact

$$DDL_BEGIN
$$DDL_EXEC[

CREATE UNIQUE INDEX XPK$$FCTTBL[]$$NEXT ON $$FCTTBL[]$$NEXT
(
    iss , ss_key , date_key , transtype_key , seq
)
]
$$DDL_END

--#BLOCK_END# PKIndexFact

/*****/
-- Inversion index the fact table
/*****/

--#BLOCK_BEGIN# IEIndexFact

$$DDL_BEGIN
$$DDL_EXEC[

```

Parameter	Value	Unit
1. α	0.001	1/s
2. β	0.001	1/s
3. γ	0.001	1/s
4. δ	0.001	1/s
5. ϵ	0.001	1/s
6. ζ	0.001	1/s
7. η	0.001	1/s
8. θ	0.001	1/s
9. ι	0.001	1/s
10. κ	0.001	1/s
11. λ	0.001	1/s
12. μ	0.001	1/s
13. ν	0.001	1/s
14. ξ	0.001	1/s
15. \omicron	0.001	1/s
16. π	0.001	1/s
17. ρ	0.001	1/s
18. σ	0.001	1/s
19. τ	0.001	1/s
20. υ	0.001	1/s
21. ϕ	0.001	1/s
22. χ	0.001	1/s
23. ψ	0.001	1/s
24. ω	0.001	1/s
25. φ	0.001	1/s
26. η	0.001	1/s
27. θ	0.001	1/s
28. ι	0.001	1/s
29. κ	0.001	1/s
30. λ	0.001	1/s
31. μ	0.001	1/s
32. ν	0.001	1/s
33. ξ	0.001	1/s
34. \omicron	0.001	1/s
35. π	0.001	1/s
36. ρ	0.001	1/s
37. σ	0.001	1/s
38. τ	0.001	1/s
39. υ	0.001	1/s
40. ϕ	0.001	1/s
41. χ	0.001	1/s
42. ψ	0.001	1/s
43. ω	0.001	1/s
44. φ	0.001	1/s
45. η	0.001	1/s
46. θ	0.001	1/s
47. ι	0.001	1/s
48. κ	0.001	1/s
49. λ	0.001	1/s
50. μ	0.001	1/s
51. ν	0.001	1/s
52. ξ	0.001	1/s
53. \omicron	0.001	1/s
54. π	0.001	1/s
55. ρ	0.001	1/s
56. σ	0.001	1/s
57. τ	0.001	1/s
58. υ	0.001	1/s
59. ϕ	0.001	1/s
60. χ	0.001	1/s
61. ψ	0.001	1/s
62. ω	0.001	1/s
63. φ	0.001	1/s
64. η	0.001	1/s
65. θ	0.001	1/s
66. ι	0.001	1/s
67. κ	0.001	1/s
68. λ	0.001	1/s
69. μ	0.001	1/s
70. ν	0.001	1/s
71. ξ	0.001	1/s
72. \omicron	0.001	1/s
73. π	0.001	1/s
74. ρ	0.001	1/s
75. σ	0.001	1/s
76. τ	0.001	1/s
77. υ	0.001	1/s
78. ϕ	0.001	1/s
79. χ	0.001	1/s
80. ψ	0.001	1/s
81. ω	0.001	1/s
82. φ	0.001	1/s
83. η	0.001	1/s
84. θ	0.001	1/s
85. ι	0.001	1/s
86. κ	0.001	1/s
87. λ	0.001	1/s
88. μ	0.001	1/s
89. ν	0.001	1/s
90. ξ	0.001	1/s
91. \omicron	0.001	1/s
92. π	0.001	1/s
93. ρ	0.001	1/s
94. σ	0.001	1/s
95. τ	0.001	1/s
96. υ	0.001	1/s
97. ϕ	0.001	1/s
98. χ	0.001	1/s
99. ψ	0.0	

Table 1		Table 2		Table 3		Table 4		Table 5		Table 6		Table 7		Table 8		Table 9		Table 10		Table 11		Table 12		Table 13		Table 14		Table 15		Table 16		Table 17		Table 18		Table 19		Table 20		Table 21		Table 22		Table 23		Table 24		Table 25		Table 26		Table 27		Table 28		Table 29		Table 30		Table 31		Table 32		Table 33		Table 34		Table 35		Table 36		Table 37		Table 38		Table 39		Table 40		Table 41		Table 42		Table 43		Table 44		Table 45		Table 46		Table 47		Table 48		Table 49		Table 50		Table 51		Table 52		Table 53		Table 54		Table 55		Table 56		Table 57		Table 58		Table 59		Table 60		Table 61		Table 62		Table 63		Table 64		Table 65		Table 66		Table 67		Table 68		Table 69		Table 70		Table 71		Table 72		Table 73		Table 74		Table 75		Table 76		Table 77		Table 78		Table 79		Table 80		Table 81		Table 82		Table 83		Table 84		Table 85		Table 86		Table 87		Table 88		Table 89		Table 90		Table 91		Table 92		Table 93		Table 94		Table 95		Table 96		Table 97		Table 98		Table 99		Table 100		Table 101		Table 102		Table 103		Table 104		Table 105		Table 106		Table 107		Table 108		Table 109		Table 110		Table 111		Table 112		Table 113		Table 114		Table 115		Table 116		Table 117		Table 118		Table 119		Table 120		Table 121		Table 122		Table 123		Table 124		Table 125		Table 126		Table 127		Table 128		Table 129		Table 130		Table 131		Table 132		Table 133		Table 134		Table 135		Table 136		Table 137		Table 138		Table 139		Table 140		Table 141		Table 142		Table 143		Table 144		Table 145		Table 146		Table 147		Table 148		Table 149		Table 150		Table 151		Table 152		Table 153		Table 154		Table 155		Table 156		Table 157		Table 158		Table 159		Table 160		Table 161		Table 162		Table 163		Table 164		Table 165		Table 166		Table 167		Table 168		Table 169		Table 170		Table 171		Table 172		Table 173		Table 174		Table 175		Table 176		Table 177		Table 178		Table 179		Table 180		Table 181		Table 182		Table 183		Table 184		Table 185		Table 186		Table 187		Table 188		Table 189		Table 190		Table 191		Table 192		Table 193		Table 194		Table 195		Table 196		Table 197		Table 198		Table 199		Table 200		Table 201		Table 202		Table 203		Table 204		Table 205		Table 206		Table 207		Table 208		Table 209		Table 210		Table 211		Table 212		Table 213		Table 214		Table 215		Table 216		Table 217		Table 218		Table 219		Table 220		Table 221		Table 222		Table 223		Table 224		Table 225		Table 226		Table 227		Table 228		Table 229		Table 230		Table 231		Table 232		Table 233		Table 234		Table 235		Table 236		Table 237		Table 238		Table 239		Table 240		Table 241		Table 242		Table 243		Table 244		Table 245		Table 246		Table 247		Table 248		Table 249		Table 250		Table 251		Table 252		Table 253		Table 254		Table 255		Table 256		Table 257		Table 258		Table 259		Table 260		Table 261		Table 262		Table 263		Table 264		Table 265		Table 266		Table 267		Table 268		Table 269		Table 270		Table 271		Table 272		Table 273		Table 274		Table 275		Table 276		Table 277		Table 278		Table 279		Table 280		Table 281		Table 282		Table 283		Table 284		Table 285		Table 286		Table 287		Table 288		Table 289		Table 290		Table 291		Table 292		Table 293		Table 294		Table 295		Table 296		Table 297		Table 298		Table 299		Table	
---------	--	---------	--	---------	--	---------	--	---------	--	---------	--	---------	--	---------	--	---------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-------	--

```

-- Map dimension keys from Staging table and report
-- on unjoined rows
--
/*****/

/*****/
-- Remove output table
/*****/

--#BLOCK_BEGIN# DropTemp

$$DDL_BEGIN
$$DROP TABLE_IF_EXISTS[$$FSTGTBL[]_MAP]
$$DDL_END

--#BLOCK_END# DropTemp

/*****/
-- Set join order for SQL Server
/*****/

--#BLOCK_BEGIN# ForcePlanOn

$$SQLSERVER[SET FORCEPLAN ON]

--#BLOCK_END# ForcePlanOn

/*****/
-- Map dimension keys via Inner joins
/*****/

--#BLOCK_BEGIN# MapAll

$$SELECT_INTO_BEGIN[$$FSTGTBL[]_MAP]
SELECT
    s.iss,
    s.ss_key,
    s.date_key,
    s.transtype_key,
    s.lkey,
    s.process_key
,
    $$PIPE_STATE
,
    m_04.$$DIMKEY_04 $$DIMKEYR_04
,
    m_03.$$DIMKEY_03 $$DIMKEYR_03
,
    m_06.$$DIMKEY_06 $$DIMKEYR_06
,
    m_02.$$DIMKEY_02 $$DIMKEYR_02
,
    m_08.$$DIMKEY_08 $$DIMKEYR_08
,
    m_05.$$DIMKEY_05 $$DIMKEYR_05
,
    m_09.$$DIMKEY_09 $$DIMKEYR_09
,
    m_01.$$DIMKEY_01 $$DIMKEYR_01
,
    m_07.$$DIMKEY_07 $$DIMKEYR_07
,
    m_10.$$DIMKEY_10 $$DIMKEYR_10
,
    $$DEGKEY_03
,
    $$DEGKEY_02
,
    $$DEGKEY_01
,
    s.$$FCTCOL_001
,
    s.$$FCTCOL_002
,
    s.$$FCTCOL_003
,
    s.$$FCTCOL_004
,
    s.$$FCTCOL_005
,
    s.$$FCTCOL_006
,
    s.$$FCTCOL_007
,
    s.$$FCTCOL_008
,
    s.$$FCTCOL_009
,
    s.$$FCTCOL_010
,
    s.$$FCTCOL_011
,
    s.$$FCTCOL_012
,
    s.$$FCTCOL_013

```

```

,      s.$$FCTCOL_014
,      s.$$FCTCOL_015
,      s.$$FCTCOL_016
,      s.$$FCTCOL_017
,      s.$$FCTCOL_018
,      s.$$FCTCOL_019
,      s.$$FCTCOL_020
,      s.$$FCTCOL_021
,      s.$$FCTCOL_022
,      s.$$FCTCOL_023
,      s.$$FCTCOL_024

$$$SELECT INTO BODY[$$FSTGTBL[]_MAP]
FROM
    $$FSTGTBL[] s
,      $$MAPTBL_04$$NEXT m_04 $$$SQLSERVER[(index = 1)]
,      $$MAPTBL_03$$NEXT m_03 $$$SQLSERVER[(index = 1)]
,      $$MAPTBL_06$$NEXT m_06 $$$SQLSERVER[(index = 1)]
,      $$MAPTBL_02$$NEXT m_02 $$$SQLSERVER[(index = 1)]
,      $$MAPTBL_08$$NEXT m_08 $$$SQLSERVER[(index = 1)]
,      $$MAPTBL_05$$NEXT m_05 $$$SQLSERVER[(index = 1)]
,      $$MAPTBL_09$$NEXT m_09 $$$SQLSERVER[(index = 1)]
,      $$MAPTBL_01$$NEXT m_01 $$$SQLSERVER[(index = 1)]
,      $$MAPTBL_07$$NEXT m_07 $$$SQLSERVER[(index = 1)]
,      $$MAPTBL_10$$NEXT m_10 $$$SQLSERVER[(index = 1)]

WHERE 1=1
AND    m_04.iss = s.iss AND m_04.$$DSTGKEY_04 = s.$$DSTGKEYR_04
AND    m_03.iss = s.iss AND m_03.$$DSTGKEY_03 = s.$$DSTGKEYR_03
AND    m_06.iss = s.iss AND m_06.$$DSTGKEY_06 = s.$$DSTGKEYR_06
AND    m_02.iss = s.iss AND m_02.$$DSTGKEY_02 = s.$$DSTGKEYR_02
AND    m_08.iss = s.iss AND m_08.$$DSTGKEY_08 = s.$$DSTGKEYR_08
AND    m_05.iss = s.iss AND m_05.$$DSTGKEY_05 = s.$$DSTGKEYR_05
AND    m_09.iss = s.iss AND m_09.$$DSTGKEY_09 = s.$$DSTGKEYR_09
AND    m_01.iss = s.iss AND m_01.$$DSTGKEY_01 = s.$$DSTGKEYR_01
AND    m_07.iss = s.iss AND m_07.$$DSTGKEY_07 = s.$$DSTGKEYR_07
AND    m_10.iss = s.iss AND m_10.$$DSTGKEY_10 = s.$$DSTGKEYR_10

--#BLOCK_END# MapAll

/*****/
-- Set join order for SQL Server
/*****/

--#BLOCK_BEGIN# ForcePlanOff

$$$SQLSERVER[SET FORCEPLAN OFF]

--#BLOCK_END# ForcePlanOff

/*****/
-- Look for unjoined data, Report on processed rows
/*****/

--#BLOCK_BEGIN# SPResults

$$DECLARE_BEGIN
$$DECLARE_BODY[$$VAR[unjoined] $$EPIINT]
$$DECLARE_BODY[$$VAR[processed] $$EPIINT]

BEGIN

$$VAR ASSIGN_BEGIN[processed]
SELECT COUNT(1)
$$VAR ASSIGN INTO[processed]
FROM $$FSTGTBL[]
$$VAR_ASSIGN_END

$$VAR_ASSIGN_BEGIN[unjoined]
SELECT $$VAR[processed] - COUNT(1)
$$VAR_ASSIGN INTO[unjoined]

```

```

FROM $$FSTGTBL[]_MAP
$$VAR_ASSIGN_END

INSERT INTO adaptive_template_profile (token_name, number_rows)
SELECT 'UNJOINED', $$VAR[unjoined] $$NO_FROM_LIST$$EOS

INSERT INTO adaptive_template_profile (token_name, number_rows)
SELECT 'PROCESSED', $$VAR[processed] $$NO_FROM_LIST$$EOS

INSERT INTO adaptive_template_profile (token_name, number_rows)
SELECT 'INSERTED', $$VAR[processed] - $$VAR[unjoined] $$NO_FROM_LIST$$EOS

END$$EOS

--#BLOCK_END# SPResults

/*****/
-- Index this temp table
/*****/

--#BLOCK_BEGIN# IndexMap

$$DDL_BEGIN
$$DDL_EXEC[
CREATE INDEX X$$FSTGTBL[]_MAP ON $$FSTGTBL[]_MAP
(
    iss, ss_key, date_key, ikey
)
]
$$DDL_END

--#BLOCK_END# IndexMap

--#TEMPLATE_END# map_keys
--#TEMPLATE_BEGIN# upd_unj

/*****/
--
-- Copyright * 1997, Epiphany Marketing Software, Inc. All Rights Reserved
--
-- upd_unj
--
-- Epiphany Marketing Software
--
-- Update all dimension keys to 'UNKNOWN' in staging table
-- where referential integrity fails
--
/*****/

/*****/
-- Count the number of rows to update in the staging table - that is, those
-- that have at least one Foreign key where referential integrity fails
/*****/

--#BLOCK_BEGIN# CountUnj

BEGIN

INSERT INTO adaptive_template_profile (token_name, number_rows)
SELECT 'PROCESSED', COUNT(1) FROM $$FSTGTBL[]$$EOS

INSERT INTO adaptive_template_profile (token_name, number_rows)
SELECT 'MODIFIED', COUNT(1)
FROM
    $$FSTGTBL[] s
WHERE 1=0
OR NOT EXISTS (SELECT 1 FROM $$MAPTBL_04$$NEXT m_04 WHERE m_04.iss = s.iss AND
m_04.$$DSTGKEY_04 = $$DSTGKEYR_04)
OR NOT EXISTS (SELECT 1 FROM $$MAPTBL_03$$NEXT m_03 WHERE m_03.iss = s.iss AND
m_03.$$DSTGKEY_03 = $$DSTGKEYR_03)
OR NOT EXISTS (SELECT 1 FROM $$MAPTBL_06$$NEXT m_06 WHERE m_06.iss = s.iss AND

```

```

m_06.$$DSTGKEY_06 = $$DSTGKEYR_06)
OR NOT EXISTS (SELECT 1 FROM $$MAPTBL_02$$NEXT m_02 WHERE m_02.iss = s.iss AND
m_02.$$DSTGKEY_02 = $$DSTGKEYR_02)
OR NOT EXISTS (SELECT 1 FROM $$MAPTBL_08$$NEXT m_08 WHERE m_08.iss = s.iss AND
m_08.$$DSTGKEY_08 = $$DSTGKEYR_08)
OR NOT EXISTS (SELECT 1 FROM $$MAPTBL_05$$NEXT m_05 WHERE m_05.iss = s.iss AND
m_05.$$DSTGKEY_05 = $$DSTGKEYR_05)
OR NOT EXISTS (SELECT 1 FROM $$MAPTBL_09$$NEXT m_09 WHERE m_09.iss = s.iss AND
m_09.$$DSTGKEY_09 = $$DSTGKEYR_09)
OR NOT EXISTS (SELECT 1 FROM $$MAPTBL_01$$NEXT m_01 WHERE m_01.iss = s.iss AND
m_01.$$DSTGKEY_01 = $$DSTGKEYR_01)
OR NOT EXISTS (SELECT 1 FROM $$MAPTBL_07$$NEXT m_07 WHERE m_07.iss = s.iss AND
m_07.$$DSTGKEY_07 = $$DSTGKEYR_07)
OR NOT EXISTS (SELECT 1 FROM $$MAPTBL_10$$NEXT m_10 WHERE m_10.iss = s.iss AND
m_10.$$DSTGKEY_10 = $$DSTGKEYR_10)
$$EOS
END$$EOS

--#BLOCK_END# CountUnj

/*****
-- Update foreign keys where referential integrity fails
*****/

--#BLOCK_BEGIN# UpdateUnj$$DSTGKEYR_04

UPDATE $$FSTGTBL[] SET $$DSTGKEYR_04 = 'UNKNOWN'
WHERE NOT EXISTS (SELECT 1 FROM $$MAPTBL_04$$NEXT m
WHERE m.iss = $$FSTGTBL[].iss AND m.$$DSTGKEY_04 = $$FSTGTBL[].$$DSTGKEYR_04)

--#BLOCK_END# UpdateUnj$$DSTGKEYR_04

--#BLOCK_BEGIN# UpdateUnj$$DSTGKEYR_03

UPDATE $$FSTGTBL[] SET $$DSTGKEYR_03 = 'UNKNOWN'
WHERE NOT EXISTS (SELECT 1 FROM $$MAPTBL_03$$NEXT m
WHERE m.iss = $$FSTGTBL[].iss AND m.$$DSTGKEY_03 = $$FSTGTBL[].$$DSTGKEYR_03)

--#BLOCK_END# UpdateUnj$$DSTGKEYR_03

--#BLOCK_BEGIN# UpdateUnj$$DSTGKEYR_06

UPDATE $$FSTGTBL[] SET $$DSTGKEYR_06 = 'UNKNOWN'
WHERE NOT EXISTS (SELECT 1 FROM $$MAPTBL_06$$NEXT m
WHERE m.iss = $$FSTGTBL[].iss AND m.$$DSTGKEY_06 = $$FSTGTBL[].$$DSTGKEYR_06)

--#BLOCK_END# UpdateUnj$$DSTGKEYR_06

--#BLOCK_BEGIN# UpdateUnj$$DSTGKEYR_02

UPDATE $$FSTGTBL[] SET $$DSTGKEYR_02 = 'UNKNOWN'
WHERE NOT EXISTS (SELECT 1 FROM $$MAPTBL_02$$NEXT m
WHERE m.iss = $$FSTGTBL[].iss AND m.$$DSTGKEY_02 = $$FSTGTBL[].$$DSTGKEYR_02)

--#BLOCK_END# UpdateUnj$$DSTGKEYR_02

--#BLOCK_BEGIN# UpdateUnj$$DSTGKEYR_08

UPDATE $$FSTGTBL[] SET $$DSTGKEYR_08 = 'UNKNOWN'
WHERE NOT EXISTS (SELECT 1 FROM $$MAPTBL_08$$NEXT m
WHERE m.iss = $$FSTGTBL[].iss AND m.$$DSTGKEY_08 = $$FSTGTBL[].$$DSTGKEYR_08)

--#BLOCK_END# UpdateUnj$$DSTGKEYR_08

--#BLOCK_BEGIN# UpdateUnj$$DSTGKEYR_05

UPDATE $$FSTGTBL[] SET $$DSTGKEYR_05 = 'UNKNOWN'
WHERE NOT EXISTS (SELECT 1 FROM $$MAPTBL_05$$NEXT m
WHERE m.iss = $$FSTGTBL[].iss AND m.$$DSTGKEY_05 = $$FSTGTBL[].$$DSTGKEYR_05)

--#BLOCK_END# UpdateUnj$$DSTGKEYR_05

```

```

--#BLOCK_BEGIN# UpdateUnj$$DSTGKEYR_09

UPDATE $$FSTGTBL[] SET $$DSTGKEYR_09 = 'UNKNOWN'
WHERE NOT EXISTS (SELECT 1 FROM $$MAPTBL_09$$NEXT m
WHERE m.iss = $$FSTGTBL[].iss AND m.$$DSTGKEY_09 = $$FSTGTBL[].$$DSTGKEYR_09)

--#BLOCK_END# UpdateUnj$$DSTGKEYR_09

--#BLOCK_BEGIN# UpdateUnj$$DSTGKEYR_01

UPDATE $$FSTGTBL[] SET $$DSTGKEYR_01 = 'UNKNOWN'
WHERE NOT EXISTS (SELECT 1 FROM $$MAPTBL_01$$NEXT m
WHERE m.iss = $$FSTGTBL[].iss AND m.$$DSTGKEY_01 = $$FSTGTBL[].$$DSTGKEYR_01)

--#BLOCK_END# UpdateUnj$$DSTGKEYR_01

--#BLOCK_BEGIN# UpdateUnj$$DSTGKEYR_07

UPDATE $$FSTGTBL[] SET $$DSTGKEYR_07 = 'UNKNOWN'
WHERE NOT EXISTS (SELECT 1 FROM $$MAPTBL_07$$NEXT m
WHERE m.iss = $$FSTGTBL[].iss AND m.$$DSTGKEY_07 = $$FSTGTBL[].$$DSTGKEYR_07)

--#BLOCK_END# UpdateUnj$$DSTGKEYR_07

--#BLOCK_BEGIN# UpdateUnj$$DSTGKEYR_10

UPDATE $$FSTGTBL[] SET $$DSTGKEYR_10 = 'UNKNOWN'
WHERE NOT EXISTS (SELECT 1 FROM $$MAPTBL_10$$NEXT m
WHERE m.iss = $$FSTGTBL[].iss AND m.$$DSTGKEY_10 = $$FSTGTBL[].$$DSTGKEYR_10)

--#BLOCK_END# UpdateUnj$$DSTGKEYR_10

--#TEMPLATE_END# upd_unj

```

The following are the post-parsed SQL source for the adaptive templates as filled in with corresponding schema definitions.

```

--#TEMPLATE_BEGIN# force_close

/*****
--
-- Copyright * 1997, Epiphany Marketing Software, Inc. All Rights Reserved.
--
-- force_close
--
-- Close out deleted orders - those that no longer appear in the
-- staging table
--
-- SEE SAFETY VALVE BELOW
--
*****/

/*****
-- Delete temporary tables

```

```

/*****/
--#BLOCK_BEGIN# DropTemps

IF EXISTS (SELECT 1 FROM sysobjects WHERE id = object_id('dbo.Order_0_FC') AND sysstat & 0xf =
3) DROP TABLE Order_0_FC

--#BLOCK_END# DropTemps

/*****/
-- Insert negative BOOKs for deleted orders
--
-- FC: ForceClose
/*****/

--#BLOCK_BEGIN# MakeFC

SELECT
    f.iss,
    f.ss_key,
    MAX(f.date_key) date_key,
    MIN(f.transtype_key) transtype_key,
    MAX(f.seq) + 1 seq
    f.customerbillto_key
    ,
    f.product_key
    ,
    f.application_key
    ,
    f.program_key
    ,
    f.customershipto_key
    ,
    f.territory_key
    ,
    f.warehouse_key
    ,
    -SUM(f.net_price) net_price
    ,
    -SUM(f.number_units) number_units

INTO Order_0_FC
FROM
    Order_0_A f
WHERE
    NOT EXISTS
    (SELECT 1 FROM OrderStage_MAP s WHERE s.iss = f.iss AND s.ss_key = f.ss_key)
GROUP BY
    f.iss,
    f.ss_key
    ,
    f.customerbillto_key
    ,
    f.product_key
    ,
    f.application_key
    ,
    f.program_key
    ,
    f.customershipto_key
    ,
    f.territory_key
    ,
    f.warehouse_key

HAVING
    (
    OR
    (SUM(f.net_price) <> 0)
    (SUM(f.number_units) <> 0)
    )
AND
    MIN(f.transtype_key) <= 99
AND
    MIN(f.transtype_key) >= 1

--#BLOCK_END# MakeFC

/*****/
-- SAFETY VALVE - THIS PROC ONLY DOES ANYTHING
-- IF THE STAGING TABLE HAS AT LEAST ONE ROW
/*****/

```

```

--#BLOCK_BEGIN# SafetyValue

DECLARE @count_MAP INT

BEGIN

SELECT @count_MAP = (
SELECT COUNT(1)

FROM OrderStage_MAP
)

IF (@count_MAP = 0)
DELETE FROM Order_0_FC

END

--#BLOCK_END# SafetyValue

/*****/
-- Count processed, inserted rows
/*****/

--#BLOCK_BEGIN# SPResults

BEGIN

INSERT INTO adaptive_template_profile (token_name, number_rows)
SELECT 'PROCESSED', COUNT(1) FROM Order_0_A

INSERT INTO adaptive_template_profile (token_name, number_rows)
SELECT 'INSERTED', COUNT(1) FROM Order_0_FC

END

--#BLOCK_END# SPResults

--#TEMPLATE_END# force_close

--#TEMPLATE_BEGIN# load_state

/*****/
--
-- Copyright * 1997, Epiphany Marketing Software, Inc. All Rights Reserved.
--
-- load_state
--
-- Load order bookings into fact table by creating transactional
-- data from state data
--
-- load_trans must be run before this procedure to create TIN table
--
/*****/

/*****/
-- Delete temporary tables
/*****/

--#BLOCK_BEGIN# DropTemps

IF EXISTS (SELECT 1 FROM sysobjects WHERE id = object_id('dbo.Order_0_MFL') AND sysstat & 0xf
= 3) DROP TABLE Order_0_MFL
IF EXISTS (SELECT 1 FROM sysobjects WHERE id = object_id('dbo.Order_0_1ST') AND sysstat & 0xf
= 3) DROP TABLE Order_0_1ST
IF EXISTS (SELECT 1 FROM sysobjects WHERE id = object_id('dbo.Order_0_IL') AND sysstat & 0xf =
3) DROP TABLE Order_0_IL
IF EXISTS (SELECT 1 FROM sysobjects WHERE id = object_id('dbo.Order_0_IR') AND sysstat & 0xf =
3) DROP TABLE Order_0_IR

```



```

IF EXISTS (SELECT 1 FROM sysobjects WHERE id = object_id('dbo.Order_0_IRD') AND sysstat & 0xf
= 3) DROP TABLE Order_0_IRD
IF EXISTS (SELECT 1 FROM sysobjects WHERE id = object_id('dbo.Order_0_IND') AND sysstat & 0xf
= 3) DROP TABLE Order_0_IND
IF EXISTS (SELECT 1 FROM sysobjects WHERE id = object_id('dbo.Order_0_NFD') AND sysstat & 0xf
= 3) DROP TABLE Order_0_NFD
IF EXISTS (SELECT 1 FROM sysobjects WHERE id = object_id('dbo.Order_0_IRM') AND sysstat & 0xf
= 3) DROP TABLE Order_0_IRM
IF EXISTS (SELECT 1 FROM sysobjects WHERE id = object_id('dbo.Order_0_IDM') AND sysstat & 0xf
= 3) DROP TABLE Order_0_IDM
IF EXISTS (SELECT 1 FROM sysobjects WHERE id = object_id('dbo.Order_0_ILM') AND sysstat & 0xf
= 3) DROP TABLE Order_0_ILM
IF EXISTS (SELECT 1 FROM sysobjects WHERE id = object_id('dbo.Order_0_IMI') AND sysstat & 0xf
= 3) DROP TABLE Order_0_IMI

--#BLOCK_END# DropTemps

/*****/
-- Set join order for SQL Server
/*****/

--#BLOCK_BEGIN# ForcePlanOn

SET FORCEPLAN ON

--#BLOCK_END# ForcePlanOn

/*****/
-- Remove rows older than fact table - history can not be rewritten - only
-- the last date for an order can be changed. Note that we compare transtype's
-- because SHIP type transactions might occur at a later date and we don't want
-- those to interfere
--
-- Also, since the staging table may have multiple entries for a given order on
-- a single day - we assume that the list one inserted in the Staging table will
-- be used (since ikey is an IDENTITY column)
--
-- Note that a given ss_key must use the same Booking transtype for all of time,
-- otherwise the transtype_key
--
-- MFL: Mapped Filtered
/*****/

--#BLOCK_BEGIN# MakeMFL

SELECT
    s.*
INTO Order_0_MFL
FROM
    OrderStage_MAP s, bus_process b
WHERE
    ((s.date_key >= (SELECT MAX(date_key) FROM Order_0_A f WHERE
        s.iss = f.iss AND s.ss_key = f.ss_key AND
        s.transtype_key = f.transtype_key))
    OR NOT EXISTS (SELECT * FROM Order_0_A f WHERE
        s.iss = f.iss AND s.ss_key = f.ss_key AND
        s.transtype_key = f.transtype_key))
AND
    s.ikey = (SELECT MAX(t.ikey) FROM OrderStage_MAP t WHERE
        s.iss = t.iss AND
        s.ss_key = t.ss_key AND
        s.date_key = t.date_key AND
        t.process_key = b.process_key)
AND
    s.process_key = b.process_key AND b.process_name = 'LoadState'

--#BLOCK_END# MakeMFL

/*****/
-- Index MFL table for later queries

```

```

/*****
--#BLOCK_BEGIN# IndexMFL

EXEC('
CREATE INDEX XOrder_0_MFL ON Order_0_MFL
(
    iss, ss_key, date_key
)
')

--#BLOCK_END# IndexMFL

/*****
-- Get oldest state rows for each unique sskey
--
-- We need to treat the first entry for each order
-- in the staging table separately from all others, since
-- only the first entry needs to be compared with
-- already existing fact entry rows to create transactions.
-- All subsequent dates for that order in the Fact table
-- can be delta'd with other staging table entries - see the
-- section below on Pairwise deltas.
--
-- MFL should be indexed
--
-- 1ST: The first record for each iss, ss_key
*****/

--#BLOCK_BEGIN# Make1ST

SELECT
    s.*
INTO Order_0_1ST
FROM
    Order_0_MFL s
WHERE
    s.date_key = (SELECT MIN(date_key) FROM Order_0_MFL t WHERE
                  s.iss = t.iss AND s.ss_key = t.ss_key)

--#BLOCK_END# Make1ST

/*****
-- Index 1ST for later queries
*****/

--#BLOCK_BEGIN# Index1ST

EXEC('
CREATE UNIQUE INDEX XPKOrder_0_1ST ON Order_0_1ST
(
    iss, ss_key
)
')

--#BLOCK_END# Index1ST

/*****
-- Insert negative BOOKs for changed dim keys
--
-- This query will add up all existing Books and Loss's
-- for this order and the net facts will be cancelled out
-- with the old Dimension keys. Note that an invariant of this
-- procedure is that only one set of dimensions at a time
-- can have non-zero facts.
--
*****/

```

```

-- Fact table Should be indexed
--
-- HAVING Clause is needed to prevent changing of dimensions
-- on fully shipped order from causing a transaction - no sense
-- creating fact rows with all zero's in them
--
-- Note that we increment the sequence number just in case
-- this new transaction occurs on the same date as the last
-- existing one in the fact table - to avoid index errors
--
-- IL: InsertLost
/*****/

--#BLOCK_BEGIN# MakeIL

SELECT
    s.iss,
    s.ss_key,
    s.date_key,
    s.transtype_key,
    MAX(f.seq) + 1 seq
,    f.customerbillto_key
,    f.product_key
,    f.application_key
,    f.program_key
,    f.customershipto_key
,    f.territory_key
,    f.warehouse_key
,
    -SUM(f.net_price) net_price
,
    -SUM(f.number_units) number_units

INTO Order_0_IL
FROM
    Order_0_1ST s, Order_0_A f
WHERE
    s.iss = f.iss AND s.ss_key = f.ss_key
AND
    ((s.territory_key <> f.territory_key) OR
    (s.customershipto_key <> f.customershipto_key) OR
    (s.warehouse_key <> f.warehouse_key) OR
    (s.program_key <> f.program_key) OR
    (s.application_key <> f.application_key) OR
    (s.product_key <> f.product_key) OR
    (s.customerbillto_key <> f.customerbillto_key) )
GROUP BY
    s.iss,
    s.ss_key,
    s.date_key,
    s.transtype_key
,    f.customerbillto_key
,    f.product_key
,    f.application_key
,    f.program_key
,    f.customershipto_key
,    f.territory_key
,    f.warehouse_key

HAVING
    MIN(f.transtype_key) = s.transtype_key
AND
    (
    (SUM(f.net_price) <> 0)
OR
    (SUM(f.number_units) <> 0)
    )

--#BLOCK_END# MakeIL

/*****/
-- Index IL for later queries

```



```

-- Note also that the Left Outer join uses transtype_key
-- so that only the Bookings at the old value will be counted.
-- Whereas above for the negative transaction value
-- we want to include Shipments in our calculation, here
-- we only want to see how Booking Facts have changed.
--
-- Here again, only one Booking transaction type is supported
-- per ss_key
--
-- IRD: Insert Rebook delta
/*****

--#BLOCK_BEGIN# MakeIRD

SELECT
    s.iss,
    s.ss_key,
    s.date_key,
    s.transtype_key,
    l.seq + 2 seq
,    s.customerbillto_key
,    s.product_key
,    s.application_key
,    s.program_key
,    s.customershipto_key
,    s.territory_key
,    s.warehouse_key

,    MAX(s.net_price)-ISNULL(SUM(f.net_price) , 0) net_price
,    MAX(s.number_units)-ISNULL(SUM(f.number_units) , 0) number_units

INTO Order_0_IRD
FROM
    Order_0_IL l, Order_0_1ST s
    LEFT OUTER JOIN Order_0_A f ON s.iss = f.iss AND s.ss_key = f.ss_key AND
    s.transtype_key = f.transtype_key
WHERE
    l.iss = s.iss AND l.ss_key = s.ss_key

GROUP BY
    s.iss,
    s.ss_key,
    s.date_key,
    s.transtype_key,
    l.seq
,    s.customerbillto_key
,    s.product_key
,    s.application_key
,    s.program_key
,    s.customershipto_key
,    s.territory_key
,    s.warehouse_key

HAVING
    (ISNULL(SUM(f.net_price) , 0) <> MAX(s.net_price))
OR
    (ISNULL(SUM(f.number_units) , 0) <> MAX(s.number_units))

--#BLOCK_END# MakeIRD

/*****
-- Insert BOOKs for deltas with same dim keys OR for
-- brand new orders.
--
-- Note that we DON'T want to count Shipments
-- (so shipment ss_key's should be different from
-- order ss_keys) since we just want bookings to sum up
-- to whatever this transaction says they should be.
--
-- Fact table should be indexed
--

```

```

-- WHERE clause prevents double booking on changed
-- dimension - if we didn't use the NOT EXISTS clause
-- then this query would repeat the work of the last one
-- above - which we have already taken care of
--
-- HAVING clause ensures that multiple 0 records don't
-- get inserted whenever this procedure is run
--
-- Note that we increment the sequence number just in case
-- this new transaction occurs on the same date as the last
-- existing one in the fact table - to avoid index errors
--
-- IND: Insert New Delta
/*****

--#BLOCK_BEGIN# MakeIND

SELECT
    s.iss,
    s.ss_key,
    s.date_key,
    s.transtype_key,
    ISNULL(MAX(f.seq) , 0) + 1 seq
,
    s.customerbillto_key
,
    s.product_key
,
    s.application_key
,
    s.program_key
,
    s.customershipto_key
,
    s.territory_key
,
    s.warehouse_key

,
    MAX(s.net_price)-ISNULL(SUM(f.net_price) , 0) net_price
,
    MAX(s.number_units)-ISNULL(SUM(f.number_units) , 0) number_units

INTO Order_0_IND
FROM
    Order_0_1ST s LEFT OUTER JOIN Order_0_A f ON
        s.iss = f.iss AND s.ss_key = f.ss_key AND f.transtype_key = s.transtype_key
WHERE
    NOT EXISTS (SELECT * FROM Order_0_IL WHERE iss = s.iss AND ss_key = s.ss_key)

GROUP BY
    s.iss,
    s.ss_key,
    s.date_key,
    s.transtype_key
,
    s.customerbillto_key
,
    s.product_key
,
    s.application_key
,
    s.program_key
,
    s.customershipto_key
,
    s.territory_key
,
    s.warehouse_key

HAVING
    (ISNULL(SUM(f.net_price) , 0) <> MAX(s.net_price))
OR
    (ISNULL(SUM(f.number_units) , 0) <> MAX(s.number_units))

--#BLOCK_END# MakeIND

/*****
-- Form pairwise deltas for all rows except earliest for each sskey
--
-- Each row created in NFD will consist of two sequential entries from the
-- staing table. So if N enties for an order exist in MFL (after we have filtered
-- out same-date duplicates) then all the queries above will deal with the earliest entry,
whereas
-- all the queries below (including this one) will deal with the N-1 deltaing transactions
--
*****/

```

```

-- This query assumes that MFL will already have been filtered
-- to have a single record for each order/datekey
--
-- NFD: Not First Delta
/*****/

--#BLOCK_BEGIN# MakeNFD

SELECT
    s.iss siss, t.iss tiss
  , s.ss_key sss_key, t.ss_key tss_key
  , s.date_key sdate_key, t.date_key tdate_key
  , s.transtype_key stranstype_key, t.transtype_key ttranstype_key
  , s.customerbillto_key scustomerbillto_key, t.customerbillto_key tcustomerbillto_key
  , s.product_key sproduct_key, t.product_key tproduct_key
  , s.application_key sapplication_key, t.application_key tapplication_key
  , s.program_key sprogram_key, t.program_key tprogram_key
  , s.customershipto_key scustomershipto_key, t.customershipto_key tcustomershipto_key
  , s.territory_key sterriory_key, t.territory_key tterriory_key
  , s.warehouse_key swarehouse_key, t.warehouse_key twarehouse_key
  , s.net_price snet_price, t.net_price tnet_price
  , s.number_units snumber_units, t.number_units tnumber_units

INTO Order_0_NFD
FROM
    Order_0_MFL s, Order_0_MFL t
WHERE
    s.iss = t.iss AND s.ss_key = t.ss_key
AND
    s.date_key = (SELECT MAX(date_key) FROM Order_0_MFL u WHERE
        u.iss = s.iss AND u.ss_key = s.ss_key AND u.date_key < t.date_key)

--#BLOCK_END# MakeNFD

/*****/
--
-- Insert BOOKs for deltas with same dim keys
--
-- If the dimensions don't change then we create a
-- new booking order (as long as at least one of the facts
-- have changed)
--
-- IDM: Insert Delta More
--
/*****/

--#BLOCK_BEGIN# MakeIDM

SELECT
    tiss iss,
    tss_key ss_key,
    tdate_key date_key,
    ttranstype_key transtype_key,
    0 seq
  , tcustomerbillto_key customerbillto_key
  , tproduct_key product_key
  , tapplication_key application_key
  , tprogram_key program_key
  , tcustomershipto_key customershipto_key
  , tterriory_key territory_key
  , twarehouse_key warehouse_key

  , tnet_price-snet_price net_price
  , tnumber_units-snumber_units number_units

INTO Order_0_IDM
FROM
    Order_0_NFD d
WHERE

```

```

        (
            (steritory_key = tterritory_key) AND
            (scustomershipto_key = tcustomershipto_key) AND
            (swarehouse_key = twarehouse_key) AND
            (sprogram_key = tprogram_key) AND
            (sapplication_key = tapplication_key) AND
            (sproduct_key = tproduct_key) AND
            (scustomerbillto_key = tcustomerbillto_key)
        )
AND
        (
            (snet_price <> tnet_price)
OR
            (snumber_units <> tnumber_units)
        )

--#BLOCK_END# MakeIDM

/*****
--
-- Insert negative BOOKs for deltas with different dim keys
--
-- If one of the dimensions change then we first create a lose transaction for
-- all the previous facts. (Negate all the facts from the earlier of the two
-- transactions)
--
-- ILM: Insert Lost More
--
*****/

--#BLOCK_BEGIN# MakeILM

SELECT
    siss iss,
    sss_key ss_key,
    tdate_key date_key,
    stranstype_key transtype_key,
    0 seq
,
    scustomerbillto_key customerbillto_key
,
    sproduct_key product_key
,
    sapplication_key application_key
,
    sprogram_key program_key
,
    scustomershipto_key customershipto_key
,
    steritory_key territory_key
,
    swarehouse_key warehouse_key
,
    -snet_price net_price
,
    -snumber_units number_units

INTO Order_0_ILM
FROM
    Order_0_NFD d
WHERE
    (
        (steritory_key <> tterritory_key) OR
        (scustomershipto_key <> tcustomershipto_key) OR
        (swarehouse_key <> twarehouse_key) OR
        (sprogram_key <> tprogram_key) OR
        (sapplication_key <> tapplication_key) OR
        (sproduct_key <> tproduct_key) OR
        (scustomerbillto_key <> tcustomerbillto_key)
    )
AND
    (
        (snet_price <> 0)
OR
        (snumber_units <> 0)
    )

--#BLOCK_END# MakeILM

/*****/

```



```

--
-- Insert BOOKs for deltas with different dim keys
--
-- When a dimension key changes then we can simply insert all the new facts with the
-- new dimension keys
--
-- Note that seq = 1 here because this is the second transaction on this date for
-- this order.
--
-- IRM: Insert Rebook More
--
/*****/

--#BLOCK_BEGIN# MakeIRM

SELECT
    tiss iss,
    tss_key ss_key,
    tdate_key date_key,
    ttranstype_key transtype_key,
    1 seq
,    tcustomerbillto_key customerbillto_key
,    tproduct_key product_key
,    tapplication_key application_key
,    tprogram_key program_key
,    tcustomershipto_key customershipto_key
,    tterritory_key territory_key
,    twarehouse_key warehouse_key

,    tnet_price net_price
,    tnumber_units number_units

INTO Order_0_IRM
FROM
    Order_0_NFD d
WHERE
    (
        (sterritory_key <> tterritory_key) OR
        (scustomershipto_key <> tcustomershipto_key) OR
        (swarehouse_key <> twarehouse_key) OR
        (sprogram_key <> tprogram_key) OR
        (sapplication_key <> tapplication_key) OR
        (sproduct_key <> tproduct_key) OR
        (scustomerbillto_key <> tcustomerbillto_key)
    )
AND
    (
        (tnet_price <> 0)
    )
OR
    (
        (tnumber_units <> 0)
    )

--#BLOCK_END# MakeIRM

/*****/
-- Delete the output tables
/*****/

--#BLOCK_BEGIN# DropOutput

IF EXISTS (SELECT 1 FROM sysobjects WHERE id = object_id('dbo.Order_0_B') AND sysstat & 0xf =
3) DROP TABLE Order_0_B
IF EXISTS (SELECT 1 FROM sysobjects WHERE id = object_id('dbo.Order_0_INC') AND sysstat & 0xf
= 3) DROP TABLE Order_0_INC

--#BLOCK_END# DropOutput

/*****/
--Create FC table in case force close was

```

```

-- not run
/*****/

--#BLOCK_BEGIN# MakeFC

DECLARE @fc_exists INT

SELECT @fc_exists = (
SELECT COUNT(1)

FROM sysobjects
WHERE
id = object_id('dbo.Order_0_FC') AND sysstat & 0xf = 3
)

IF (@fc_exists = 0)
EXEC('

SELECT
*
INTO Order_0_FC
FROM
    Order_0_A
WHERE
    1=0
')

--#BLOCK_END# MakeFC

/*****/
-- Create the incremental table
/*****/

--#BLOCK_BEGIN# MakeINC

SELECT
*
INTO Order_0_INC
FROM Order_0_TIN UNION ALL
SELECT * FROM Order_0_IL UNION ALL
SELECT * FROM Order_0_IR UNION ALL
SELECT * FROM Order_0_IRD UNION ALL
SELECT * FROM Order_0_IND UNION ALL
SELECT * FROM Order_0_IRM UNION ALL
SELECT * FROM Order_0_ILM UNION ALL
SELECT * FROM Order_0_FC UNION ALL
SELECT * FROM Order_0_IDM

--#BLOCK_END# MakeINC

/*****/
-- CR158: We want to load _IMI table and still keep the non-descending
-- order so that the clustered index on a fact table can be created
-- without sorting. This way can speed up significantly in creating a
-- clustered index on a very large already sorted fact table.
/*****/

--#BLOCK_BEGIN# MakeIMI

SELECT
*
INTO Order_0_IMI
FROM Order_0_A
WHERE date_key >= (SELECT MIN(date key) FROM Order 0 INC)

```

```

UNION ALL
SELECT * FROM Order_0_INC
ORDER BY
    date_key
    , customerbillto_key
    , product_key
    , application_key
    , program_key
    , customershipto_key
    , territory_key
    , warehouse_key

--#BLOCK_END# MakeIMI

/*****
-- Create the new fact table and incremental table
--
-- Note that transaction tables must be built before
-- these statements are run
*****/

--#BLOCK_BEGIN# MakeNewFact

SELECT *
INTO Order_0_B
FROM Order_0_A s
WHERE s.date_key < (SELECT MIN(date_key) FROM Order_0_INC)
UNION ALL
SELECT * FROM Order_0_IMI

--#BLOCK_END# MakeNewFact

/*****
-- Count processed, inserted rows
*****/

--#BLOCK_BEGIN# SPResults

DECLARE @count_INC INT

BEGIN

SELECT @count_INC = (
SELECT COUNT(1)

FROM Order_0_INC
)

INSERT INTO adaptive_template_profile (token_name, number_rows)
SELECT 'PROCESSED', COUNT(1) FROM Order_0_MFL

INSERT INTO adaptive_template_profile (token_name, number_rows)
SELECT 'INSERTED', @count_INC - COUNT(1) FROM Order_0_TIN

END

--#BLOCK_END# SPResults

/*****
-- Set join order for SQL Server
*****/

--#BLOCK_BEGIN# ForcePlanOff

SET FORCEPLAN OFF

--#BLOCK_END# ForcePlanOff

/*****

```

```

-- Drop temp tables and TXN and TIN table
/*****

--#BLOCK_BEGIN# DropTempsAfter

IF EXISTS (SELECT 1 FROM sysobjects WHERE id = object_id('dbo.Order_0_TIN') AND sysstat & 0xf
= 3) DROP TABLE Order_0_TIN
IF EXISTS (SELECT 1 FROM sysobjects WHERE id = object_id('dbo.Order_0_TMI') AND sysstat & 0xf
= 3) DROP TABLE Order_0_TMI
IF EXISTS (SELECT 1 FROM sysobjects WHERE id = object_id('dbo.Order_0_FC') AND sysstat & 0xf =
3) DROP TABLE Order_0_FC
IF EXISTS (SELECT 1 FROM sysobjects WHERE id = object_id('dbo.Order_0_TXN') AND sysstat & 0xf
= 3) DROP TABLE Order_0_TXN
IF EXISTS (SELECT 1 FROM sysobjects WHERE id = object_id('dbo.Concat_MFL') AND sysstat & 0xf =
3) DROP TABLE Concat_MFL
IF EXISTS (SELECT 1 FROM sysobjects WHERE id = object_id('dbo.Order_0_1ST') AND sysstat & 0xf
= 3) DROP TABLE Order_0_1ST
IF EXISTS (SELECT 1 FROM sysobjects WHERE id = object_id('dbo.Order_0_IL') AND sysstat & 0xf =
3) DROP TABLE Order_0_IL
IF EXISTS (SELECT 1 FROM sysobjects WHERE id = object_id('dbo.Order_0_IR') AND sysstat & 0xf =
3) DROP TABLE Order_0_IR
IF EXISTS (SELECT 1 FROM sysobjects WHERE id = object_id('dbo.Order_0_IRD') AND sysstat & 0xf
= 3) DROP TABLE Order_0_IRD
IF EXISTS (SELECT 1 FROM sysobjects WHERE id = object_id('dbo.Order_0_IND') AND sysstat & 0xf
= 3) DROP TABLE Order_0_IND
IF EXISTS (SELECT 1 FROM sysobjects WHERE id = object_id('dbo.Order_0_NFD') AND sysstat & 0xf
= 3) DROP TABLE Order_0_NFD
IF EXISTS (SELECT 1 FROM sysobjects WHERE id = object_id('dbo.Order_0_IRM') AND sysstat & 0xf
= 3) DROP TABLE Order_0_IRM
IF EXISTS (SELECT 1 FROM sysobjects WHERE id = object_id('dbo.Order_0_IDM') AND sysstat & 0xf
= 3) DROP TABLE Order_0_IDM
IF EXISTS (SELECT 1 FROM sysobjects WHERE id = object_id('dbo.Order_0_ILM') AND sysstat & 0xf
= 3) DROP TABLE Order_0_ILM
IF EXISTS (SELECT 1 FROM sysobjects WHERE id = object_id('dbo.Order_0_IMI') AND sysstat & 0xf
= 3) DROP TABLE Order_0_IMI

--#BLOCK_END# DropTempsAfter

--#TEMPLATE_END# load_state
--#TEMPLATE_BEGIN# load_trans

/*****
--
-- Copyright * 1997, Epiphany Marketing Software, Inc. All Rights Reserved.
--
-- load_trans
--
-- Move transaction-like staging data into Fact table - create a temp
-- table with TXN extension that has all old rows along with new rows.
-- Also produce a TIN (TXN INC) table that has only the new rows
--
-- Note that the new table will also include all existing rows from
-- the Fact table.
--
/*****
/*****
-- Delete output tables
--
-- Output table is called TXN and includes old and new rows
--
-- Also, leave around _TIN as incremental table from this
-- procedure
--
-- We also create a table called _TMI which contains all the
-- _TIN records plus the records of overlapping period from the
-- old existing fact table.
/*****

```

```

--#BLOCK_BEGIN# RemoveOutput

IF EXISTS (SELECT 1 FROM sysobjects WHERE id = object_id('dbo.Order_0_TXN') AND sysstat & 0xf
= 3) DROP TABLE Order_0_TXN
IF EXISTS (SELECT 1 FROM sysobjects WHERE id = object_id('dbo.Order_0_TMI') AND sysstat & 0xf
= 3) DROP TABLE Order_0_TMI
IF EXISTS (SELECT 1 FROM sysobjects WHERE id = object_id('dbo.Order_0_TIN') AND sysstat & 0xf
= 3) DROP TABLE Order_0_TIN

--#BLOCK_END# RemoveOutput

/*****
-- Set join order for SQL Server
*****/

--#BLOCK_BEGIN# ForcePlanOn

SET FORCEPLAN ON

--#BLOCK_END# ForcePlanOn

/*****
-- Remove stuff already in fact table
--
-- Note that currently this filter implies that once a transactional
-- fact entry is made it cannot be changed - and no further fact
-- entries on that date or any previous date can be made either
*****/

--#BLOCK_BEGIN# CreateTIN

SELECT
    s.iss,
    s.ss_key,
    s.date_key,
    s.transtype_key,
    s.ikey seq
,
    s.customerbillto_key
,
    s.product_key
,
    s.application_key
,
    s.program_key
,
    s.customershipto_key
,
    s.territory_key
,
    s.warehouse_key
,
    s.net_price
,
    s.number_units

INTO Order_0_TIN
FROM
    OrderStage_MAP s, bus_process b
WHERE
    NOT EXISTS (SELECT * FROM Order_0_A f WHERE
        s.iss = f.iss AND
        s.ss_key = f.ss_key AND
        f.date_key >= s.date_key)
AND
    (
        (s.net_price <> 0)
    OR
        (s.number_units <> 0)
    )
AND
    s.process_key = b.process_key AND b.process_name = 'LoadTrans'

--#BLOCK_END# CreateTIN

/*****
-- Set join order for SQL Server
*****/

```

```

--#BLOCK_BEGIN# ForcePlanOff

SET FORCEPLAN OFF

--#BLOCK_END# ForcePlanOff

/*****
-- CR158: We want to load _TMI table and still keep the non-descending
-- order so that the clustered index on a fact table can be created
-- without sorting. This way can speed up significantly in creating a
-- clustered index on a very large already sorted fact table.
*****/

--#BLOCK_BEGIN# CreateTMI

SELECT
    *
INTO Order_0_TMI
FROM
    Order_0_A
WHERE
    date_key >= (SELECT MAX(date_key) FROM Order_0_TIN)
UNION ALL
SELECT
    *
FROM
    Order_0_TIN
ORDER BY
    date_key
    , customerbillto_key
    , product_key
    , application_key
    , program_key
    , customershipto_key
    , territory_key
    , warehouse_key

--#BLOCK_END# CreateTMI

/*****
-- Insert everything into the new fact table
*****/

--#BLOCK_BEGIN# CreateTXN

SELECT
    *
INTO Order_0_TXN
FROM
    Order_0_A s
WHERE s.date_key < (SELECT MAX(date_key) FROM Order_0_TIN)
UNION ALL
SELECT
    *
FROM
    Order_0_TMI f

--#BLOCK_END# CreateTXN

/*****
-- Count inserted data and put results into communication table
*****/

--#BLOCK_BEGIN# SPResults

BEGIN

```

```

INSERT INTO adaptive_template_profile (token_name, number_rows)
SELECT 'PROCESSED', COUNT(1) FROM OrderStage_MAP

INSERT INTO adaptive_template_profile (token_name, number_rows)
SELECT 'INSERTED', COUNT(1) FROM Order_0_TIN

END

--#BLOCK_END# SPResults
--#TEMPLATE_END# load_trans
--#TEMPLATE_BEGIN# index_fact

/*****/
--
-- Copyright * 1997, Epiphany Marketing Software, Inc. All Rights Reserved.
--
-- Post processing after an extraction run
--
-- Reindex fact tables
-- CR158: added WITH SORTED_DATA in creating cluster index on fact table
--
-- Remove any temp tables generated during the extraction
--
/*****/

/*****/
-- Primary key index the fact table
/*****/

--#BLOCK_BEGIN# PKIndexFact

EXEC('

CREATE UNIQUE INDEX XPKOrder_0_B ON Order_0_B
(
    iss , ss_key , date_key , transtype_key , seq
)
')

--#BLOCK_END# PKIndexFact

/*****/
-- Inversion index the fact table
/*****/

--#BLOCK_BEGIN# IEIndexFact

EXEC('

CREATE CLUSTERED INDEX XIEKOrder_0_B ON Order_0_B
(
    date_key
,   customerbillto_key
,   product_key
,   application_key
,   program_key
,   customershipto_key
,   territory_key
,   warehouse_key
) WITH SORTED_DATA
')

--#BLOCK_END# IEIndexFact

```

```

/*****
-- Remove any mapped tables
/*****/

--#BLOCK_BEGIN# RemoveTemps

IF EXISTS (SELECT 1 FROM sysobjects WHERE id = object_id('dbo.OrderStage_MAP') AND sysstat & 0xf = 3) DROP TABLE OrderStage_MAP

--#BLOCK_END# RemoveTemps

--#TEMPLATE_END# index_fact
--#TEMPLATE_BEGIN# ren_trans
/*****/
--
-- Copyright * 1997, Epiphany Marketing Software, Inc. All Rights Reserved.
--
-- ren_trans
--
-- Epiphany Marketing Software, 1997
--
-- Simply change the name of the transaction new table to the
-- actual fact table name - used for Fact tables that don't have
-- any stored procedure other than load_trans attached to them
--
/*****/

/*****/
-- Delete the output tables
/*****/

--#BLOCK_BEGIN# RemoveOutput

IF EXISTS (SELECT 1 FROM sysobjects WHERE id = object_id('dbo.Order_0_B') AND sysstat & 0xf = 3) DROP TABLE Order_0_B
IF EXISTS (SELECT 1 FROM sysobjects WHERE id = object_id('dbo.Order_0_INC') AND sysstat & 0xf = 3) DROP TABLE Order_0_INC

--#BLOCK_END# RemoveOutput

/*****/
-- Move all transaction rows into the correct new fact table
-- name. Note that we would use sp_rename, except it
-- doesn't work with DB name prefixes
--
-- TBD: Rename instead of re-select
/*****/

--#BLOCK_BEGIN# BuildNewFact

SELECT
    *
INTO Order_0_B
FROM
    Order_0_TXN

--#BLOCK_END# BuildNewFact

/*****/
-- Preserve incremental table
/*****/

--#BLOCK_BEGIN# BuildIncremental

```



```

SELECT
    *
INTO Order_0_INC
FROM
    Order_0_TIN

--#BLOCK_END# BuildIncremental

/*****/
-- Count inserted data and put results into communication table
/*****/

--#BLOCK_BEGIN# SPResults

BEGIN

INSERT INTO adaptive_template_profile (token_name, number_rows)
SELECT 'PROCESSED', COUNT(1) FROM Order_0_TXN

INSERT INTO adaptive_template_profile (token_name, number_rows)
SELECT 'INSERTED', COUNT(1) FROM Order_0_TXN

END

--#BLOCK_END# SPResults

/*****/
-- Remove temp tables
/*****/

--#BLOCK_BEGIN# RemoveTemps

IF EXISTS (SELECT 1 FROM sysobjects WHERE id = object_id('dbo.Order_0_TXN') AND sysstat & 0xf
= 3) DROP TABLE Order_0_TXN
IF EXISTS (SELECT 1 FROM sysobjects WHERE id = object_id('dbo.Order_0_TIN') AND sysstat & 0xf
= 3) DROP TABLE Order_0_TIN
IF EXISTS (SELECT 1 FROM sysobjects WHERE id = object_id('dbo.Order_0_TMI') AND sysstat & 0xf
= 3) DROP TABLE Order_0_TMI

--#BLOCK_END# RemoveTemps

--#TEMPLATE_END# ren_trans

--#TEMPLATE_BEGIN# map_keys

/*****/
--
-- Copyright * 1997, Epiphany Marketing Software, Inc. All Rights Reserved.
--
-- map_keys
--
-- Epiphany Marketing Software
--
-- Map dimension keys from Staging table and report
-- on unjoined rows
--
/*****/

/*****/
-- Remove output table
/*****/

--#BLOCK_BEGIN# DropTemp

IF EXISTS (SELECT 1 FROM sysobjects WHERE id = object_id('dbo.OrderStage_MAP') AND sysstat &
0xf = 3) DROP TABLE OrderStage_MAP

```

```

--#BLOCK_END# DropTemp

/*****/
-- Set join order for SQL Server
/*****/

--#BLOCK_BEGIN# ForcePlanOn

SET FORCEPLAN ON

--#BLOCK_END# ForcePlanOn

/*****/
-- Map dimension keys via Inner joins
/*****/

--#BLOCK_BEGIN# MapAll

SELECT
    s.iss,
    s.ss_key,
    s.date_key,
    s.transtype_key,
    s.ikey,
    s.process_key

,
    m_04.program_key program_key
,
    m_03.application_key application_key
,
    m_06.territory_key territory_key
,
    m_02.product_key product_key
,
    m_05.customer_key customershipto_key
,
    m_01.customer_key customerbillto_key
,
    m_07.warehouse_key warehouse_key

,
    s.net_price
,
    s.number_units

INTO OrderStage_MAP
FROM
    OrderStage s
    ProgramMap_B m_04 (index = 1)
    ApplicationMap_B m_03 (index = 1)
    TerritoryMap_B m_06 (index = 1)
    ProductMap_B m_02 (index = 1)
    CustomerMap_B m_05 (index = 1)
    CustomerMap_B m_01 (index = 1)
    WarehouseMap_B m_07 (index = 1)

WHERE 1=1
AND m_04.iss = s.iss AND m_04.program_sskey = s.program_sskey
AND m_03.iss = s.iss AND m_03.application_sskey = s.application_sskey
AND m_06.iss = s.iss AND m_06.territory_sskey = s.territory_sskey
AND m_02.iss = s.iss AND m_02.product_sskey = s.product_sskey
AND m_05.iss = s.iss AND m_05.customer_sskey = s.customershipto_sskey
AND m_01.iss = s.iss AND m_01.customer_sskey = s.customerbillto_sskey
AND m_07.iss = s.iss AND m_07.warehouse_sskey = s.warehouse_sskey

--#BLOCK_END# MapAll

/*****/
-- Set join order for SQL Server
/*****/

--#BLOCK_BEGIN# ForcePlanOff

SET FORCEPLAN OFF

--#BLOCK_END# ForcePlanOff

```

```

/*****
-- Look for unjoined data, Report on processed rows
*****/

--#BLOCK_BEGIN# SPResults

DECLARE @unjoined INT
DECLARE @processed INT

BEGIN

SELECT @processed = (
SELECT COUNT(1)

FROM OrderStage
)

SELECT @unjoined = (
SELECT @processed - COUNT(1)

FROM OrderStage_MAP
)

INSERT INTO adaptive_template_profile (token_name, number_rows)
SELECT 'UNJOINED', @unjoined

INSERT INTO adaptive_template_profile (token_name, number_rows)
SELECT 'PROCESSED', @processed

INSERT INTO adaptive_template_profile (token_name, number_rows)
SELECT 'INSERTED', @processed - @unjoined

END

--#BLOCK_END# SPResults

/*****
-- Index this temp table
*****/

--#BLOCK_BEGIN# IndexMap

EXEC('
CREATE INDEX XOrderStage_MAP ON OrderStage_MAP
(
    iss, ss_key, date_key, ikey
)
')

--#BLOCK_END# IndexMap

--#TEMPLATE_END# map_keys
--#TEMPLATE_BEGIN# upd_unj

/*****
--
-- Copyright * 1997, Epiphany Marketing Software, Inc. All Rights Reserved
--
-- upd_unj
--
-- Epiphany Marketing Software
--
-- Update all dimension keys to 'UNKNOWN' in staging table
-- where referential integrity fails
--
*****/

```

```

/*****
-- Count the number of rows to update in the staging table - that is, those
-- that have at least one Foreign key where referential integrity fails
*****/

--#BLOCK_BEGIN# CountUnj

BEGIN

INSERT INTO adaptive_template_profile (token_name, number_rows)
SELECT 'PROCESSED', COUNT(1) FROM OrderStage

INSERT INTO adaptive_template_profile (token_name, number_rows)
SELECT 'MODIFIED', COUNT(1)
FROM
    OrderStage s
WHERE 1=0
OR NOT EXISTS (SELECT 1 FROM ProgramMap_B m_04 WHERE m_04.iss = s.iss AND m_04.program_skey =
program_skey)
OR NOT EXISTS (SELECT 1 FROM ApplicationMap_B m_03 WHERE m_03.iss = s.iss AND
m_03.application_skey = application_skey)
OR NOT EXISTS (SELECT 1 FROM TerritoryMap_B m_06 WHERE m_06.iss = s.iss AND
m_06.territory_skey = territory_skey)
OR NOT EXISTS (SELECT 1 FROM ProductMap_B m_02 WHERE m_02.iss = s.iss AND m_02.product_skey =
product_skey)
OR NOT EXISTS (SELECT 1 FROM CustomerMap_B m_05 WHERE m_05.iss = s.iss AND m_05.customer_skey
= customershipto_skey)
OR NOT EXISTS (SELECT 1 FROM CustomerMap_B m_01 WHERE m_01.iss = s.iss AND m_01.customer_skey
= customerbillto_skey)
OR NOT EXISTS (SELECT 1 FROM WarehouseMap_B m_07 WHERE m_07.iss = s.iss AND
m_07.warehouse_skey = warehouse_skey)

END

--#BLOCK_END# CountUnj

/*****
-- Update foreign keys where referential integrity fails
*****/

--#BLOCK_BEGIN# UpdateUnjprogram_skey

UPDATE OrderStage SET program_skey = 'UNKNOWN'
WHERE NOT EXISTS (SELECT 1 FROM ProgramMap_B m
WHERE m.iss = OrderStage.iss AND m.program_skey = OrderStage.program_skey)

--#BLOCK_END# UpdateUnjprogram_skey

--#BLOCK_BEGIN# UpdateUnjapplication_skey

UPDATE OrderStage SET application_skey = 'UNKNOWN'
WHERE NOT EXISTS (SELECT 1 FROM ApplicationMap_B m
WHERE m.iss = OrderStage.iss AND m.application_skey = OrderStage.application_skey)

--#BLOCK_END# UpdateUnjapplication_skey

--#BLOCK_BEGIN# UpdateUnjterritory_skey

UPDATE OrderStage SET territory_skey = 'UNKNOWN'
WHERE NOT EXISTS (SELECT 1 FROM TerritoryMap_B m
WHERE m.iss = OrderStage.iss AND m.territory_skey = OrderStage.territory_skey)

--#BLOCK_END# UpdateUnjterritory_skey

--#BLOCK_BEGIN# UpdateUnjproduct_skey

UPDATE OrderStage SET product_skey = 'UNKNOWN'
WHERE NOT EXISTS (SELECT 1 FROM ProductMap_B m
WHERE m.iss = OrderStage.iss AND m.product_skey = OrderStage.product_skey)

--#BLOCK_END# UpdateUnjproduct_skey

```

```

--#BLOCK_BEGIN# UpdateUnjcustomershipto_sskey

UPDATE OrderStage SET customershipto_sskey = 'UNKNOWN'
WHERE NOT EXISTS (SELECT 1 FROM CustomerMap_B m
WHERE m.iss = OrderStage.iss AND m.customer_sskey = OrderStage.customershipto_sskey)

--#BLOCK_END# UpdateUnjcustomershipto_sskey


--#BLOCK_BEGIN# UpdateUnjcustomerbillto_sskey

UPDATE OrderStage SET customerbillto_sskey = 'UNKNOWN'
WHERE NOT EXISTS (SELECT 1 FROM CustomerMap_B m
WHERE m.iss = OrderStage.iss AND m.customer_sskey = OrderStage.customerbillto_sskey)

--#BLOCK_END# UpdateUnjcustomerbillto_sskey


--#BLOCK_BEGIN# UpdateUnjwarehouse_sskey

UPDATE OrderStage SET warehouse_sskey = 'UNKNOWN'
WHERE NOT EXISTS (SELECT 1 FROM WarehouseMap_B m
WHERE m.iss = OrderStage.iss AND m.warehouse_sskey = OrderStage.warehouse_sskey)

--#BLOCK_END# UpdateUnjwarehouse_sskey


--#TEMPLATE_END# upd_unj

```

Note, additional semantic types and adaptive templates can be imported into the system 100.




Figure 2









FIGURE 3



Runtime

005



FIGURES

fact_tbl 304

fact_tbl	key
constellation_key	(FK)
building_key	(FK)
building_manages_flag	
truncate_stage_flag	
cleanse_flag	
description	

fact_col 310

fact_col	key
fact_tbl_key	(FK)
fact_col_name	
physical_type	(FK)
fact_agg_operator	(FK)
fact_col_nbr	(FK)
cleanse_flag	
description	

backlog_type 638

backlog_type	
backlog_type	

measure_unit 624

measure_unit	
measure_unit	

measure_mapping 622

measure_mapping	key
measure_key	(FK)
lookup_key	(FK)
combination_id	




FIGURE 6




Figure 7




Figure 8

0000749-050600




Figure 11

The screenshot displays the Epicenter Enterprise Manager application. The main window shows a tree view of the system structure, including Servers, yeti, Epicenters, and epitest. Under epitest, the Base Dimensions are listed: Account, Application, CostCenter, Customer, Date, Entity, FormatPos, GLTranstype, Product, Program, Project, SubAccount, Territory, and Transtype. The Date dimension is selected, and its configuration window is open. The Base Name is set to Date, and the Semantic Type is set to Date. The Description is 'Built-in time dimension'. The Dimension Column window is also open, showing the list of available fields for the Date dimension. The fields include: BASE, cq_and_cy_name, cq_name, cy_name, date_key, day_cq_begin, day_cq_end, day_cy_begin, day_cy_end, day_fq_begin, day_fq_end, day_fy_begin, and day_fy_end. The Dimension Column window is titled 'Dimension Column: Date.day_cq_end' and has checkboxes for 'Group By Field', 'Primary Key Field', and 'Time Navigation Field'. The Description field is empty. The OK and Cancel buttons are at the bottom.

Enterprise Manager Interface 192

Base Dimension Window 900

Dimension Column Window 1000

H:\PRIVATE\CLIENT\20308 Epiphany\701 MetaSchemas - EpiCenter System\Figure 12 datespecialcolumnmdef vsd




Figure 13




Figure 14




Figure 15

0007343-020603




Figure 16

Figure 1 consists of 12 histograms arranged horizontally, labeled x_1 through x_{12} . Each histogram shows the frequency (count) of values for x_k ranging from 0 to 10. The distributions are approximately normal, centered around 5. The peak count for each distribution is as follows:

k	Peak Count
1	10
2	12
3	14
4	16
5	18
6	20
7	22
8	24
9	26
10	28
11	30
12	32




Figure 17

Enterprise
Manager
Interface 192

Job Definition
- Window
1700

Job Steps
1810




Figure 18




Figure 20




Figure 21

2007-07-24 09:00




Figure 22

Enterprise
Manager
Interface 192

SQL Statement
Window
2200

Figure 23




Figure 24

20080507 09:40:50




Figure 25




Figure 26




Figure 27




Figure 28

The screenshot displays the Epicenter Enterprise Manager interface. The main window shows a tree view of the system structure, including 'yeti', 'Epicenters', 'epitest', and 'Base Dimensions'. The 'Base Dimensions' list includes Account, Application, CostCenter, Customer, Date, Entity, FormatPos, GLTranstype, Product, Program, Project, SubAccount, and Territory.

Two windows are open in the foreground:

- Configuration Window 2900:** This window is titled 'Configuration' and contains a 'Transaction Types' tab. It displays a table of transaction types with columns for Name, Key, and Description.
- Transaction Types 2910:** This window is titled 'Transaction Types' and shows a detailed view of a transaction type. It includes fields for Name, Key, and Description, along with buttons for Add Type, Remove, Update, and Close.

Name	Key	Description
BOOK	1	Normal Bookings - positive
BOOK_RETURN	2	Returned Bookings - negative
LOST	3	De-bookings - for internal use
LEAD_LOST	4	Indicates that a pipeline lead is lost
SHIP	101	Normal Shipment - negative
SHIP_RETURN	102	Returned Shipment - positive
SHIP_ADJUST	103	An adjusting shipment, internal use
SHIP_RADJ	104	An adjusting return shipment, internal use
GL	105	A general ledger entry, internal use
INV_ADJUST	201	An Inventory adjusting entry, internal use

The Transaction Types window shows the following details:

- Name: BOOK
- Key: 1
- Description: Normal Bookings - positively signed

H:\PRIVATE\CLIENT\20308 Epiphany\701 MetaSchemas - EpiCenter System\Figure29 transtypedef.vsd

- Enterprise Manager Interface 192
- User Interface Definition Window 3000




Figure 30

The screenshot displays the Epicenter Enterprise Manager application. The main window is titled "Epicenter Enterprise Manager" and shows a hierarchical tree structure under the "yeti" node, including "Epicenters", "epitest", "Base Dimensions", "Account", "Application", and "CostCenter". A callout box labeled "Enterprise Manager Interface 192" points to the top of the window. Another callout box labeled "User Interface Definition Window 3000" points to the "Base Dimensions" node. Below the main window, a "Web Builder - yeti\epimm" window is visible, showing a "Executive [Type: clarity / Constellation: Sales]" report. This report includes a table with columns for "Fiscal Year", "Fiscal Quarter", "Sales", and "Revenue". The table data shows sales for 1995, 1996, 1997, and 1998, with a total revenue of 1,000,000. A callout box labeled "Table 1" points to the table data.

H:\PRIVATE\CLIENT\20308 Epiphany\701 MetaSchemas - EpiCenter System\Figure31 ticksheetfilterdef.vsd




Figure 32

Browser 182

Query/Results Interface 184

Query Form 3200

H:\PRIVATE\CLIENT\20308 Epiphany\701 MetaSchemas - EpiCenter System\Figure34 salesticketsheet.vsd

2000 04 24 10:00




Figure 35

20308 - 04/24/00




Figure 36

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application) PATENT APPLICATION
)
Inventor(s): Craig David Weissman, Gregory Vincent)
Walsh, Eliot Leonard Wegbreit)
)
Serial No.: Not Assigned)
)
Filed: Filed Herewith)
)
Title: *Method and Apparatus for Creating a*)
Well-Formed Database System Using a)
Computer)
_____)

DECLARATION FOR PATENT APPLICATION

As a below named inventor, I hereby declare that my residence, post office address and citizenship are as stated below next to my name; I believe that I am the original, first and sole inventor (if one name is listed below), first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

**METHOD AND APPARATUS FOR CREATING A WELL-FORMED
DATABASE SYSTEM USING A COMPUTER**

the specification of which (check applicable ones):

- X is attached hereto;
_____ was filed with the above-identified "Filed" date and "Serial No."
_____ was amended on (or amended through) .
_____ The present application is a utility application of Prior Provisional Application, Application No. _____, filed: _____ and may be considered to disclose and claim subject matter in addition to that disclosed in the Prior Application, and I hereby claim the benefit of 35 U.S.C. Section 119(e).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment(s) referred to above. I acknowledge the duty to disclose information which is material to the examination of the application in accordance with Title 37, Code of Federal Regulations, §1.56, including information which became available between the filing date of the Prior Application and the national or PCT international filing date of the present application.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true, and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under §1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

(1) Full name of sole
or first inventor: CRAIG DAVID WEISSMAN

(1) Residence: 735 Old County Road, Apartment C
Belmont, CA 94002

(1) Post Office Address: Same As Above

(1) Citizenship: United States

(1) Inventor's signature: 


(1) Date: 5/5/98

(2) Full name of second
joint inventor: GREGORY VINCENT WALSH

(2) Residence: 16000 Montebello Road
Cupertino, CA 95014

(2) Post Office Address: Same As Above

(2) Citizenship: United States

(2) Inventor's signature: 

(2) Date: 5/5/98

(3) Full name of third
joint inventor: ELIOT LEONARD WEGBREIT

(3) Residence: 1516 Dana Avenue
Palo Alto, CA 94303

(3) Post Office Address: Same As Above

(3) Citizenship: United States

(3) Inventor's signature: 

(3) Date: 5/5/98

**SECTION 1.56. DUTY TO DISCLOSE INFORMATION
MATERIAL TO PATENTABILITY**

(a) A patent by its very nature is affected with a public interest. The public interest is best served, and the most effective patent examination occurs when, at the time an application is being examined, the Office is aware of and evaluates the teachings of all information material to patentability. Each individual associated with the filing and prosecution of a patent application has a duty of candor and good faith in dealing with the Office, which includes a duty to disclose to the Office all information known to that individual to be material to patentability as defined in this section. The duty to disclose information exists with respect to each pending claim until the claim is canceled or withdrawn from consideration, or the application becomes abandoned. Information material to the patentability of a claim that is canceled or withdrawn from consideration need not be submitted if the information is not material to the patentability of any claim remaining under consideration in the application. There is no duty to submit information which is not material to the patentability of any existing claim. The duty to disclose all information known to be material to patentability is deemed to be satisfied if all information known to be material to patentability of any claim issued in a patent was cited by the Office or submitted to the Office in the manner prescribed by §§1.97(b)-(d) and 1.98.* However, no patent will be granted on an application in connection with which fraud on the Office was practiced or attempted or the duty of disclosure was violated through bad faith or intentional misconduct. The Office encourages applicants to carefully examine:

- (1) prior art cited in search reports of a foreign patent office in a counterpart application, and
- (2) the closest information over which individuals associated with the filing or prosecution of a patent application believe any pending claim patentably defines, to make sure that any material information contained therein is disclosed to the Office.

(b) Under this section, information is material to patentability when it is not cumulative to information already of record or being made of record in the application, and

- (1) It establishes, by itself or in combination with other information, a prima facie case of unpatentability of a claim; or
- (2) It refutes, or is inconsistent with, a position the applicant takes in:
 - (i) Opposing an argument of unpatentability relied on by the Office; or
 - (ii) Asserting an argument of patentability.

A prima facie case of unpatentability is established when the information compels a conclusion that a claim is unpatentable under the preponderance of evidence, burden-of-proof standard, giving each term in the claim its broadest reasonable construction consistent with the specification, and before any consideration is given to evidence which may be submitted in an attempt to establish a contrary conclusion of patentability.

(c) Individuals associated with the filing or prosecution of a patent application within the meaning of this section are:

- (1) Each inventor named in the application;
- (2) Each attorney or agent who prepares or prosecutes the application; and
- (3) Every other person who is substantively involved in the preparation or prosecution of the application and who is associated with the inventor, with the assignee or with anyone to whom there is an obligation to assign the application.

(d) Individuals other than the attorney, agent or inventor may comply with this section by disclosing information to the attorney, agent, or inventor.

* §§1.97(b)-(d) and 1.98 relate to the timing and manner in which information is to be submitted to the Office.
